

November 12, 2015

Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYNTHETIC BARRIER FLUIDS

BARRIER FLUID SERIES

Summit Barrier Fluid Series lubricants are formulated from the highest quality synthetic base stocks and fortified with additives to provide a non-reactive, oxidatively stable fluid for seal service over an extremely wide temperature range. These fluids have excellent low temperature fluidity and high temperature stability properties as well as the ability to efficiently transfer heat, and keep the seal face cool. Summit's Barrier Fluid Series lubricants do not contain components that are known catalyst poisons, and are compatible with most commonly used seal materials. Barrier Fluid 5 is environmentally safe and readily biodegradable according to OECD 301B.

Barrier Fluid Series products are NSF Registered and meet USDA 1998 (H1) guidelines (lubricants with incidental food contact) for use in food plants. Do not add directly to food. Summit is an ISO 21469 certified facility.

Physical Properties

PRODUCTS	5	17	30	46	68
Viscosity					
@ 40°C, cSt	5.1	16.9	30.5	46.0	66.0
@ 100°C, cSt	1.7	3.9	5.9	7.8	10.0
Viscosity Index	-	127	141	139	136
Pour Point, °F (°C)	-103(-75)	-99(-73)	-78(-61)	-42(-41)	-71(-57)
Flash Point, °F (°C)	305(152)	425(219)	460(238)	495(257)	510(266)
Specific Gravity	0.798	0.820	0.827	0.833	0.835
Copper Strip Corrosion	1A	1A	1A	1A	1A
Emulsion Tendency	40/40/0 (10)	40/40/0 (10)	40/40/0 (10)	40/40/0 (10)	40/40/0 (10)
NSF Registered	H1	H1	H1	H1	H1
ISO 21469	Yes	-	-	-	-
Kosher	Yes	Yes	Yes	Yes	Yes
Halal	Yes	Yes	Yes	Yes	Yes
CFIA	Yes	Yes	Yes	Yes	Yes

Shelf Life: Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use. Barrier Fluid 5 has a 5 year shelf life.