

CO-220 FG

High temperature food grade chain lubricant



Your benefits at a glance

- Excellent wear protection for extended chain life
- Low evaporation rate delivers a reduction in oil consumption
- Little or no deposits being left on chain

Your requirements - our solution

CO-220 FG chain oil was developed specifically for all drive, control and transport chains subject to high temperatures and loads. It is ideal for use in bakery and other high temperature chain applications in the food industry. CO-220 FG has excellent wear protection for extended chain life. Its low evaporation rate delivers a

reduction in oil consumption, along with little or no deposits being left on the chain.

Application

Drive, control and transport chains

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	CO-220FG
Article number	340367
Density	0.964 g/cm ³
Flash point	250 °C
Kinematic viscosity, 100°C	17.0 mm ² /s
Kinematic viscosity, 40°C	220 mm ² /s
Viscosity index	143
Pour point	-38 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.