

LCG Series

Synthetic natural gas compressor lubricant



Your benefits at a glance

- Inhibits effects of sour gases
- Provides longer fluid and equipment life
- Protects oil wetted parts against corrosion

Your requirements - our solution

Summit LCG Series are specially formulated compressor lubricants designed to be inert to most reactive and corrosive gases encountered in landfills, refineries, EOR and chemical process plants. LCG Series is based on 100% pure synthetic PAO. It's extremely low vapor pressure results in minimal carryover past the separator. It does not contain sulfur or other impurities associated with petroleum based products that might react with the acids, chlorinated compounds or sour gases found in various applications. PAOs are fully saturated compounds and do not contain the alkenes or aromatics found in group I, II or even the group III mineral oils touted as being "pure". LCG Series is ester free and not subject to hydrolysis issues encountered with most esters when used in acidic environments. LCG Series is suitable for use in certain chloride containing environments where the use of mineral oil, ester

and synthetic polyglycols (PAGs) are not permitted. Lubricants that are reactive with a gas stream may form by-products that are harmful to equipment or the environment. Solids may form and cause fouling or plugging issues in certain applications.

Summit LCG Series will protect oil wetted parts against corrosive effects of common acids and water. It is engineered with superior technology to inhibit the effects of sour gases such as hydrogen sulfide or carbon dioxide on metal surfaces found within the oil wetted parts of a compressor.

Summit LCG Series is designed to result in longer fluid and equipment life for rotating compressors in corrosive and reactive environments. Please consult with a Summit lubrication expert about the suitability of LCG Series in these types of applications.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	LCG-68	LCG-100	LCG-150
Article number	340287	340207	340369
Density	0.835 g/cm ³	0.84 g/cm ³	0.9 g/cm ³
Fire point	299 °C	304 °C	316 °C
Flash point	250 °C	260 °C	260 °C
Kinematic viscosity, 100°C	10.8 mm ² /s	13.9 mm ² /s	20.0 mm ² /s
Kinematic viscosity, 40°C	69.4 mm ² /s	96.8 mm ² /s	158.9 mm ² /s
Viscosity index	146	146	146
Pour point	-40 °C	-40 °C	-45 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	36 months	36 months

LCG Series

Synthetic natural gas compressor lubricant



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.