

June 3, 2015

Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, TX 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

PETROLEUM BARRIER FLUID

BARRIER FLUID-22P

Summit Barrier Fluid-22P is formulated from highly refined hydrotreated base stocks and fortified with additives to provide a non-reactive, oxidatively stable fluid for seal service over a wide temperature range. This fluid has an excellent low temperature fluidity and high temperature stability property as well as the ability to efficiently transfer heat, and keep the seal face cool. Summit Barrier Fluid-22P does not contain components that are known catalyst poisons, and are compatible with most commonly used seal materials

Physical Properties

PRODUCT	22-P
Viscosity	
@ 40°C, cSt	21.60
@ 100°C, cSt	4.31
Viscosity Index	105
Specific Gravity	0.856
Flash Point, °F (°C)	410 (210)
Pour Point, °F (°C)	-54 (-48)
Copper Strip Corrosion	1A
Emulsion Tendency	40/40/0 (10)
Rust	Pass

Shelf Life: Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.