

May 2, 2022

Klüber Lubrication NA LP • 9010 CR 2120 Tyler, Texas 75707 • Phone 903.534.8021 • sales@klsummit.com

# Product Data Sheet

**NOTE:** The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## SYNTHETIC AIR COMPRESSOR

### SUPRA-32

*Summit Supra-32 has been formulated to address the specific problems associated with conventional rotary screw and centrifugal compressor lubricants - thermal degradation and deposit formation. The polyglycol/ester blend has provided superior performance in the areas of oxidation resistance and deposit formation. **Supra-32** eliminates the varnish, sludge and the frequent lubricant changes associated with petroleum oils.*

### Physical Properties

PRODUCT	SUPRA-32
SAE GRADE	5W-20
Viscosity	
@ 40°C, cSt	37.1
@ 100°C, cSt	7.1
@ 100°F, SUS	185
@ 210°F, SUS	49.6
Viscosity Index	157
Specific Gravity	0.9636
Density, lbs/gal	8.027
Pour Point, °F (°C)	-65 (-54)
Flash Point, °F (°C)	490 (254)
RPVOT, (AVG min)	1942

**Shelf Life:** Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.

