

Varnasolv Series

Equipment varnish cleaner



Your benefits at a glance

- Eliminates need for disassembling equipment for cleaning
- Removes varnish and sludge
- Reduces maintenance costs

Your requirements - our solution

The use of petroleum lubricants, mainly automatic transmission fluid (ATF), in rotary screw compressors, rotary vane compressors and other high temperature equipment, results in varnish and carbon formation. The varnish and carbon deposited throughout the equipment can cause many serious operational problems, resulting in excessively high maintenance costs.

Varnasolv can help reduce the problems caused by varnish and carbon. Varnasolv should be added to the existing lubricant to remove and suspend varnish while the equipment is running. Using Varnasolv eliminates the need for disassembling the equipment for cleaning. For maximum benefit, use Varnasolv before each lubricant change. Varnasolv is NSF Registered HX-2

Additional applications for Varnasolv include cleaning hydraulic systems, gearboxes, and high temperature chains. Varnasolv can also be used for cleaning Heat Transfer systems with temperatures up to 400 °F.

Varnasolv HV is blended to a higher viscosity for minimal dilution when used in gear box lubricants.

Application notes

How to use Varnasolv:

Cleaning hydrocarbon deposits from equipment

Initial clean-out method:

Add one gallon of Varnasolv concentrate to each ten gallons of oil in the unit, first draining enough oil to allow adding the Varnasolv. Continue to run equipment for 20 to 40 hours, allowing the treated oil to disperse and suspend the varnish. To avoid redepositing the suspended contaminants, drain the oil while warm and replace filters. Refill with new oil.

Varnasolv is available in cases (six gallons), five gallon pails or 55 gallon drums.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	VARNASOLV	VARNASOLV HV
Article number	340472	340378
Density	0.969 g/cm ³	0.941 g/cm ³
Fire point	263 °C	279 °C
Flash point	210 °C	220 °C
Kinematic viscosity, 100°C	5.2 mm ² /s	29.0 mm ² /s
Kinematic viscosity, 40°C	32.0 mm ² /s	207.6 mm ² /s
Viscosity index	95	
Pour point	-18 °C	-6 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months

Varnasolv Series

Equipment varnish cleaner



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.