

MultiPump SPO Series

Synthetic gear lubricants



Your benefits at a glance

- Outstanding oxidation and thermal stability
- Withstands extreme pressure
- Provides maximum protection against wear, rust corrosion and foaming

Your requirements - our solution

Summit MultiPump SPO Series gear lubricants are formulated with synthetic base stocks and fortified with select additive systems to enhance their exceptional performance. The PAO base fluid used has outstanding oxidation and thermal stability, naturally high viscosity index and excellent low temperature pumpability and fluidity. The unique additive system used provides increased oxidation stability, extreme pressure properties, and maximum protection against wear, rust, corrosion and foaming.

Summit MultiPump SPO synthetic gear lubricants have proven to reduce friction, thereby reducing the input power to operate the equipment or increasing the available power output. This product line meets the requirements of U.S. Steel 224 specification, AGMA

9005-D94 specification, DIN 51517 Part 3 CLP specification and API GL-4 Gear Service Category.

Summit MultiPump SPO Series gear lubricants are recommended for use in all types of enclosed gearing with specific focus on Multiplex Pumps. These lubricants are ideal for the complex tribological requirements of multiplex pump such as high temperatures, heavy loads and extreme environments. Summit MultiPump SPO Series gear lubricants are compatible with most seal materials, paints and plastics, including nitrile buna N, neoprene, Viton®, Teflon®, polyethylene, polyurethane ether, fluorocarbon, polyacrylate, polysulfide, ethylene acrylic, epoxy, plastisol, PVC, acrylic paint and lacquer.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	MultiPump SPO-100	MultiPump SPO-150	MultiPump SPO-220	MultiPump SPO-320
Article number	340571	340572	340573	340574
Density	0.854 g/cm ³	0.865 g/cm ³	0.87 g/cm ³	0.87 g/cm ³
Flash point	204 °C	200 °C	200 °C	200 °C
Kinematic viscosity, 100°C	12.9 mm ² /s	17.8 mm ² /s	25.4 mm ² /s	32.8 mm ² /s
Kinematic viscosity, 40°C	95.7 mm ² /s	147 mm ² /s	232 mm ² /s	342 mm ² /s
Viscosity index	132	133	134	134
Copper corrosion	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree
Steel corrosion	passed	passed	passed	passed
Pour point	-41 °C	-45 °C	-43 °C	-40 °C
Four-ball tester: wear characteristics	0.30 mm	0.39 mm	0.34 mm	0.30 mm
Four-ball tester, welding load	200 kgf	315 kgf	315 kgf	315 kgf
FZG scuffing test	12+	12+	12+	12+
Timken test	65 lbs	65 lbs	65 lbs	65 lbs

MultiPump SPO Series

Synthetic gear lubricants



Characteristics	MultiPump SPO-100	MultiPump SPO-150	MultiPump SPO-220	MultiPump SPO-320
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months	60 months	60 months

Characteristics	MultiPump SPO-460
Article number	340575
Density	0.879 g/cm ³
Flash point	200 °C
Kinematic viscosity, 100°C	43.1 mm ² /s
Kinematic viscosity, 40°C	490 mm ² /s
Viscosity index	139
Copper corrosion	1 - - corrosion degree
Steel corrosion	passed
Pour point	-37 °C
Four-ball tester: wear characteristics	0.30 mm
Four-ball tester, welding load	315 kgf
FZG scuffing test	12+
Timken test	65 lbs
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.