

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

DROSERA MS 22

SDS #: 34188

Section 1. Identification

GHS product identifier : DROSERA MS 22

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Multifunctional oil for machine tools

Supplier's details

: TotalEnergies Marketing USA, Inc. 1201 Louisiana St. Suite 1800

Houston, TX 77002 Phone: 713-483-5000

ProductSafety@totalenergies.com

TotalEnergies Marketing Puerto Rico Corp Millennium Park Plaza, #15 Road 2, Suite 525

Guaynabo, P.R. 00968 Phone: 1-787-783-4625

Emergency telephone number (with hours of operation)

1-866-928-0789 (For Emergencies, call CARECHEM 24/7 Domestic) 1-215-207-0061 (For Emergencies, call CARECHEM 24/7 International)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: TOXIC TO REPRODUCTION - Category 2

GHS label elements

Hazard pictograms



Signal word

Warning

Hazard statements

Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention

: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face

protection.

Response

: IF exposed or concerned: Get medical advice or attention.

Storage

: Store locked up.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

elements

: Avoid contact with skin and clothing. Wash thoroughly after handling.

Date of revision : 2025/02/20 2 USA ENGLISH 1/15



SDS #: 34188

Hazards not otherwise classified

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	Identifiers	GHS Classification
vistillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	CAS: 64742-54-7	Not classified.
Distillates (petroleum), solvent- dewaxed heavy paraffinic	≥25 - ≤50	CAS: 64742-65-0	Not classified.
Distillates (petroleum), hydrotreated light paraffinic	≥25 - ≤50	CAS: 64742-55-8	ASPIRATION HAZARD - Category 1
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	≤0.3		TOXIC TO REPRODUCTION - Category 2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Additional information

: Mineral oil of petroleum origin. Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.

Date of revision : 2025/02/20 2 USA ENGLISH 2/15



lotalEnergies SDS#: 34188

Inhalation : No known significant effects or critical hazards.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

 carbon monoxide carbon dioxide
 Silicon Dioxide nitrogen oxides phosphorus oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

: In a fire or if heated, a pressure increase will occur and the container may burst.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark : Mon-flammable.

 Date of revision
 : 2025/02/20
 2
 USA
 ENGLISH
 3/15



SDS#: 34188

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

See Section 10 for incompatible materials before handling or use.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

2 USA **ENGLISH** Date of revision : 2025/02/20 4/15



SDS #: 34188

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Product/substance	Exposure limits
vistillates (petroleum), hydrotreated heavy	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]
paraffinic	TWA 10 hours: 5 mg/m³. Form: Mist.
	STEL 15 minutes: 10 mg/m³. Form: Mist.
	OSHA PEL (United States, 5/2018) [Oil mist, mineral]
	TWA 8 hours: 5 mg/m³.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined] A4.
	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]
paraffinic	TWA 10 hours: 5 mg/m³. Form: Mist.
paramino	STEL 15 minutes: 10 mg/m³. Form: Mist.
	OSHA PEL (United States, 5/2018) [Oil mist, mineral]
	TWA 8 hours: 5 mg/m³.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and
	severely refined] A4.
	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
Distillates (petroleum), hydrotreated light	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]
paraffinic	TWA 10 hours: 5 mg/m³. Form: Mist.
	STEL 15 minutes: 10 mg/m³. Form: Mist.
	OSHA PEL (United States, 5/2018) [Oil mist, mineral]
	TWA 8 hours: 5 mg/m³.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and
	severely refined] A4.
	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
Benzenamine, N-phenyl-, reaction products with	ACGIH TLV (United States)
2,4,4-trimethylpentene	TWA: 3 mg/m³. Form: Respirable dust.
	TWA: 10 mg/m³. Form: Total dust.

Biological exposure indices

No exposure indices known.

Advisory OEL

: Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of revision : 2025/02/20 2 USA ENGLISH 5/15



SDS #: 34188

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Hydrocarbon-proof gloves

Fluorinated rubber nitrile rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of insufficient ventilation, wear suitable respiratory equipment. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

Appearance

Physical state : Liquid. [limpid]
Color : Not available.
Odor : Characteristic.
Odor threshold : Not available.
pH : Not applicable.

Melting point/freezing point : Technically not possible to measure

Pour point : -21°C (-5.8°F)

Boiling point : >316°C (>600.8°F) [EN ISO 3405] **Flash point** : Open cup: 190°C (374°F) [ISO 2592]

Evaporation rate : Not available.

Flammability (solid, gas) : Mon-flammable.

Lower and upper explosive (flammable) limits : Lower: 0.9% Upper: 7%

Vapor pressure : ✓0.01 kPa (<0.075 mm Hg) [room temperature] [ASTM D 5191]

Not applicable. [50°C]

Vapor density : >2 [Air = 1]

Relative density : 0.854 [ISO 12185]

Density : 0.854 g/cm³ [15°C] [ISO 12185]

Solubility(ies) :

Date of revision : 2025/02/20 2 USA ENGLISH 6/15



SDS#:

34188

MediaResultwaterNot soluble

Miscible with water : No.

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature

: >190°C (>374°F) [ASTM E 659]

Decomposition temperature

: Not applicable.

Viscosity

Dynamic (room temperature): Not available. Kinematic (room temperature): Not available.

Kinematic (40°C (104°F)): 20.6 mm²/s (20.6 cSt) [ISO 3104]

Flow time (ISO 2431)

Particle characteristics

: Not available.

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/substance	Result
☑stillates (petroleum), hydrotreated heavy	Rat - Male, Female - Oral - LD50
paraffinic	>5000 mg/kg
	OECD [401 Read across]
	Rabbit - Dermal - LD50
	>5000 mg/kg
	OECD [402 Read across]
	Rat - Inhalation - LC50 Dusts and mists
	>5 mg/l [4 hours]
	OECD [403 Read across]
Distillates (petroleum), solvent-dewaxed	Rabbit - Dermal - LD50
heavy paraffinic	>5000 mg/kg
	OECD [402]
	Rat - Oral - LD50
	>5000 mg/kg

Date of revision : 2025/02/20 2 USA ENGLISH 7/15



paraffinic

DROSERA MS 22

SDS#: 34188

OECD [420]

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours] OECD [403] Rat - Oral - LD50

Distillates (petroleum), hydrotreated light >5000 mg/kg

OECD [420]

Rabbit - Dermal - LD50

>5000 mg/kg OECD [402]

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours] OECD [403]

Benzenamine, N-phenyl-, reaction products

with 2,4,4-trimethylpentene

Rat - Male, Female - Oral - LD50

>5000 mg/kg OECD [401]

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory corrosion/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin

Based on available data, the classification criteria are not met.

Respiratory

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are met.

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards. : No known significant effects or critical hazards. Inhalation

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

Date of revision : 2025/02/20 USA **ENGLISH** 8/15



otalEnergies sps #: 34188

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Potential chronic health effects

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Reproductive toxicity: Suspected of damaging fertility or the unborn child.

Other information :

Not available.

Section 12. Ecological information

Ecotoxicity

Product/substance	Result
Distillates (petroleum), hydrotreated heavy paraffinic	Acute - LL50 OECD [202] Crustaceans - Daphnia magna >10000 mg/l [48 hours] Effect: Mobility Acute - LL50 OECD [201] Algae - Pseudokirchneriella subcapitata >100 mg/l [72 hours] Effect: (growth rate) Chronic - NOEL Fish - Oncorhynchus mykiss >1000 mg/l [21 days] Effect: Mortality Chronic - NOEL Crustaceans - Daphnia magna 10 mg/l [21 days]
	Effect: (growth rate) Chronic - NOEL Fish - Oncorhynchus mykiss >1000 mg/l [21 days] Effect: Mortality Chronic - NOEL Crustaceans - Daphnia magna

Date of revision : 2025/02/20 2 USA ENGLISH 9/15



heavy paraffinic

paraffinic

Distillates (petroleum), solvent-dewaxed

Distillates (petroleum), hydrotreated light

Benzenamine, N-phenyl-, reaction products

DROSERA MS 22

SDS#: 34188

Effect: Reproduction **Chronic - NOEL** OECD [201]

Algae - Pseudokirchneriella subcapitata

>100 mg/l [72 hours] Effect: (growth rate)

Acute - EC50 OECD [201]

Algae - Pseudokirchnerella subcapitata

>100 mg/l [72 hours]

Acute - EC50 **OECD** [202]

Daphnia - Daphnia magna >10000 mg/l [48 hours]

Chronic - NOEL

Fish - Oncorhynchus mykiss

>1000 mg/l [21 days]

Chronic - NOEL

OECD [211]

Daphnia - Daphnia magna

10 mg/l [21 days]

Acute - EC50

OECD [201]

Algae - Pseudokirchnerella subcapitata

>100 mg/l [48 hours]

Acute - EC50

OECD [202]

Daphnia - Daphnia magna >10000 mg/l [48 hours]

Chronic - NOEL

Fish - Oncorhynchus mykiss

>1000 mg/l [21 days] **Chronic - NOEL**

OECD [211]

Daphnia - Daphnia magna

10 mg/l [21 days]

Acute - LC50 - Fresh water

OECD [203] Fish - Danio rerio >100 mg/l [96 hours] Effect: Mortality

Acute - EC50 - Fresh water

OECD [201]

Algae - Desmodesmus subspicatus

>100 mg/l [72 hours] Effect: (growth rate)

Persistence and degradability

with 2,4,4-trimethylpentene

Product/substance	Result
vistillates (petroleum), hydrotreated heavy	OECD 301F
paraffinic	31% [28 days] - Not readily
Benzenamine, N-phenyl-, reaction products	OECD [301B]
with 2,4,4-trimethylpentene	1% [28 days]

Date of revision : 2025/02/20 2 USA **ENGLISH** 10/15



SDS#:

34188

Product/substance	Aquatic half-life	Photolysis	Biodegradability
istillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	-	-	Not readily

Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
istillates (petroleum), solvent-dewaxed heavy paraffinic	6.1	-	High
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	5.1	1730	High

Mobility in soil

Soil/water partition coefficient (Koc) Mobility in soil : Not available.

: Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	ICAO/IATA
UN/ID No	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-

Date of revision : 2025/02/20 2 USA ENGLISH 11/15



SDS#: 34188

Environmental No. No. No. hazards

Additional information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) PAIR: diphenylamine; Siloxanes and Silicones, di-Me

TSCA 12(b) - Chemical export notification

Not applicable.

Clean Air Act Section 112

(b) Hazardous Air

Pollutants (HAPs) Clean Air Act Section 602 : Not listed

Class I Substances

Clean Air Act Section 602

Class II Substances

: Not listed

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals) : Not listed : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : TOXIC TO REPRODUCTION - Category 2

HNOC - Defatting irritant

Composition/information on ingredients

Name	%	Classification
☑istillates (petroleum), hydrotreated light paraffinic	≥25 - ≤50	ASPIRATION HAZARD - Category 1
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	≤0.3	TOXIC TO REPRODUCTION - Category 2

State regulations

Massachusetts : The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL;

MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC

New York : None of the components are listed. **New Jersey** : None of the components are listed. **Pennsylvania** : None of the components are listed.

Date of revision : 2025/02/20 2 USA **ENGLISH** 12/15



SDS #: 34188

California Prop. 65

To the best of our knowledge, this product does not contain any substances known to the State of California to cause cancer, developmental and/or reproductive harm.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia inventory (AIIC) : All components are listed or exempted.

Canada inventory (DSL/NDSL) : All components are listed or exempted.

China inventory (IECSC) : All components are listed or exempted.

Europe inventory (EC) : All components are listed or exempted.

Japan inventory : Japan inventory (CSCL): All components are listed or

exempled.

Japan inventory (ISHL): All components are listed or

exempted.

New Zealand Inventory of Chemicals (NZIoC) : All components are listed or exempted.

Philippines inventory (PICCS) : All components are listed or exempted.

Korea inventory (KECI) : All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) : All components are listed or exempted.

Thailand inventory : Not determined.

Turkey inventory : Not determined.

United States inventory (TSCA 8b) : All components are listed or exempted.

Vietnam inventory : Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Date of revision : 2025/02/20 2 USA ENGLISH 13/15



SDS #: 34188

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
TOXIC TO REPRODUCTION - Category 2	Calculation method

History

Date of revision : 2025/02/20 previous revision date : 2022/11/24

Version : 2

Key to abbreviations : ACGIH = American Conference of Governmental Industrial Hygienists

BCF = Bioconcentration Factor

EC50 = Half maximal effective concentration

EL50 = median Effective Loading

IC50 = Half maximal inhibitory concentration IDHL = Immediately dangerous to life or health

LC50 = Median lethal concentration

LD50 = Median lethal dose LL50 = median Lethal Loading

LogKow = logarithm of the octanol/water partition coefficient

N/A = Not available

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level NOEC No Observed Effect Concentration

NOEL = No Observed Effect Level

NOELR = No observed Effect Loading Rate

OECD = Organisation for Economic Co-operation and Development

OEL = Occupational Exposure Limit

QSAR = Quantitative Structure—Activity Relationship

REL = Recommanded Exposure Limit STEL = Short Term Exposure Limit TLV = Threshold Limit Value

TWA = Time Weight Average
VOC = Volatile Organic Compound

Date of revision : 2025/02/20 2 USA ENGLISH 14/15



SDS #: 34188

UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material

References : Not available.

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of revision : 2025/02/20 2 USA ENGLISH 15/15