

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS #: 083319 CARTER EP 680

Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

1. IDENTIFICATION

Product identifier

Product name CARTER EP 680

Other means of identification

Product Code(s) 083319

Number 194 **Substance/mixture** Mixture

Recommended use of the chemical and restrictions on use

Identified uses Industrial gear oil.

Uses advised againstDo not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA, Inc.

1201 Louisiana St. Suite 1800

Houston, TX 77002 Phone: 713-483-5000

Contact Point Technical/ HSEQ

E-mail Address ProductSafety@total.com

Emergency telephone number

Company Phone Number +1 (908) 862-9300

Emergency telephone 1-866-928-0789 (For Emergencies, call CARECHEM 24/7

Domestic)

1-215-207-0061 (For Emergencies, call CARECHEM 24/7

International)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

Hazard Statements

None

Hazards not otherwise classified (HNOC)

None known

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental propertiesShould not be released into the environment. The product may form an oil film on the water

surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated light	64742-53-6	0.1-<0.25
naphthenic		
2-ethylhexan-1-ol	104-76-7	0.1-<0.25
2,6-di-tert-butylphenol	128-39-2	0.1-<0.25

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse. High pressure jets may

cause skin damage. Take victim immediately to hospital.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration.

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician or Poison Control Center immediately.

Protection of First-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device.

Most important symptoms/effects, acute and delayed

Skin contact Not classified based on available data. High pressure injection of the products under the

skin may have very serious consequences even though no symptom or injury may be

apparent.

Eye contact Not classified based on available data.

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Symptoms No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S, Mercaptans, Nitrogen oxides (NOx), Phosphorous oxides, Hydrogen fluoride. Hydrogen chloride. Sodium

oxides. Silicon dioxide, Zinc oxides.

Explosion Data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General InformationDo not allow material to contaminate ground water system. Prevent entry into waterways,

sewers, basements or confined areas. Local authorities should be advised if significant

spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or

similar non-combustible materials.

Methods for cleaning up Dispose of contents/container in accordance with local regulation. In case of soil

contamination, remove contaminated soil for remediation or disposal, in accordance with

local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe

vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges.

Hygiene measuresEnsure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Provide regular cleaning of equipment, work area and clothing. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into

workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

Materials to Avoid Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

Control parameters

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH

(TLV) TWA 5 mg/m³ (highly refined).

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. Ensure

adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the

recommended equipment.

Individual protection measures, such as personal protective equipment

General Information Protective engineering solutions should be implemented and in use before personal

protective equipment is considered. The personal protective equipment (PPE)

recommendations apply to the product ITSELF. In case of mixtures or formulations, it is

suggested that you contact the relevant PPE suppliers.

Eye/face protection If splashes are likely to occur, wear:. Safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

Hand Protection Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. Warning! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's

instructions and the regulations governing their choices and uses.

Hygiene measuresEnsure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Provide regular cleaning of equipment, work area and clothing. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into

workwear pockets.



Revision Date: 2020-08-05 Version 4 Date of the previous version: 2017-09-20

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color dark amber Physical State @20°C liquid

Odor Strong Rotten-egg like

Odor Threshold No information available

Property Values Remarks Method Not applicable pН

No information available Melting point/range

Boiling point/boiling range Not applicable

260 °C Cleveland Open Cup (COC) Flash point

ASTM D 92

500 °F Cleveland Open Cup (COC). ASTM D 92.

No information available **Evaporation rate**

Flammability Limits in Air No information available

upper Lower

Vapor Pressure Not applicable

No information available Vapor density

No information available Relative density

@ 15 °C **Density** 915.5 kg/m³ **ASTM D 1298**

Water solubility Insoluble

No information available Solubility in other solvents No information available logPow **Autoignition temperature** No information available

Decomposition temperature No information available Viscosity, kinematic 680 mm2/s @ 40 °C

Explosive properties Not explosive **Oxidizing Properties** Not applicable

Not applicable Possibility of hazardous reactions

Other information

0.916 @ 15 °C **ASTM D 1298 Specific Gravity**

Freezing Point No information available

Pour point -12 °C ASTM D 97

10. STABILITY AND REACTIVITY

Reactivity None under normal processing.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

ASTM D 445



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

<u>Conditions to avoid</u>

Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat

and sparks. Take precautionary measures against static discharges.

<u>Incompatible materials</u> Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S, Mercaptans, Phosphorous oxides, Nitrogen oxides (NOx), Hydrogen fluoride, Sodium oxides, Hydrogen

chloride, Silicon dioxide, Zinc oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Symptoms No information available.

Skin contact Not classified based on available data. High pressure injection of the products under the

skin may have very serious consequences even though no symptom or injury may be

apparent.

Eye contact Not classified based on available data.

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Oral Not classified based on available data

Dermal Not classified based on available data

Inhalation Not classified based on available data

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	
light naphthenic			



Date of the previous version: 2017-09-20 **Revision Date: 2020-08-05** Version 4

64742-53-6			
2-ethylhexan-1-ol 104-76-7	2047 - 3730 mg/kg (rat - OECD 401)	> 3000 mg/kg bw (rat - OECD 402)	LC50 (4h) 0.89 - 5.3 mg/l (rat - OCDE 403)
2,6-di-tert-butylphenol 128-39-2	> 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	

Skin corrosion/irritation Serious eye damage/eye irritation

Sensitization Carcinogenicity

Not classified based on available data. Not classified based on available data. Not classified based on available data. Not classified based on available data.

Mutagenicity Not classified based on available data. Not classified based on available data. Reproductive toxicity **Target Organ Effects (STOT)** None known. Not classified based on available data.

STOT - single exposure

Other adverse effects

Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Not classified based on available data. **Aspiration hazard**

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute aquatic toxicity - Product Information

No information available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6		LC50 (96h) > 5000 mg/L Oncorhynchus mykiss ()	EC50 (48h) > 1000 mg/L Daphnia magna	
2-ethylhexan-1-ol 104-76-7	EC50 (96h) 1.3 mg/l (Skeletonema costatum - OECD) EbC50 (72h) 11.5 mg/l (Desmodesmus subspicatus - OECD 201) CE50r (72h) 16.6 mg/l (Scenedesmus subspicatus- OECD 201)	LC50 (96h) 17.1 mg/l Leuciscus idus (OCDE 203)	EC50 (48h) 39 mg/l (Daphnia magna - OECD 202) EC50 (48h) 1.82 mg/l (Daphnia magna - OECD 202) EC50 (24h) 2.72 mg/l (Daphnia magna - OECD 202)	
2,6-di-tert-butylphenol 128-39-2	EC50 (72h) 1.2 mg/l	LC50(96h) 1 mg/l (fish)	EC50 (48h) = 0.45 mg/L Daphnia magna	

Chronic aquatic toxicity - Product Information

No information available



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
2,6-di-tert-butylphenol 128-39-2		NOEC(21d) 0.035 mg/l	NOEC (28d) 0.3 mg/l (fish)	

Effects on terrestrial organisms No information available.

Persistence and degradability

General Information No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

Chemical Name	log Pow
2-ethylhexan-1-ol 104-76-7	2.9
2,6-di-tert-butylphenol 128-39-2	4.48

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility.

Air Loss by evaporation is limited.

Water The product is insoluble and floats on water. The product is insoluble and sinks in water

Other adverse effects

General Information No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Should not be released into the environment. Dispose of in accordance with all applicable

national environmental laws and regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard

Chronic Health Hazard

Fire Hazard

Sudden Release of Pressure Hazard

No
Reactive Hazard

No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

U.S. State Regulations

California Proposition 65

To the best of our knowledge, this product does not contain any substances known to the State of California to cause cancer, developmental and/or reproductive harm.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Paraffin oils (petroleum),	X			
catalytic dewaxed heavy				
64742-70-7				

16. OTHER INFORMATION

NFPAHealth Hazard 1Flammability 1Instability 0Special hazards -HMISHealth Hazard 0Flammability 1Physical Hazard 0Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2020-08-05
Revision Note Document Review

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

ATE = Acute Toxicity Estimate

QSAR = Quantitative Structure-Activity Relationship

EL50 = median Effective Loading

NOELR = No Observed Effect Loading Rate

PAH = Polycyclic aromatic hydrocarbons



Date of the previous version: 2017-09-20 Revision Date: 2020-08-05 Version 4

LOEC = Lowest Observed Effect Concentration

PVA = Polyvinyl alcohol PVC = Polyvinyl chloride

ECOSAR = Ecological Structure Activity Relationships

CNS = Central nervous system

EPA = Environmental Protection Agency

ErL50 = effective loading on growth rate in algae test, to cause a 50% response

EbL50 = effective loading on growth with the control in algae test, to cause a 50% response

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet