NEVASTANE® WET LUBE 100





Food Machinery Lubricant.

APPLICATIONS

Multi-purpose Lubricant for Wet Environments.

H1 Registered Food Grade Lubricant.





- NEVASTANE WET LUBE 100 is specially designed to lubricate and protect food
 processing machinery in a wet environment. It preferentially displaces water and
 keeps bearings, slides, guides, and chains lubricated for satisfactory machine life. It
 assures long machine life while reducing contamination problems as required by the
 Hazard Analysis and Critical Control Point System (HACCP).
- **NEVASTANE WET LUBE 100** is suitable for use on machinery such as fruit peeling and coring machines, tables, conveyors, and around fillers.
- NSF H1 Registered meets USDA 1998 H1 Guidelines for incidental contact with food.

ADVANTAGES

- Lubricates in very wet environments.
- Provides excellent lubricity.
- Provides rust protection.
- H1 registered.
- Kosher Pareve.
- Star-K.

| TYPICAL CHARACTERISTICS | METHODS | NEVASTANE WET LUBE |
|---|-------------|-----------------------------|
| ISO VG Grade | | 100 |
| NSF Registration Number | | 123140 |
| SAE Grade | | 30W |
| Appearance | Visual | Bright, Clear, Amber Liquid |
| Odor | | Mild Chemical |
| Viscosity @ 40°C, cSt | ASTM D 445 | 100 |
| Viscosity @ 100°C, cSt | ASTM D 445 | 12.5 |
| Viscosity @ 40°C, cSt | ASTM D 2270 | 113 |
| Color | ASTM D 1500 | 1.5 |
| Flash Point, COC, °F(°C) | ASTM D 92 | 455(235) |
| Fire Point, COC, °F(°C) | ASTM D 92 | 515(268) |
| Pour Point, °F(°C) | ASTM D 97 | 10(-12) |
| Density @ 60°F, lbs./gal. (kg/m ³ ,15°C) | ASTM D 1298 | 7.31(876) |

Shelf Life: Use by 60 months or 5 years.

TOTAL Specialties USA, Inc.

Linden, NJ 07036 5 North Stiles Street 1-800-323-3198 www.totalspecialties.com

NEVASTANE

6-2016