

NEVASTANE® FLUSH OIL



FOOD INDUSTRY



TOTAL

Food Machinery System Flushing Oil.

APPLICATIONS

Cleans and Flushes Old Oil and Residues.

H1 Registered Food Grade.



- **NEVASTANE FLUSH OIL** is a very light viscosity fluid for cleaning and flushing old oil and residues in mechanical systems found in food processing plants. It is compatible with petroleum products and most synthetics. It is non-corrosive to metals.
- **NEVASTANE FLUSH OIL** assures long machine life while reducing contamination problems as required by the Hazard Analysis Critical Control Point System (HACCP).
- **NEVASTANE FLUSH OIL** has been successfully used in hydraulic systems, gear reducers, airlines, air tools, circulating oil systems, bearings and chains.
- **NSF H1 Registered meets USDA 1998 H1 Guidelines for incidental contact with food.**

ADVANTAGES

- Non-toxic.
- Low odor.
- Non-staining.
- Non-corrosive.

TYPICAL CHARACTERISTICS	METHODS	NEVASTANE FLUSH OIL
NSF Registration Number		123139
ISO Viscosity Grade		10
Appearance	Visual	Clear, Water White
Color	ASTM D 1500	< 0.5
Odor		Mild Chemical
Viscosity @ 40°C, cSt	ASTM D 445	9.5
Viscosity @ 100°C, cSt	ASTM D 445	2.5
Density @ 60°F, lbs./gal.(kg/m ³ , 15°C)	ASTM D 1298	6.90(827)
Flash Point, COC, °F (°C)	ASTM D 92	230(110)
Fire Point, COC, °F (°C)	ASTM D 92	240(115)
Pour Point, °F (°C)	ASTM D 97	-24(-31)

Shelf Life: Use by 60 months or 5 years.

TOTAL Specialties USA, Inc.

Linden, NJ 07036

5 North Stiles Street
1-800-323-3198

www.totalspecialties.com

NEVASTANE

7-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.