

# NEVASTANE® 2 PLUS



FOOD INDUSTRY



**TOTAL**

## White Food Machinery Grease.

### APPLICATIONS

**Multi-purpose, Aluminum Complex Grease.**

**H1 Registered Food Grade Grease.**



### ADVANTAGES

- **NEVASTANE 2 PLUS** grease is a white, aluminum complex grease that outperforms other food grade lubricants by combining superior anti-wear properties with a tacky texture. Specially designed additives enable the anti-wear ingredients to provide as much as 50% higher wear resistance. **NEVASTANE 2 PLUS** is enhanced even further with oxidation and water resistant properties to protect against corrosion and increase re-grease intervals. Stability over a wide temperature range allows for use in a variety of food processing machinery and general purpose lubrication applications.
- **NSF Nonfood compounds program listed H1 for incidental contact with food.**
- **Complies with US FDA regulation 21 CFR 178.3570.**

- Water resistant.
- Tacky.
- Wide operating temperature range
- Extends equipment life.
- Protection against wear.

TYPICAL CHARACTERISTICS	METHODS	NEVASTANE 2 PLUS
NSF Registration Number		123541
NLGI Grade		2
Penetration, Worked 60 strokes	ASTM D 217	265-295
Dropping Point, °C	ASTM D 2265	232 min.
Appearance	Visual	Smooth, Tacky White
4 Ball Wear, 40kg, 120rpm, 167°F, 1hr, mm	ASTM D 2266	0.63
Operating Range, °F		0-350
Copper Corrosion	ASTM D 130	1A
Thickener Type		Aluminum Complex
Water Washout @ 175°F, % loss	ASTM D 1264	< 5.0
Base Oil Properties:		
Viscosity @ 40°C, cSt	ASTM D 445	105
Viscosity @ 100°C, cSt	ASTM D 445	11.96
Viscosity Index	ASTM D 2270	90
Flash Point, COC, °F(°C)	ASTM D 92	435(225)
Pour Point, °F	ASTM D 97	20

Shelf Life: Use by 36 months or 3 years.

## TOTAL Specialties USA, Inc.

Linden, NJ 07036  
5 North Stiles Street  
1-800-323-3198  
www.totalspecialties.com

NEVASTANE

6-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at [www.totalspecialties.com](http://www.totalspecialties.com). Copyright 2016 All rights reserved.