



METALWORKING



Chlorine-free Cutting Oil for Severe Machining and Machine Tool Lubrication.

| APPLICATIONS | | |
|--------------|--|--|
| | SCILIA 46 S is a low odor, non-staining, neat cutting oil dedicated to both ferrous and non-ferrous metals and to the lubrication of various machine parts: bearings, gears, and slideways. SCILIA 46 S is widely used on cutting operations such as screw cutting on copper alloys, aluminum, low carbon steels, medium, hard, and stainless steels, bronze, tin, nickel, high nickel steel, and heat resistant alloys. It is recommended for all general machining operations, heavy load and high speed operations, and on difficult to machine alloys. SCILIA 46 S can be utilized as a dual purpose oil in low pressure lube systems. | |
| | where cross contamination of cutting oil and lube oil is a problem. | |
| ADVANTAGES | | |
| | Excellent anti-wear and extreme pressure performance. Promotes excellent surface finish | |
| | Excellent lubricity propertiesIncreases the tool life on a large scale of cutting parameters maintaining an additive layer on the chip / workpiece / tool surface. Excellent metal wetting ability. Non-staining. | |
| | Very good oxidation resistance. | |
| | Excellent compatibility with seals and paints. | |
| | SCILIA 46 S | |

| | SCILIA 46 S | |
|----------------------------------|---------------------|--|
| TIFICAL CHARACTERISTICS | | |
| Appearance | Clear Yellow Liquid | |
| Color, ASTM D-1500 | 1.0 | |
| Viscosity at 40°C, cSt | 41.4 - 50.6 | |
| Density @ 60 °F, lbs./gal. | 7.31 | |
| Specific Gravity @ 60/60 °F | 0.878 | |
| Flash Point, COC, ^o F | 380 | |
| Copper Strip Corrosion | 1A-1B | |
| Lubricity Content, %wt. | 5.0 | |
| Sulfur Content, %wt. | 1.0 | |
| Chlorine Content, %wt. | Nil | |

TOTAL Specialties USA, Inc.

Linden, NJ 07036 5 North Stiles Street 1-800-323-3198 www.totalspecialties.com

SCILIA 6-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.