



DYNATRANS MP



Lubricant for transmission systems, hydraulic circuits and oil-bath disc brakes fitted to agricultural tractors, construction machinery and handling systems.

APPLICATIONS

Transmission systems

Hydraulics

Submerged brakes

- Lubrication of mechanical transmission systems requiring a GL4 product.
- Lubrication of automatic transmission systems, torque converters and hydrostatic transmissions.
- Lubrication of power take-offs.
- Application to all hydraulic circuits.
- Lubrication of power-assisted steering systems.
- Lubrication of wet brakes with cellulose liners.

PERFORMANCES

Classifications

Meets manufacturers' specifications

Suitable when the product is recommended

API GL-4

JOHN DEERE JDM J 20A / J20C
FORD M2C 134D / FHNA 2C 201.00
CASE MS 1206 / 1207

Please see supplemental page for additional OEMs

CUSTOMER BENEFITS

Wide range of applications

Long component life

- Equally suitable for agricultural machinery and for construction machinery, meaning fewer lubricants need be stocked.
- Excellent low temperature performance (protects friction discs against any risk of binding).

SPECIFICATIONS

TYPICAL PROPERTIES OF DYNATRANS MP	
Specific Gravity @ 60/60°F ASTM D 1298	0.878 (7.3 lb/gal)
Color, ASTM D 1500	L3.5
Flash Point °C, open cup ASTM D 92	204
Kinematic viscosity at 40°C, cSt ASTM D 445	63
Kinematic viscosity at 100°C, cSt ASTM D 445	10.8
Viscosity Index (140 minimum) ASTM D 2270	153
Pour point °C ASTM D 97	-33

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

DYNATRANS 7-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.