

# FLUIDMATIC MV LV



## Synthetic Premium Multi-vehicle ATF

### APPLICATIONS

#### Types of service

- **FLUIDMATIC MV LV** is recommended for wherever low-viscosity automatic transmission fluids are needed. These fluids have the best fuel economy.
- **FLUIDMATIC MV LV** meets and exceeds current original equipment manufacturers specifications for automatic transmission fluids, including some of the latest OEM specifications as specified by GM, Ford, Chrysler, Toyota, Mitsubishi and others.
- Consult your owner's manual regarding its suitability as ATF in imported vehicles. Do not use in ATF applications where CVT fluids or Ford ATF type F is required. Do not use this ATF in Honda power steering fluid systems.

### PERFORMANCE

#### Product Suitability

- GM Dexron VI
- Obsolete GM Dexron products (DII, DIII, DIII-G, DIII-H)
- Ford Mercon LV or Mercon SP
- Hyundai/KIA/Mitsubishi SP-IV
- Toyota WS (World Standard)
- Volvo STD 1273.41

### CUSTOMER BENEFITS

#### High technical performance

- Exceptional cleanliness of delicate control valves resulting in trouble-free transmission performance
- Dyed red to detect leaks
- Proper frictional properties provide the required shift feel characteristics.
- Excellent anti-wear, anti-corrosion, anti-foam and oxidation resistance.
- Excellent low temperature fluidity protects against wear under extremely cold operating conditions.

### CHARACTERISTICS

PROPERTY	Test Method	FLUIDMATIC MV LV
Color	Visual	Red
Specific gravity @60F/60F (lb/gal)		0.873 (7.26)
Viscosity, cP @ -40°C (-40°F)	ASTM D-2983	7,900
Viscosity, cSt @ 100°C:	ASTM D-445	5.6
Viscosity Index	ASTM D-2270	175
Pour Point, °C (°F)	ASTM D-97	-46 (-50)
Flash Point, °C (°F)	ASTM D-93	220 (428)

## TOTAL Specialties USA, Inc.

Linden, NJ 07036

5 North Stiles Street

1-800-323-3198

[www.totalspecialties.com](http://www.totalspecialties.com)

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at [www.totalspecialties.com](http://www.totalspecialties.com). Copyright 2016 All rights reserved.

# FLUIDMATIC MV LV



---

## Synthetic Premium Multi-vehicle ATF

### SUITABILITY GUIDE—ATF

**FLUIDMATIC MV LV** (low viscosity) is suitable for most ATFs in the low ATF viscosity range such as:

Bentley P/N PY112995PA	JWS None
BMW/Mini	Land Rover P/N TYK500050
P/N 83 22 0 142 516	MAN 339A
P/N 83 22 0 397 114	Maserati P/N 231603
Chrysler/Dodge/Jeep MB 236.12	Mazda FZ
P/N 05127382AA, P/N 68043742AA	Mercedes 236.12, 236.14, 236.15, 236.41
Ford/Lincoln/Mercury	Mitsubishi ATF-J2 (Diamond Queen), ATF-J3
P/N XT-10-QLV [= Mercon LV],	Nissan/Infinity Matic J, Matic S
P/N XT-6-QSP or -DSP [= Mercon SP]	Porsche P/N 000 043 304 00
GM/GMC/Opel/Saturn Dexron VI, AW-1,	Saab P/N 93 165 147 - AW-1
P/N 88863400 P/N 88863401	Shell 3353, Shell 134, Shell M-1375.4
Dexron, Dexron II, IID and IIE	SSang Yong DSIH 5M-66
Dexron III, III-G, III-H,	Subaru none
Honda/Acura DW-1, Z-1	Suzuki none
Hyundai / Kia NWS-9638 T-5, SP-IV/SPH-IV	Toyota/Lexus/Scion Type WS
P/N 040000C90SG	VW / Audi G 055 540 (A2)
Idemitsu none	G 055 005 (-A, A2)
Izusu None	Volvo none
JASO M315-Class 1A	ZF TE-ML none
Jaguar - Fluid 8432	

---

## TOTAL Specialties USA, Inc.

**Linden, NJ 07036**

5 North Stiles Street

1-800-323-3198

[www.totalspecialties.com](http://www.totalspecialties.com)

FLUIDMATIC

7-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at [www.totalspecialties.com](http://www.totalspecialties.com). Copyright 2016 All rights reserved.

