

MARTOL LVG 25 AQ



Metalworking



VOC free metal forming vanishing oil.

UTILISATIONS

- **MARTOL LVG 25 AQ** is an evaporating oil for low and medium severity drawing on steel and non-ferrous metals.
- **MARTOL LVG 25 AQ** can be applied with a brush, by spray, or with a roller.
- **MARTOL LVG 25 AQ** is thermally degreasable, does not leave any residue over 220 °C.
- **MARTOL LVG 25 AQ** is recommended for brazing assembly lines.

ADVANTAGES

- **MARTOL LVG 25 AQ** is a VOC free product.
- **MARTOL LVG 25 AQ** is characterized by:
 - Evaporating character.
 - A good wetability of the lubricant which ensures an excellent surface covering.
 - Can be used on coated metal in certain cases.
 - Leaves a thin film that usually does not need to be degreased.
- **MARTOL LVG 25 AQ** ensures extended tool life.

TYPICAL CHARACTERISTICS	UNITS	MARTOL LVG 25 AQ
Color	-	0.35
Viscosity at 40°C	cSt	2.8
Flash point	°C	111
Density @ 25°C	kg/m ³	824

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

MARTOL

4-2017

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.