# **NEPTUNA 2T SUPER SPORT**







# Water cooled 2-cycle outboard engine oil

## **APPLICATIONS**

2-stroke engines

**NEPTUNA 2T SUPER SPORT** is specially formulated for pleasure craft engines that are water cooled. Mixing of the oil with the fuel should be in accordance with the manufacturer's recommendations. It is suitable for air-cooled engines calling for JASO FB quality level.

#### **PERFORMANCE**

**OEM** approvals

NMMA TC-W3 officially approved. RL-00288J

Other claims, OEMs

Meets air cooled requirements of API TC and JASO FB.
Conforming to the manufacturer's recommendations including:
Johnson, Mariner, Mercury, Suzuki, Yamaha...

#### **CUSTOMER BENEFITS**

High technical performance

- Fortified detergent capability prevents clogging of ports, ring sticking and spark plug fouling
- Increased lubrication capacity which prevents seizure
- Anti-rust and anti-corrosion properties protect engines during prolonged periods of layup.

## **CHARACTERISTICS**

TYPICAL CHARACTERISTICS—NEPTUNA 2T SUPER SPORT	
Density at 15°C, (ASTM D 1298)	0.863
Viscosity, cSt @ 100°C (ASTM D 445)	8.2
Viscosity, cSt @ 40°C (ASTM D 445)	54.5
Color, visual	Blue
Flash point °C (°F) ASTM D 92	138 (280)
Pour point °C (°F) ASTM D 97	-36 (-33)
Sulfated ash	Nil
NMMA certification number	RL-00288J

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418 Plano, Texas 75075 800-442-5823 or 469-241-0950 www.total-us.com

Neptuna 2T Super Sport Sheet updated: 5/10/2010 5 North Stiles Street Linden, New Jersey 07036 800-526-4127 or 908-862-9300 www.total-us.com.