

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

QUARTZ 9000 FUTURE XT 5W-20

SDS #: 091250

Section 1. Identification

GHS product identifier : QUARTZ 9000 FUTURE XT 5W-20

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Engine oil

Supplier's details

: TotalEnergies Marketing USA, Inc. 1201 Louisiana St. Suite 1800

Houston, TX 77002 Phone: 713-483-5000

ProductSafety@totalenergies.com

▼otalEnergies Marketing Canada Inc.

220 LAFLEUR LASALLE, QUEBEC H8R 4C9

Tel: (514) 595-7579 Fax: (514) 595-5950

Emergency telephone number (with hours of operation)

1-866-928-0789 (For Emergencies, call CARECHEM 24/7 Domestic) 1-215-207-0061 (For Emergencies, call CARECHEM 24/7 International)

Section 2. Hazards identification

OSHA/HCS status

: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

GHS label elements

Signal word : No signal word.

Hazard statements : No hazard statement.

Precautionary statements

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.
Hazards not otherwise : None known.

classified

Date of revision : 2024/11/25 1.01 USA ENGLISH 1/14



SDS #: 091250

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	Identifiers	GHS Classification
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	≥50 - ≤75	CAS: 72623-86-0	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	≥25 - ≤50	CAS: 72623-87-1	Not classified.
Distillates (petroleum), hydrotreated heavy paraffinic	≤5	CAS: 64742-54-7	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	CAS: 64742-54-7	Not classified.
Distillates (petroleum), solvent- dewaxed heavy paraffinic	≤1	CAS: 64742-65-0	ASPIRATION HAZARD - Category 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Additional information

: The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed person is

conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Date of revision : 2024/11/25 1.01 USA ENGLISH 2/14



SDS#: 091250

: No specific data. Ingestion

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

: 2024/11/25 1.01 USA **ENGLISH** Date of revision 3/14



SDS #: 091250

Small spill

: Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). See Section 10 for incompatible materials before handling or use.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Product/substance	Exposure limits
Lubricating oils (petroleum), C15-30,	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]
hydrotreated neutral oil-based	TWA 10 hours: 5 mg/m³. Form: Mist.
	STEL 15 minutes: 10 mg/m³. Form: Mist.
	OSHA PEL (United States, 5/2018) [Oil mist, mineral]
	TWA 8 hours: 5 mg/m³.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined] A4.
	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
Lubricating oils (petroleum), C20-50,	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]
hydrotreated neutral oil-based	TWA 10 hours: 5 mg/m³. Form: Mist.
	STEL 15 minutes: 10 mg/m³. Form: Mist.
Distillates (petroleum), hydrotreated heavy	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]
paraffinic	TWA 10 hours: 5 mg/m³. Form: Mist.
	STEL 15 minutes: 10 mg/m³. Form: Mist.
	OSHA PEL (United States, 5/2018) [Oil mist, mineral]
	TWA 8 hours: 5 mg/m³.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and
	severely refined] A4.
	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
Distillates (petroleum), hydrotreated heavy	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]
paraffinic	TWA 10 hours: 5 mg/m³. Form: Mist.
	STEL 15 minutes: 10 mg/m³. Form: Mist.
	OSHA PEL (United States, 5/2018) [Oil mist, mineral]

 Date of revision
 : 2024/11/25
 1.01
 USA
 ENGLISH
 4/14



paraffinic

QUARTZ 9000 FUTURE XT 5W-20

SDS #: 091250

TWA 8 hours: 5 mg/m³.

ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and

severely refined] A4.

TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.

NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]

TWA 10 hours: 5 mg/m³. Form: Mist. STEL 15 minutes: 10 mg/m³. Form: Mist.

OSHA PEL (United States, 5/2018) [Oil mist, mineral]

TWA 8 hours: 5 mg/m³.

ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined] A4.

TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.

Biological exposure indices

No exposure indices known.

Advisory OEL : Not available.

Distillates (petroleum), solvent-dewaxed heavy

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Hydrocarbon-proof gloves

Fluorinated rubber

nitrile rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: None under normal use conditions. If these are not sufficient to maintain exposure below the OEL, suitable respiratory protection must be worn.

Date of revision : 2024/11/25 1.01 USA ENGLISH 5/14



SDS #: 091250

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

Appearance

Physical state : Liquid. [limpid]

Color : Amber.

Odor : Characteristic.
Odor threshold : Not available.

pH : Not available.

Melting point/freezing point : Not available.

Pour point : -40°C (-40°F)

Boiling point : >316°C (>600.8°F)

Flash point : Open cup: >200°C (>392°F) [ASTM D 92]

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive (flammable) limits : Lower: 0.9% Upper: 7%
Vapor pressure : Not available.
Vapor density : Not available.

 Relative density
 : 0.852 [ASTM D 4052]

 Density
 : 0.852 g/cm³ [15°C]

Solubility(ies) :

Media	Result
water	Not soluble

Miscible with water : No.

Solubility in water : Insoluble

Partition coefficient: noctanol/water : Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available.

Kinematic (40°C (104°F)): 48 mm²/s (48 cSt) [ASTM D 445]

Flow time (ISO 2431) : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Date of revision : 2024/11/25 1.01 USA ENGLISH 6/14



SDS #: 091250

Conditions to avoid

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products

: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.53 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Lubricating oils (petroleum),	LC50 Inhalation Dusts	Rat	>5.54 mg/l	4 hours	OECD 403
C20-50, hydrotreated neutral oil-based	and mists				Read across
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Distillates (petroleum),	LC50 Inhalation Dusts	Rat - Male,	>5 mg/l	4 hours	OECD 403
hydrotreated heavy paraffinic	and mists	Female	J J		Read across
	LD50 Dermal	Rabbit - Male,	>5000 mg/kg	-	OECD 402
		Female			Read across
	LD50 Oral	Rat - Male,	>5000 mg/kg	-	OECD 401
		Female			Read across
Distillates (petroleum),	LC50 Inhalation Dusts	Rat	>5 mg/l	4 hours	OECD 403
hydrotreated heavy paraffinic	and mists				Read across
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
					Read across
	LD50 Oral	Rat - Male,	>5000 mg/kg	-	OECD 401
		Female			Read across
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
i e	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Irritation/Corrosion

Conclusion/Summary

Skin
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Respiratory
 Based on available data, the classification criteria are not met.

Sensitization

Conclusion/Summary

Date of revision : 2024/11/25 1.01 USA ENGLISH 7/14



nergies sps #: 091250

Skin : Based on available data, the classification criteria are not met.Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Conclusion/Summary: Based on available data, the classification criteria are not met.

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Conclusion/Summary: Based on available data, the classification criteria are not met.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Date of revision : 2024/11/25 1.01 USA ENGLISH 8/14



SDS #: 091250

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.53

Other information

Not available.

Section 12. Ecological information

Toxicity

Product/substance	Result	Species	Exposure	Test
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	5-30, hydrotreated neutral subcapitata		72 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - Pimephales promelas	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - Pseudokircheriella subcapitata	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	OECD 211
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EC50 >10000 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute NOEL >100 mg/l	Algae - Pseudokirchnerella subcapitata	72 hours	OECD 201
	Acute NOEL >1.93 mg/l	Micro-organism	10 minutes	-
	Chronic NOEC 10 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	-
Distillates (petroleum), hydrotreated heavy paraffinic	Acute LL50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute LL50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Chronic NOEL 10 mg/l	Crustaceans - Daphnia	21 days	-

Date of revision : 2024/11/25 1.01 USA ENGLISH 9/14



SDS #: 091250

	Chronic NOEL >1000 mg/l	magna Fish - Oncorhynchus mykiss	21 days	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EL50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - Oncorhynchus mykiss	96 hours	OECD 203
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	OECD 211

Persistence and degradability

Product/substance	Test	Result		Dose	Inoculum
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily -	28 days	-	Activated sludge
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily -	28 days	-	Activated sludge
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily -	28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F	31 % - Not readily -	28 days	-	Activated sludge
Product/substance	Aquatic half-life		Photolysis		Biodegradability

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	-	-	Not readily
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Not readily
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Not readily

Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	6.1	-	High
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	6.1	-	High
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	Low

Mobility in soil

Date of revision : 2024/11/25 1.01 USA ENGLISH 10/14



SDS#: 091250

Soil/water partition coefficient (Koc) **Mobility in soil**

: Not available.

: Given its physical and chemical characteristics, the product generally shows low soil mobility The product is insoluble and floats on water Loss by evaporation is limited

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and

Section 14. Transport information

	DOT Classification	IMDG	ICAO/IATA
UN/ID No	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Additional information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations

: Clean Water Act (CWA) 307: zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis (phosphorodithioate); zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)

TSCA 12(b) - Chemical export notification

Not applicable.

1.01 USA **ENGLISH** Date of revision : 2024/11/25 11/14



TotalEnergies sps #: 091250

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Not listed

Politicalits (HAPS)

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEALIST II Observiced

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

Name	%	Classification
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-	≥50 - ≤75	ASPIRATION HAZARD - Category 1
based Distillates (petroleum), hydrotreated heavy paraffinic	≤5	ASPIRATION HAZARD - Category 1

State regulations

Massachusetts : The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL; OIL

MIST, MINERAL; OIL MIST, MINERAL

New York : None of the components are listed.

New Jersey : The following components are listed: MINERAL OIL (UNTREATED and MILDLY

TREATED)

Pennsylvania : None of the components are listed.

California Prop. 65

To the best of our knowledge, this product does not contain any substances known to the State of California to cause cancer, developmental and/or reproductive harm

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Date of revision : 2024/11/25 1.01 USA ENGLISH 12/14



SDS #: 091250

Inventory list

Australia inventory (AIIC)

Canada inventory (DSL/NDSL)

China inventory (IECSC)

Europe inventory (EC)

Japan inventory

: All components are listed or exempted.

: All components are listed or exempted.

: All components are listed or exempted.

: At least one component is not listed.

: Japan inventory (CSCL): All components are listed or

exempted.

Japan inventory (ISHL): Not determined.

New Zealand Inventory of Chemicals (NZIoC)

Philippines inventory (PICCS)

Korea inventory (KECI)

Taiwan Chemical Substances Inventory (TCSI)

Thailand inventory
Turkey inventory

United States inventory (TSCA 8b)

Vietnam inventory

: Not determined.

: All components are listed or exempted.

: All components are listed or exempted.

: All components are listed or exempted.

: Not determined.

: Not determined.

: All components are listed or exempted.

: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of revision : 2024/11/25 1.01 USA ENGLISH 13/14



SDS #: 091250

Procedure used to derive the classification

Classification	Justification
Not classified.	

History

Date of revision: 2024/11/25previous revision date: 2024/11/14Version: 1.01

Karria alalamaniatiana

Key to abbreviations : ACGIH = American Conference of Governmental Industrial Hygienists

BCF = Bioconcentration Factor

EC50 = Half maximal effective concentration

EL50 = median Effective Loading

IC50 = Half maximal inhibitory concentration IDHL = Immediately dangerous to life or health

LC50 = Median lethal concentration

LD50 = Median lethal dose LL50 = median Lethal Loading

LogKow = logarithm of the octanol/water partition coefficient

N/A = Not available

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL = No Observed Effect Level

NOELR = No observed Effect Loading Rate

NOELR - No observed Effect Loading Rate

OECD = Organisation for Economic Co-operation and Development

OEL = Occupational Exposure Limit

QSAR = Quantitative Structure–Activity Relationship

REL = Recommanded Exposure Limit STEL = Short Term Exposure Limit TLV = Threshold Limit Value TWA = Time Weight Average VOC = Volatile Organic Compound

UVCB Substance of unknown or Variable composition, Complex reaction products

or Biological material

References : Not available.

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of revision : 2024/11/25 1.01 USA ENGLISH 14/14