

#### SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

## **QUARTZ 7000 FUTURE XT 5W-30**

**SDS #**: 091029

#### Section 1. Identification

GHS product identifier : QUARTZ 7000 FUTURE XT 5W-30

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Engine oil

Supplier's details

: TotalEnergies Marketing USA, Inc. 1201 Louisiana St. Suite 1800

Houston, TX 77002 Phone: 713-483-5000

ProductSafety@totalenergies.com
TotalEnergies Marketing Canada Inc.

220 LAFLEUR LASALLE, QUEBEC

H8R 4C9

Tel: (514) 595-7579 Fax: (514) 595-5950

Emergency telephone number (with hours of operation)

1-866-928-0789 (For Emergencies, call CARECHEM 24/7 Domestic) 1-215-207-0061 (For Emergencies, call CARECHEM 24/7 International)

### Section 2. Hazards identification

**OSHA/HCS** status

: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

**GHS label elements** 

Signal word : No signal word.

Hazard statements : No hazard statement.

**Precautionary statements** 

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.
Hazards not otherwise : None known.

classified

 Date of revision
 : 2025/02/11
 1
 USA
 ENGLISH
 1/16



**SDS #:** 091029

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	Identifiers	GHS Classification
Lubricating oils (petroleum), hydrotreated spent	≥50 - ≤75	CAS: 64742-58-1	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	≥10 - ≤25	CAS: 72623-86-0	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	≤10	CAS: 64742-54-7	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	CAS: 64742-54-7	Not classified.
Distillates (petroleum), solvent- dewaxed heavy paraffinic	≤1	CAS: 64742-65-0	ASPIRATION HAZARD - Category 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Additional information

: Mineral oil of petroleum origin. Product containing mineral oil with less than 3% DMSO extract

as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact : Immediately

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

**Skin contact**: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove

contaminated clothing and shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. If material has been swallowed and the exposed person is

conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

**Ingestion** : No known significant effects or critical hazards.

#### **Over-exposure signs/symptoms**

Eye contact : No specific data.

Inhalation : No specific data.

**Date of revision** : 2025/02/11 1 USA ENGLISH 2/16



SDS#: 091029

**Skin contact** : Adverse symptoms may include the following:

> irritation dryness cracking

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

: No specific treatment. Specific treatments

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

#### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use dry chemical, CO2, water spray (fog) or foam.

: Do not use water jet.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of revision 1 USA **ENGLISH** : 2025/02/11 3/16



**SDS #**: 091029

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

### Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). See Section 10 for incompatible materials before handling or use.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

Product/substance	Exposure limits
Lubricating oils (petroleum), hydrotreated spent Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	None. NIOSH REL (United States, 10/2020) [OIL MIST MINERAL] TWA 10 hours: 5 mg/m³. Form: Mist. STEL 15 minutes: 10 mg/m³. Form: Mist. OSHA PEL (United States, 5/2018) [Oil mist, mineral] TWA 8 hours: 5 mg/m³. ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined] A4. TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
Distillates (petroleum), hydrotreated heavy paraffinic	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL] TWA 10 hours: 5 mg/m³. Form: Mist. STEL 15 minutes: 10 mg/m³. Form: Mist. OSHA PEL (United States, 5/2018) [Oil mist, mineral] TWA 8 hours: 5 mg/m³. ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined] A4. TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
Distillates (petroleum), hydrotreated heavy paraffinic	NIOSH REL (United States, 10/2020) [OIL MIST MINERAL] TWA 10 hours: 5 mg/m³. Form: Mist. STEL 15 minutes: 10 mg/m³. Form: Mist. OSHA PEL (United States, 5/2018) [Oil mist, mineral] TWA 8 hours: 5 mg/m³. ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and

**Date of revision** : 2025/02/11 1 USA ENGLISH 4/16



**SDS #**: 091029

Distillates (petroleum), solvent-dewaxed heavy paraffinic

severely refined] A4.

TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.

NIOSH REL (United States, 10/2020) [OIL MIST MINERAL]

TWA 10 hours: 5 mg/m³. Form: Mist. STEL 15 minutes: 10 mg/m³. Form: Mist.

OSHA PEL (United States, 5/2018) [Oil mist, mineral]

TWA 8 hours: 5 mg/m<sup>3</sup>.

ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and

severely refined] A4.

TWA 8 hours: 5 mg/m<sup>3</sup>. Form: Inhalable fraction.

#### **Biological exposure indices**

No exposure indices known.

**Advisory OEL** 

: Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

Appropriate engineering controls

Environmental exposure controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Hydrocarbon-proof gloves

Fluorinated rubber nitrile rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: None under normal use conditions. If these are not sufficient to maintain exposure below the OEL, suitable respiratory protection must be worn.

**Date of revision** : 2025/02/11 1 USA ENGLISH 5/16



SDS#: 091029

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

**Appearance** 

**Physical state** : Liquid. [limpid] Color : Amber. [Dark] Odor : Characteristic. : Not available. **Odor threshold** pН : Not available. **Melting point/freezing point** : Not available. : -49°C (-56.2°F) **Pour point Boiling point** : >316°C (>600.8°F)

: Open cup: 204°C (399.2°F) [ASTM D 92] Flash point

**Evaporation rate** : Not available. : Not available. Flammability (solid, gas) Lower and upper explosive : Lower: 0.9% (flammable) limits Upper: 7% Vapor pressure : Not available. Vapor density : Not available.

**Relative density** : 0.86 [ASTM D 4052]

**Density** : 0.86 g/cm3 [15°C] [ASTM D 4052]

Solubility(ies)

Media	Result
water	Not soluble

Miscible with water : No.

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** 

: >247°C (>476.6°F)

**Decomposition temperature** 

: Not available.

: Dynamic (room temperature): Not available.

**Viscosity** 

Kinematic (room temperature): 11 mm<sup>2</sup>/s (11 cSt) [ASTM D 445]

Kinematic (40°C (104°F)): 60 mm<sup>2</sup>/s (60 cSt) [ASTM D 445]

Flow time (ISO 2431)

**Particle characteristics** 

: Not available.

Median particle size

: Not applicable.

### Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Date of revision USA **ENGLISH** 6/16 : 2025/02/11 1



**SDS #:** 091029

**Conditions to avoid** 

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

**Incompatible materials** : Strong oxidizing agents

Hazardous decomposition

products

: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

### **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/substance	Result
Lubricating oils (petroleum), hydrotreated	Rat - Inhalation - LC50 Vapor
spent	80.4 mg/l [1 hours]
	Rat - Inhalation - LC50 Vapor
	20.1 mg/l [4 hours]
	Rat - Inhalation - LC50 Dusts and mists
	5.1 mg/l [4 hours]
Lubricating oils (petroleum), C15-30,	Rat - Oral - LD50
hydrotreated neutral oil-based	>5000 mg/kg
	OECD [401]
	Rabbit - Dermal - LD50
	>5000 mg/kg
	OECD [402]
	Rat - Inhalation - LC50 Dusts and mists
	5.53 mg/l [4 hours]
Distillator (control cons) has before the library	OECD [403]
Distillates (petroleum), hydrotreated heavy	Rat - Male, Female - Oral - LD50
paraffinic	>5000 mg/kg
	OECD [401 Read across]
	Rabbit - Male, Female - Dermal - LD50
	>5000 mg/kg
	OECD [402 Read across]
	Rat - Male, Female - Inhalation - LC50 Dusts and mists >5 mg/l [4 hours]
	OECD [403 Read across]
Distillates (petroleum), hydrotreated heavy	Rat - Male, Female - Oral - LD50
paraffinic	>5000 mg/kg
paramino	OECD [401 Read across]
	Rabbit - Dermal - LD50
	>5000 mg/kg
	OECD [402 Read across]
	Rat - Inhalation - LC50 Dusts and mists
	>5 mg/l [4 hours]
	OECD [403 Read across]
Distillates (petroleum), solvent-dewaxed	Rabbit - Dermal - LD50
heavy paraffinic	>5000 mg/kg
	OECD [402]
of raviaion + 2025/02/41	LICA ENGLICH 7/46

**Date of revision** : 2025/02/11 1 USA ENGLISH 7/16



**SDS #:** 091029

Rat - Oral - LD50 >5000 mg/kg

OECD [420]

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours] OECD [403]

#### **Acute toxicity estimates**

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Lubricating oils (petroleum), hydrotreated spent Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	N/A	N/A	N/A	20.1	5.1
	N/A	N/A	N/A	N/A	5.53

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

#### **Respiratory corrosion/irritation**

Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitization

#### Skin

Based on available data, the classification criteria are not met.

#### Respiratory

Based on available data, the classification criteria are not met.

### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

Information on the likely routes of exposure

: Not available.

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Date of revision** : 2025/02/11 1 USA ENGLISH 8/16



sps#: 091029

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

**Ingestion**: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Other information :

Not available.

### Section 12. Ecological information

#### **Ecotoxicity**

Product/substance	Result	
Lubricating oils (petroleum), hydrotreated	Acute - NOEL - Fresh water	
spent	OECD [201]	
	Algae - Raphidocelis subcapitata	
	≥100 mg/l [72 hours]	
	Acute - LL50 - Fresh water	
	OECD [203]	
	Fish - <i>Pimephales promelas</i>	
	>100 mg/l [96 hours]	
	<u>Effect</u> : Mortality	
	Acute - EL50 - Fresh water	
	OECD [202]	
	Daphnia	
	>10000 mg/l [48 hours]	
	Effect: Mobility	
	Acute - NOEL - Fresh water	
	OECD [203]	
	Fish - <i>Pimephales promelas</i>	
	≥100 mg/l [96 hours]	
	Effect: Mortality	
	Acute - NOEL - Fresh water	
	OECD [202]	
	Daphnia 1100000000000000000000000000000000000	
	≥10000 mg/l [48 hours]	
	Effect: Mobility	
Lubricating oils (petroleum), C15-30,	Acute - LL50	
hydrotreated neutral oil-based	OECD 203	

**Date of revision** : 2025/02/11 1 USA ENGLISH 9/16



paraffinic

paraffinic

Distillates (petroleum), hydrotreated heavy

Distillates (petroleum), hydrotreated heavy

## **QUARTZ 7000 FUTURE XT 5W-30**

**SDS #**: 091029

Fish - *Pimephales promelas* >1000 mg/l [96 hours]

Acute - EL50 OECD [202]

Crustaceans - Daphnia magna

>10000 mg/l [48 hours]

Effect: Mobility
Acute - EL50
OECD 201

Algae - Pseudokircheriella subcapitata

>100 mg/l [72 hours] <u>Effect</u>: (growth rate) **Chronic - NOEL** OECD 211

Crustaceans - Daphnia magna

>1000 mg/l [21 days] Effect: Reproduction

**Chronic - NOEL** 

**OECD 201** 

Algae - Pseudokircheriella subcapitata

>100 mg/l [72 hours] Effect: (growth rate)

Acute - EC50

OECD [202]

Crustaceans - Daphnia magna

>10000 mg/l [48 hours]

Effect: Mobility
Acute - EC50
OECD [201]

Algae - Pseudokirchneriella subcapitata

>100 mg/l [72 hours] <u>Effect</u>: (growth rate) **Chronic - NOEL** 

Crustaceans - Daphnia magna

>1000 mg/l [21 days] <u>Effect</u>: Reproduction **Chronic - NOEL** 

OECD [201]

Algae - Pseudokirchneriella subcapitata

>100 mg/l [72 hours] Effect: (growth rate)

Acute - LL50

OECD [202]

Crustaceans - Daphnia magna

>10000 mg/l [48 hours]

Effect: Mobility
Acute - LL50

OECD [201]

Algae - Pseudokirchneriella subcapitata

>100 mg/l [72 hours] <u>Effect</u>: (growth rate) **Chronic - NOEL** 

Fish - Oncorhynchus mykiss

>1000 mg/l [21 days] <u>Effect</u>: Mortality **Chronic - NOEL** 

Crustaceans - Daphnia magna

 Date of revision
 : 2025/02/11
 1
 USA
 ENGLISH
 10/16



heavy paraffinic

# **QUARTZ 7000 FUTURE XT 5W-30**

SDS#: 091029

10 mg/l [21 days] Effect: Reproduction **Chronic - NOEL** OECD [201]

Algae - Pseudokirchneriella subcapitata

>100 mg/l [72 hours] Effect: (growth rate)

Distillates (petroleum), solvent-dewaxed Acute - LL50 **OECD 203** 

> Fish - Oncorhynchus mykiss >1000 mg/l [96 hours]

Acute - EL50 OECD [202]

Crustaceans - Daphnia magna >10000 mg/l [48 hours]

Effect: Mobility **Chronic - NOEL** OECD [211]

Crustaceans - Daphnia magna

>1000 mg/l [21 days] Effect: Reproduction

#### Persistence and degradability

Product/substance	Result
Lubricating oils (petroleum), C15-30,	OECD 301F
hydrotreated neutral oil-based Distillates (petroleum), hydrotreated heavy	31% [28 days] - Not readily OECD 301F
paraffinic	31% [28 days] - Not readily
Distillates (petroleum), hydrotreated heavy	OECD 301F
paraffinic Distillates (petroleum), solvent-dewaxed	31% [28 days] - Not readily OECD 301F
heavy paraffinic	31% [28 days] - Not readily

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Lubricating oils (petroleum),	-	-	Readily
hydrotreated spent			-
Lubricating oils (petroleum),	-	-	Not readily
C15-30, hydrotreated neutral			
oil-based			
Distillates (petroleum),	-	-	Not readily
hydrotreated heavy paraffinic			
Distillates (petroleum),	-	-	Not readily
hydrotreated heavy paraffinic			
Distillates (petroleum),	-	-	Not readily
solvent-dewaxed heavy			
paraffinic			

#### **Bioaccumulative potential**

Date of revision : 2025/02/11 1 USA **ENGLISH** 11/16



091029

SDS#:

Product/substance	LogK <sub>ow</sub>	BCF	Potential
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	6.1	-	High
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc) **Mobility in soil** 

Not available.

: Given its physical and chemical characteristics, the product generally shows low soil mobility The product is insoluble and floats on water Loss by evaporation is limited

#### Other adverse effects

No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and

### Section 14. Transport information

			-
	DOT Classification	IMDG	ICAO/IATA
UN/ID No	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

#### **Additional information**

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of revision 1 USA **ENGLISH** : 2025/02/11 12/16



**SDS #**: 091029

Transport in bulk according : Not available.

to IMO instruments

### Section 15. Regulatory information

U.S. Federal regulations : Clean Water Act (CWA) 307: zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis

(phosphorodithioate); zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)

#### TSCA 12(b) - Chemical export notification

Not applicable.

Clean Air Act Section 112 : Not listed

(b) Hazardous Air Pollutants (HAPs)

**Clean Air Act Section 602** 

**Class I Substances** 

: Not listed

**Clean Air Act Section 602** 

Class II Substances

: Not listed

**DEA List I Chemicals** 

DEA LIST I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals
(Facential Chemicals)

: Not listed

(Essential Chemicals)

#### **SARA 302/304**

#### **Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : Not applicable.

Composition/information on ingredients

Name	%	Classification
Lubricating oils (petroleum), hydrotreated spent	≥50 - ≤75	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-	≥10 - ≤25	ASPIRATION HAZARD - Category 1
based Distillates (petroleum), hydrotreated heavy paraffinic	≤10	ASPIRATION HAZARD - Category 1

#### **State regulations**

Massachusetts : The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL; OIL

MIST, MINERAL

New York
None of the components are listed.
New Jersey
None of the components are listed.
Pennsylvania
None of the components are listed.

California Prop. 65

To the best of our knowledge, this product does not contain any substances known to the State of California to cause cancer, developmental and/or reproductive harm

#### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

**Date of revision** : 2025/02/11 1 USA ENGLISH 13/16



**SDS #**: 091029

Not listed.

#### **Montreal Protocol**

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

#### **Inventory list**

Australia inventory (AIIC)

Canada inventory (DSL/NDSL)

**China inventory (IECSC)** 

**Europe inventory (EC)** 

Japan inventory

: All components are listed or exempted.

: All components are listed or exempted.

: All components are listed or exempted.

: At least one component is not listed.

: Japan inventory (CSCL): At least one component is not

listed.

Japan inventory (ISHL): At least one component is not listed.

**New Zealand Inventory of Chemicals (NZIoC)** 

Philippines inventory (PICCS)

Korea inventory (KECI)

**Taiwan Chemical Substances Inventory (TCSI)** 

Thailand inventory

**Turkey inventory** 

**United States inventory (TSCA 8b)** 

Vietnam inventory

: Not determined.

: Not determined.

: At least one component is not listed.

: All components are listed or exempted.

: At least one component is not listed.

: Not determined.


: All components are listed or exempted.

: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

### Section 16. Other information

**Hazardous Material Information System (U.S.A.)** 



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

**Date of revision** : 2025/02/11 1 USA ENGLISH 14/16



**SDS #**: 091029



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### Procedure used to derive the classification

Classification	Justification
Not classified.	

#### **History**

Date of revision : 2025/02/11

previous revision date : No previous validation

Version :

**Key to abbreviations** : ACGIH = American Conference of Governmental Industrial Hygienists

BCF = Bioconcentration Factor

EC50 = Half maximal effective concentration

EL50 = median Effective Loading

IC50 = Half maximal inhibitory concentration IDHL = Immediately dangerous to life or health

LC50 = Median lethal concentration

LD50 = Median lethal dose LL50 = median Lethal Loading

LogKow = logarithm of the octanol/water partition coefficient

N/A = Not available

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL = No Observed Effect Level

NOELR = No observed Effect Loading Rate

OECD = Organisation for Economic Co-operation and Development

OEL = Occupational Exposure Limit

QSAR = Quantitative Structure-Activity Relationship

REL = Recommanded Exposure Limit STEL = Short Term Exposure Limit TLV = Threshold Limit Value TWA = Time Weight Average

VOC = Volatile Organic Compound

UVCB Substance of unknown or Variable composition, Complex reaction products

or Biological material

References : Not available.

Indicates information that has changed from previously issued version.

**Notice to reader** 

**Date of revision** : 2025/02/11 1 USA ENGLISH 15/16



**SDS #**: 091029

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Date of revision** : 2025/02/11 1 USA ENGLISH 16/16