

CITGO MULTI-PURPOSE AIR-COOLED 2-CYCLE ENGINE OIL



Date 07/15

DESCRIPTION: CITGO Multi-Purpose Air-Cooled 2-Cycle Engine Oil is designed for use in air-cooled two-stroke engines.

QUALITIES: CITGO Multi-Purpose Air-Cooled 2-Cycle Engine Oil is engineered for lower smoke and protection against exhaust port blocking, combustion chamber and piston deposits, ring sticking and scuffing, and wear in today's high RPM air-cooled 2-cycle engines.

APPLICATIONS: CITGO Multi-Purpose Air-Cooled 2-Cycle Engine Oil can be used in motorcycles, generators, lawnmowers, and hand held power equipment such as leaf blowers, trimmers, and chainsaws operating in hot, dirty, dusty environments and high loads for extended periods. Do not use in engines requiring an NMMA® TC-W3® product. Consult owners manual for Fluid Specification.

TYPICAL PROPERTIES:

CITGO MULTI-PURPOSE AIR-COOLED 2-CYCLE ENGINE OIL

Material Code	621610001
Gravity, ASTM D 4052, °API	31.5
Density, lb/gal, at 60°F	7.23
Flash Point, PMCC, ASTM D 93, °F (°C)	201 (94)
COC, ASTM D 92, °F (°C)	221 (105)
Viscosity, ASTM D 445, cSt at 40°C	61
cSt at 100°C	8.6
ASTM D 2161, SUS at 100°F	295
SUS at 210°F	55
Viscosity Index, ASTM D 2270	125
Pour Point, ASTM D 97, °F (°C)	-42 (-36)
Appearance, Color	Purple
Sulfated Ash, ASTM D 874, %	0.11
Total Base Number, ASTM D 2896, mg KOH/g	1.6

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.