PRODUCT INFORMATION SHEET

Houston, Texas

LubesCS@CITGO.com

lubeshelp@CITGO.com

Mystik[®] JT-5[®] Tractor **Trans-Hydraulic Fluid**



	 A multi-function hydraulic, transmission, differential, and brake fluid for tractors and other off-road equipment with a single reservoir for all four systems. Provides excellent performance in modern agricultural equipment, with outstanding protection against gear wear, brake chatter, and oxidation. Particularly suited for hard-working applications where an added level of protection is desired. Proven field performance.
FEATURES & BENEFITS	 Excellent filterability characteristics along with rust and corrosion inhibitors, water tolerance, and wide temperature range performance. Contains special friction modifiers for superior brake chatter control. Formulated to resist leakage. Formulated with advanced detergent/dispersant, antiwear, antioxidant, antirust, and antifoam additives.
APPLICATIONS	 Recommended for use in equipment where the following fluids are specified: AGCO Power Fluid 821XL Allison C-4 CASE MS 1205, 1206, 1207, 1209, 1210 CAT TO-2 Denison HF-0, HF-1, HF-2 Eaton Hydraulics Ford New Holland ESN-M2C134-D Kubota UDT API GL-4 Case New Holland: MAT 3525 John Deere J20C (including for use in John Deere IVT transmissions) Massey Ferguson M-1145 White Q-1826
CITGO Petroleum Corporation	Customer Service Line Product Answer Line Online at Manufactured in USA M20014 1-800-331-4068 1-800-248-4684 www.mystiklubes.com Manufactured in USA M20014

Mystik

663509002

APPLICATIONS

IS Suitable for use in the following equipment:

- AGCOCASE IH
- KH Deutz
- Ford
- John Deere
- Komatsu
- Kubota
- Massey Ferguson
- New Holland
- Volvo WB101

Material Code

• White

PROPERTIES

Typical Properties for Mystik JT-5 Tractor Trans-Hydraulic Fluid:

$ \ \ \ \ \ \ \ \ \ \ \ \ \ $	

API Gravity, ASTM D4052, °API	31.7
Density, lb/gal	7.22
Specific Gravity	0.867
Viscosities:	
at -35°C, cP	18,080
at 40°C, cSt	62.8
at 100°C, cSt	10.0
Viscosity Index	148
Flash Point, COC, ASTM D92, °F (°C)	457 (236)
Pour Point, ASTM D97, °F (°C)	-45 (-43)
Falex, ASTM D3233-A, lbs	1,350
4-Ball EP Wear, ASTM D4172, mm	0.38
Color	Light Amber

Mystik and JT-5 are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

CITGO Petroleum Corporation Houston, Texas Manufactured in USA

Customer Service Line 1-800-331-4068 Product Answer Line 1-800-248-4684 lubeshelp@CITGO.com

Customer Service Email LubesCS@CITGO.com Online at www.mystiklubes.com