



## Mobil Delvac 1™ LE 5W-30

Mobil Commercial-Vehicle-Lube , United States

Fully Synthetic Heavy-Duty Diesel Engine Oil

### Product Description

Mobil Delvac 1™ LE 5W-30 is a fully synthetic, heavy-duty diesel engine oil that combines advanced engine protection for modern low emissions vehicles with enhanced fuel economy potential<sup>1</sup> and other sustainability-related benefits such as engine durability, emissions system protection and extended drain capability.

Mobil Delvac 1 LE 5W-30 utilizes state-of-the-art technology to deliver exceptional performance and is well suited for an extensive array of diesel-powered commercial vehicles for both on- and off-highway use in industries such as transportation, mining, construction and agriculture. Mobil Delvac 1 LE 5W-30 meets or exceeds an extremely broad range of industry and manufacturer specifications from around the world.

<sup>1</sup> Relative to 15W-40 engine oil - Actual fuel economy improvement is dependent on vehicle/equipment type, outside temperature, driving conditions and your current fluid viscosity.

### Features and Benefits

High output, low emissions engines significantly increase demands on engine lubricants. Tighter engine design reduces oil consumption, resulting in less fresh oil makeup to replenish depleted additives. Thermal stresses on the lubricant are increased with the use of inter-coolers and turbochargers. Higher fuel injection and cylinder pressures and retarded timing improve burn efficiency, but also increase engine temperatures, volatility, and soot loading of the oil. The advanced technology in Mobil Delvac 1 LE 5W-30 delivers exceptional performance in these severe conditions while protecting emissions systems.

Features	Advantages and Potential Benefits
Advanced Wear Protection	Engine Durability
Enhanced Fuel Economy Potential	Reduced Fuel Consumption
Extended Drain Interval Capability	Fewer Oil Changes and Less Oil Disposal
Emissions System Protection	Emissions System Durability and Performance
Excellent Low Temperature Performance	Easier Starting in Cold Weather

### Applications

- Heavy Duty Diesel Engines including Euro V/VI and US EPA 2007/2010 Modern Low Emissions Vehicles, Utilizing Technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR)
- Heavy Duty Diesel Engines using low sulfur diesel fuels and many biodiesel fuel formulations
- Naturally Aspirated and Turbo-Charged Diesel Powered Equipment
- On-Highway Short-Haul and Long-Haul Trucks and Buses
- Off-Highway Mining, Construction and Agricultural Equipment

Please refer to the owners handbook for OEM application requirements and oil drain intervals for your vehicle or equipment

## Specifications and Approvals

**This product has the following approvals:**

Detroit Fluids Specification 93K218

DEUTZ DQC IV-10 LA

Mack EO-O Premium Plus

MAN M 3691

MAN M 3677

MTU Oil Category 3.1

RENAULT TRUCKS RLD-2

RENAULT TRUCKS RLD-3

VOLVO VDS-3

VOLVO VDS-4

**This product is recommended for use in applications requiring:**

MAN M 3271-1

MAN M 3575

**This product meets or exceeds the requirements of:**

API CI-4

API CI-4 PLUS

API CJ-4

API SN

CATERPILLAR ECF-3

Cummins CES 20081

DAF Extended Drain

Ford WSS-M2C171-E

Scania Low Ash

ACEA E6

ACEA E7

ACEA E9

## Properties and Specifications

Property	
Grade	SAE 5W-30
Ash, Sulfated, mass%, ASTM D874	1
Density @ 15 C, g/cm3, ASTM D4052	0.855
Flash Point, °C, ASTM D92	234
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	69
Pour Point, °C, ASTM D97	-51
Total Base Number, mgKOH/g, ASTM D2896	10
Viscosity Index, ASTM D2270	168

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

## Exxon Mobil Corporation

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved