

BIODEGRADABLE LITHIUM COMPLEX # 2 EXTREME PRESSURE GREASE

Description

RSC *EnviroLogic*® Grease 2 is a multi-purpose, biodegradable Lithium Complex #2 extreme pressure grease. It demonstrates excellent dropping point, water resistance, and mechanical stability over an extremely wide range of temperatures. It is also formulated to possess excellent oxidative stability, corrosion protection, and extreme pressure/antiwear performance. Specially designed for high performance in industrial equipment applications where incidental environmental exposure of the lubricant is a cause for concern. It is biodegradable and will not cause harm to aquatic life or animals.

RSC *EnviroLogic*[®] Grease 2 is an Environmentally Acceptable Lubricant (EAL) compliant with 2013 US EPA Vessel General Permit (VGP).

RSC *EnviroLogic*[®] Greases meet the requirements for various manufacturers. Visit our <u>website</u> or contact customer service for a full list of OEM approvals.

Typical Properties

	#2
ASTM D217	265 – 295
ASTM D2265	+450
ASTM D1742*	1.7
ASTM D2596	315
ASTM D2266	0.43
ASTM D1743	Pass
ASTM D4048	1b
ASTM D2509	55
ASTM D1264	5.0 max.
ASTM D445	+55
Visual	Amber
Visual	Smooth, slightly tacky
	ASTM D2265 ASTM D1742* ASTM D2596 ASTM D2266 ASTM D1743 ASTM D4048 ASTM D2509 ASTM D1264 ASTM D445 Visual

^{*}Oil separation from lubricating grease during storage

NOTICE: While this information is presented in good faith and believed to be accurate, RSC Bio Solutions does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and RSC Bio Solutions disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

Updated: 12/7/16

For more information about RSC Bio Solutions, visit us at rscbio.com or call +1 704.684.6100.



