According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: | SDS Number: | Print Date: 02/25/2021 |
|---------|----------------|--------------|--------------------------------|
| 2.1 | 02/24/2021 | 800001010457 | Date of last issue: 09/11/2020 |

SECTION 1. IDENTIFICATION

Product name : Shell Gas Compressor Oil S3 PSN 220

Product code : 001D8382

Manufacturer or supplier's details

| Manufacturer/Supplier | : Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA |
|-----------------------|--|
| SDS Request | : (+1) 877-276-7285 |
| Customer Service | : |

Emergency telephone number

| Spill Information | : | 877-504-9351 |
|--------------------|---|--------------|
| Health Information | : | 877-242-7400 |

Recommended use of the chemical and restrictions on use Recommended use

: Compressor oil.

SECTION 2. HAZARDS IDENTIFICATION

| GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) | | | |
|---|---|---|--|
| Skin sensitisation | ategory 1 | | |
| GHS label elements | | | |
| Hazard pictograms | !> | | |
| Signal word | arning | | |
| Hazard statements | EALTH HAZARDS: 317 May cause an all NVIRONMENTAL HA | ical hazard under GHS criteria. ergic skin reaction. | |
| Precautionary statements | r evention: 280 Wear protective g ce protection. | loves/ protective clothing/ eye protection/ | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

Version Revision Date: 2.1 02/24/2021

SDS Number: 800001010457

Print Date: 02/25/2021 Date of last issue: 09/11/2020

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water and soap. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label: Contains thiophosphate alkyl ester.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Substance / Mixture | : | Mixture |
|---------------------|---|--|
| Chemical nature | : | Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regula- tion (EC) 1272/2008, Annex VI, Part 3, Note L). |
| | | * contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8. |

Hazardous components

| Chemical name | Synonyms | CAS-No. | Concentration (% w/w) |
|--|---|--------------|-----------------------|
| Interchangeable low viscosity base oil (<20,5 cSt @40°C) * | | Not Assigned | 0 - 90 |
| Thiophosphate alkyl ester | 2-ethylhexyl 10-ethyl-4-[[2- [(2- ethylhexyl)oxy]- 2- oxoethyl]thio]- 7-oxo-8-oxa- 3,5-dithia-4- phosphatetra- decanoate 4- oxide | 83547-95-9 | 0.1 - 0.9 |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: | SDS Number: | Print Date: 02/25/2021 |
|---------|----------------|--------------|--------------------------------|
| 2.1 | 02/24/2021 | 800001010457 | Date of last issue: 09/11/2020 |

SECTION 4. FIRST-AID MEASURES

| If inhaled | : | No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice. |
|--|---|---|
| In case of skin contact | : | Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment. |
| In case of eye contact | : | Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention. |
| If swallowed | : | In general no treatment is necessary unless large quantities are swallowed, however, get medical advice. |
| Most important symptoms and effects, both acute and delayed | : | Skin sensitisation (allergic skin reaction) signs and symptoms may include itching and/or a rash. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. |
| Protection of first-aiders | : | When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings. |
| Indication of any immediate medical attention and special treatment needed | : | Treat symptomatically. |

SECTION 5. FIRE-FIGHTING MEASURES

| Suitable extinguishing media | : | Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only. |
|---|---|--|
| Unsuitable extinguishing media | : | Do not use water in a jet. |
| Specific hazards during fire- fighting | : | Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. |
| Specific extinguishing meth- ods | : | Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. |
| Special protective equipment | : | Proper protective equipment including chemical resistant |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: | SDS Number: | Print Date: 02/25/2021 |
|---------|----------------|--------------|--------------------------------|
| 2.1 | 02/24/2021 | 800001010457 | Date of last issue: 09/11/2020 |
| | | | |

for firefighters gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protec- tive equipment and emer- gency procedures | : | Avoid contact with skin and eyes. |
|---|---|--|
| Environmental precautions | : | Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. |
| Additional advice | : | For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet. |

SECTION 7. HANDLING AND STORAGE

| Technical measures | : | Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material. |
|---|---|---|
| Advice on safe handling | : | Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires. |
| Avoidance of contact | : | Strong oxidising agents. |
| Product Transfer | : | Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation. |
| Further information on stor- age stability | : | Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version 2.1 | Revision Date: 02/24/2021 | SDS Number: 800001010457 | Print Date: 02/25/2021 Date of last issue: 09/11/2020 |
|--------------------|------------------------------|-----------------------------|---|
| | | Store at ambier | nt temperature. |
| Packaging material | | | al: For containers or container linings, use mild nsity polyethylene. erial: PVC. |
| Cont | ainer Advice | | ontainers should not be exposed to high tem- use of possible risk of distortion. |

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of | Control parame- ters / Permissible | Basis |
|-------------------|--------------|------------------------|---------------------------------------|----------|
| | | exposure) | concentration | |
| Oil mist, mineral | Not Assigned | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| Oil mist, mineral | | TWA (Inhal- | 5 mg/m3 | ACGIH |
| | | able particu- | | |
| | | late matter) | | |

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

| | Engineering measures | : | |
|--|----------------------|---|--|
|--|----------------------|---|--|

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: | SDS Number: | Print Date: 02/25/2021 |
|---------|----------------|--------------|--------------------------------|
| 2.1 | 02/24/2021 | 800001010457 | Date of last issue: 09/11/2020 |

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

| Respiratory protection : | No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. |
|--------------------------|--|
| Hand protection | |
| Remarks : | Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with break-through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version 2.1 | Revision Date: 02/24/2021 | DS Number: 0000101045 | Print Date: 02/25/2021 7 Date of last issue: 09/11/2020 |
|----------------|------------------------------|---|---|
| | | Glove thic | on the exact composition of the glove material. ness should be typically greater than 0.35 mm on the glove make and model. |
| Eye | e protection | Wear full f | ace shield if splashes are likely to occur. |
| Ski | n and body protection | | nical resistant gloves/gauntlets and boots. Where shing, also wear an apron. |
| Pro | tective measures | | rotective equipment (PPE) should meet recom- ational standards. Check with PPE suppliers. |
| The | ermal hazards | : Not applic | able |
| En | vironmental exposure co | rols | |
| Ge | neral advice | vant enviro of the enviro necessary charged to municipal discharge Local guid | opriate measures to fulfill the requirements of rele- onmental protection legislation. Avoid contamination ronment by following advice given in Section 6. If prevent undissolved material from being dis- waste water. Waste water should be treated in a or industrial waste water treatment plant before to surface water. elines on emission limits for volatile substances oserved for the discharge of exhaust air containing |
| SECTIO | N 9. PHYSICAL AND CH | IICAL PROP | ERTIES |
| App | bearance | : Liquid at | oom temperature. |
| Col | our | : amber | |
| Od | our Threshold | : Data not | available |
| pН | | : Not applie | able |
| ροι | ır point | : -24 °C / - Method: l | 1 °F Inspecified |

| Appearance | : | Liquid at room temperature. |
|---|---|---|
| Colour | : | amber |
| Odour Threshold | : | Data not available |
| рН | : | Not applicable |
| pour point | : | -24 °C / -11 °F Method: Unspecified |
| Melting / freezing point | | Data not available |
| Initial boiling point and boiling range | : | > 280 °C / 536 °F estimated value(s) |
| Flash point | : | 268 °C / 514 °F |
| | | Method: ASTM D92 (COC) |
| Evaporation rate | : | Data not available |
| Flammability (solid, gas) | : | Data not available |
| Upper explosion limit / upper | : | Typical 10 %(V) |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version 2.1 | Revision Date: 02/24/2021 | | S Number: 0001010457 | Print Date: 02/25/2021 Date of last issue: 09/11/2020 |
|----------------|--|---|-----------------------------------|--|
| flan | nmability limit | | | |
| | ver explosion limit / Lower nmability limit | : | Typical 1 %(V) | |
| Vap | oour pressure | : | < 0.5 Pa (20 °C / | 68 °F) |
| | | | estimated value(| s) |
| Rel | ative vapour density | : | > 1 estimated value(| s) |
| Rel | ative density | : | 0.888 (15 °C / 59 |)°F) |
| Der | nsity | : | 888 kg/m3 (15.0 Method: ASTM D | |
| | ubility(ies) Water solubility | : | negligible | |
| : | Solubility in other solvents | : | Data not availabl | e |
| | tition coefficient: n- anol/water | : | 0 | ation on similar products) |
| Aut | o-ignition temperature | : | > 320 °C / 608 °F | = |
| Dec | composition temperature | : | Data not availabl | e |
| | cosity √iscosity, dynamic | : | Data not availabl | e |
| , | Viscosity, kinematic | : | 17.9 mm2/s (100 | °C / 212 °F) |
| | | | Method: ASTM D | 0445 |
| | | | 211 mm2/s (40.0 | °C / 104.0 °F) |
| | | | Method: ASTM D | 0445 |
| Exp | losive properties | : | Not classified | |
| Oxi | dizing properties | : | Data not availabl | e |
| Cor | nductivity | : | This material is n | ot expected to be a static accumulator. |

SECTION 10. STABILITY AND REACTIVITY

| Reactivity | : | The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. |
|--------------------|---|--|
| Chemical stability | : | Stable. |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version 2.1 | Revision Date: 02/24/2021 | | S Number: 0001010457 | Print Date: 02/25/2021 Date of last issue: 09/11/2020 |
|----------------|------------------------------|-----|-------------------------|--|
| Poss tions | ibility of hazardous reac- | • : | Reacts with stron | ng oxidising agents. |
| Cond | ditions to avoid | : | Extremes of tem | perature and direct sunlight. |
| Incor | mpatible materials | : | Strong oxidising | agents. |
| Haza prod | ardous decomposition ucts | : | No decompositic | on if stored and applied as directed. |

SECTION 11. TOXICOLOGICAL INFORMATION

| Basis for assessment | : | Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |
|----------------------|---|---|
| | | |

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

| Acute oral toxicity | LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met. |
|---------------------------|---|
| Acute inhalation toxicity | Remarks: Based on available data, the classification criteria are not met. |
| Acute dermal toxicity | LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met. |

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Expected to be a skin sensitizer.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: | SDS Number: | Print Date: 02/25/2021 |
|---------|----------------|--------------|--------------------------------|
| 2.1 | 02/24/2021 | 800001010457 | Date of last issue: 09/11/2020 |

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

| IARC | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. |
|------|---|
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. |
| NTP | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

Version Revision Date: 2.1 02/24/2021

SDS Number: 800001010457

Print Date: 02/25/2021 Date of last issue: 09/11/2020

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

| Basis for assessment | : | Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract). | |
|--|---|---|--|
| Ecotoxicity | | | |
| <u>Product:</u> Toxicity to fish (Acute toxici- ty) | : | Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met. | |
| Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) | : | Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met. | |
| Toxicity to algae (Acute tox- icity) | : | Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met. | |
| Toxicity to fish (Chronic tox- icity) | : | Remarks: Data not available | |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | Remarks: Data not available | |
| Toxicity to microorganisms (Acute toxicity) | : | Remarks: Data not available | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Versic 2.1 | on Revision Date: 02/24/2021 | | 0S Number: 0001010457 | Print Date: 02/25/2021 Date of last issue: 09/11/2020 | |
|---------------|--|------|---|---|--|
| P | Persistence and degradabil | lity | | | |
| P | Product: | | | | |
| | Biodegradability : | | Remarks: Not readily biodegradable. Major constituents are inherently biodegradable, but contains components that may persist in the environment. | | |
| E | Bioaccumulative potential | | | | |
| <u>P</u> | Product: | | | | |
| B | Bioaccumulation : | | Remarks: Contains components with the potential to bioac- cumulate. | | |
| N | lobility in soil | | | | |
| P | Product: | | | | |
| N | <i>l</i> obility | : | | under most environmental conditions. vill adsorb to soil particles and will not be | |
| | | | Remarks: Floats of | on water. | |
| c | Other adverse effects | | | | |
| P | Product: | | | | |
| | Additional ecological infor- nation | : | ozone creation po Product is a mixtu | one depletion potential, photochemical otential or global warming potential. Ire of non-volatile components, which will not in any significant quantities under normal | |
| | | | Poorly soluble mix Causes physical f | xture. ouling of aquatic organisms. | |
| | | | | ot cause chronic toxicity to aquatic organ- tions less than 1 mg/l. | |

SECTION 13. DISPOSAL CONSIDERATIONS

| Disposal methods | | |
|---------------------|--|---------------------|
| Waste from residues | Recover or recycle if possible. It is the responsibility of the waste generator to detern toxicity and physical properties of the material general determine the proper waste classification and dispose ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in w courses | ated to al meth- |
| | Waste product should not be allowed to contaminate ground water, or be disposed of into the environment Waste, spills or used product is dangerous waste. | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version 2.1 | Revision Date: 02/24/2021 | SDS Numb 800001010 | • | Print Date: 02/25/2021 Date of last issue: 09/11/2020 |
|----------------------|------------------------------|---|--|--|
| | | posed o to a rec collecto Do not o | of in accord ognised co r or contra dispose of to the grou | m a spillage or tank cleaning should be dis- dance with prevailing regulations, preferably ollector or contractor. The competence of the actor should be established beforehand. tank water bottoms by allowing them to und. This will result in soil and groundwater |
| | | Pollutio | n from Shi | ternational Convention for the Prevention of ps (MARPOL 73/78) which provides tech- ontrolling pollutions from ships. |
| Conta | minated packaging | to a rec the colle Dispose | ognized co ector or co Il should b | lance with prevailing regulations, preferably ollector or contractor. The competence of intractor should be established beforehand. ie in accordance with applicable regional, I laws and regulations. |
| Local Rema | legislation rks | • | | e in accordance with applicable regional, I laws and regulations. |

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: | SDS Number: |
|---------|----------------|--------------|
| 2.1 | 02/24/2021 | 800001010457 |

Print Date: 02/25/2021 Date of last issue: 09/11/2020

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

| SARA 311/312 Hazards | : | Respiratory or skin sensitisation |
|----------------------|---|---|
| SARA 313 | : | This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. |

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

| Highly refined mineral oil (IP346 <3%) | 64741-88-4 |
|--|------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 |
| barium salts | 25619-56-1 |
| Distillates (petroleum), hydrotreated light | 64742-47-8 |

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

California List of Hazardous Substances

| Highly refined mineral oil (IP346 <3%) | 64741-88-4 |
|--|------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 |

California Permissible Exposure Limits for Chemical Contaminants

Highly refined mineral oil (IP346 <3%)</th>64741-88-4

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

| EINECS | : | Not established. |
|--------|---|------------------------|
| TSCA | : | All components listed. |
| DSL | : | All components listed. |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: |
|---------|----------------|
| 2.1 | 02/24/2021 |

SDS Number: 800001010457

Print Date: 02/25/2021 Date of last issue: 09/11/2020

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 2, 1, 0 tivity)

Full text of other abbreviations

| ACGIH OSHA Z-1 | : | USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants |
|---|----|---|
| ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms | :: | 8-hour, time-weighted average 8-hour time weighted average The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc). The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites. |
| | | ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Center on Ecotoxicology and Toxicolo- gy Of Chemicals ECHA = European Inventory of Existing Commercial Chemical Substances EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substances Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer IATA = International Air Transport Association |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Gas Compressor Oil S3 PSN 220

| Version | Revision Date: | SDS Number: | Print Date: 02/25/2021 |
|---------|----------------|---|--|
| 2.1 | 02/24/2021 | 800001010457 | Date of last issue: 09/11/2020 |
| | | IL50 = Inhibitor IMDG = Interna INV = Chinese IP346 = Institu determination of KECI = Korea E LC50 = Lethal 0 LD50 = Lethal 1 LL/EL/IL = Leth LL50 = Lethal L MARPOL = Inte Pollution From NOEC/NOEL = served Effect L OE_HPV = Occ PBT = Persiste PICCS = Philip Substances PNEC = Predic REACH = Regi Chemicals RID = Regulatid gerous Goods I SKIN_DES = S STEL = Short to TRA = Targeted TSCA = US To TWA = Time-W | Ational Maritime Dangerous Goods Chemicals Inventory te of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. Tal Loading/Effective Loading/Inhibitory loading Loading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume nt, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical Ated No Effect Concentration stration Evaluation And Authorisation Of |

A vertical bar () in the left margin indicates an amendment from the previous version.

| Sources of key data used to compile the Safety Data Sheet | : | The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc). |
|---|---|--|
| | | |

Revision Date : 02/24/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN