

PENNZOIL PLATINUM™ CVT-2 Premium, Synthetic

Technology, Push Belt CVT Fluid

TECHNICAL DATA SHEET



Pennzoil Platinum™ CVT-2 fluid is a CVT fluid fulfilling JATCO and Nissan FF and SF specifications. This fluid can be used as well for a variety of other vehicle manufacturer's with Push Belt CVTs.

PERFORMANCE, FEATURES & BENEFITS

Excellent thermal and oxidative stability

Excellent low temperature fluidity

Smooth speed changing due to delicately balanced friction coefficient between belt and pulley

Excellent shear stability

Offers high wear protection

Highest production quality control system in place to ensure consistent product quality

MAIN APPLICATIONS

This product can be used in all service fill applications requiring NS-2 or NS-2V Fluid.

These applications include:

Chrysler CVTF+4 (CVTF Green 1V), Suzuki, Mercedes Benz 236.20, Mini EZL 799, GM/Saturn DEX-CVT, Mitsubishi CVTF-J1.

TYPICAL PHYSICAL CHARACTERISTICS

Properties			Method	Pennzoil Platinum™ CVT-2
Kinematic Viscosity	@40°C	mm ² /s	JIS K 2283	32.6
Kinematic Viscosity	@100°C	mm ² /s	JIS K 2283	7.01
Viscosity Index			JIS K 2283	184
Density	@15°C	kg/m ³	JIS K 2249	0.852
Flash Point (COC)		°C	JIS K 2265 7	212
Pour Point		°C	JIS K 2269	-50

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

Please consult the vehicle manual carefully before utilizing this fluid.

This fluid is NOT interchangeable with Nissan CVT Fluid NS-1.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Nissan NS-2V Replacement Fluid

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

To find the right Pennzoil® product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

PENNZOIL PLATINUM™ CVT-2 Premium, Synthetic Technology, Push Belt CVT Fluid

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

Pennzoil Platinum™ CVT-2 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from www.epc.shell.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Help Desk.