According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:	Print Date: 04/21/2020	
1.4	04/20/2020	800010028556	Date of last issue: 11/07/2019	
SECTION	1. IDENTIFICATION			

Product name : Shell Omala S4 GXV 220

Product code : 001F8458

Manufacturer or supplier's details

Manufacturer/Supplier	: Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA
SDS Request	: (+1) 877-276-7285
Customer Service	:

Emergency telephone number

Spill Information	:	877-504-9351
Health Information	:	877-242-7400

Recommended use of the chemical and restrictions on use Recommended use : Gear oil

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements		
Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention: No precautionary phrases. Response: No precautionary phrases.
Precautionary statements	:	No precautionary phrases. Response:
Precautionary statements	:	No precautionary phrases. Response: No precautionary phrases. Storage:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:
1.4	04/20/2020	800010028556

Print Date: 04/21/2020 Date of last issue: 11/07/2019

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Blend of polyolefins and additives.

Hazardous components

No hazardous ingredients

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Indication of any immediate medical attention and special treatment needed	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media :

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version 1.4	Revision Date: 04/20/2020		DS Number: 00010028556	Print Date: 04/21/2020 Date of last issue: 11/07/2019
Unsui media	table extinguishing	:	Do not use water	in a jet.
Speci fightir	fic hazards during fire- Ig	:	A complex mixtur gases (smoke). Carbon monoxide occurs.	ustion products may include: e of airborne solid and liquid particulates and e may be evolved if incomplete combustion nic and inorganic compounds.
Speci ods	fic extinguishing meth-	:		measures that are appropriate to local cir- the surrounding environment.
	al protective equipment efighters	:	gloves are to be v large contact with Breathing Appara a confined space.	equipment including chemical resistant vorn; chemical resistant suit is indicated if spilled product is expected. Self-Contained tus must be worn when approaching a fire in Select fire fighter's clothing approved to Is (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of
		vapours, mists or aerosols.
		Use the information in this data sheet as input to a risk as-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Versio 1.4	n Revision Date: 04/20/2020		0S Number: 0010028556	Print Date: 04/21/2020 Date of last issue: 11/07/2019
				circumstances to help determine appropri- ife handling, storage and disposal of this
A	dvice on safe handling	:	Avoid inhaling var When handling pr worn and proper l	oduct in drums, safety footwear should be nandling equipment should be used. of any contaminated rags or cleaning mate-
A	voidance of contact	:	Strong oxidising a	igents.
Р	roduct Transfer	:		and bonding procedures should be used nsfer operations to avoid static accumulation.
-	urther information on stor- ge stability	:	place.	htly closed and in a cool, well-ventilated led and closable containers.
			Store at ambient	emperature.
Ρ	ackaging material	:	Suitable material: steel or high dens Unsuitable materi	
С	ontainer Advice	:		ainers should not be exposed to high tem- e of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:	Print Date: 04/21/2020
1.4	04/20/2020	800010028556	Date of last issue: 11/07/2019

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	The level of protection and types of controls necessa vary depending upon potential exposure conditions. S controls based on a risk assessment of local circums Appropriate measures include: Adequate ventilation to control airborne concentration	Select tances.
	Where material is heated, sprayed or mist formed, the greater potential for airborne concentrations to be get	
	General Information: Define procedures for safe handling and maintenance controls.	ə of
	Educate and train workers in the hazards and control measures relevant to normal activities associated wit product.	
	Ensure appropriate selection, testing and maintenance equipment used to control exposure, e.g. personal pr equipment, local exhaust ventilation.	otective
	Drain down system prior to equipment break-in or ma nance. Retain drain downs in sealed storage pending dispos	
	subsequent recycle. Always observe good personal hygiene measures, su washing hands after handling the material and before drinking, and/or smoking. Routinely wash work clothin protective equipment to remove contaminants. Disca taminated clothing and footwear that cannot be clean Practice good housekeeping.	e eating, ing and ard con-
Personal protective equipm		
Respiratory protection	No respiratory protection is ordinarily required under conditions of use. In accordance with good industrial hygiene practices, tions should be taken to avoid breathing of material. If engineering controls do not maintain airborne conce tions to a level which is adequate to protect worker he select respiratory protection equipment suitable for th cific conditions of use and meeting relevant legislation Check with respiratory protective equipment suppliers Where air-filtering respirators are suitable, select an a priate combination of mask and filter. Select a filter suitable for the combination of organic g and vapours and particles [Type A/Type P boiling poi >65°C (149°F)].	precau- entra- ealth, ne spe- n. s. appro- gases
Hand protection Remarks	Where hand contact with the product may occur the u gloves approved to relevant standards (e.g. Europe: US: F739) made from the following materials may pro suitable chemical protection. PVC, neoprene or nitrile	EN374, ovide

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

/ersion .4	Revision Date: 04/20/2020	SDS Number: 800010028556	Print Date: 04/21/2020 Date of last issue: 11/07/2019
		usage, e.g. sistance of glove suppl Personal hy Gloves mus gloves, han cation of a r For continue through time 480 minutes short-term/s recognize th may not be time maybe and replace a good prec dependent of Glove thick	ability and durability of a glove is dependent on frequency and duration of contact, chemical re- glove material, dexterity. Always seek advice from iers. Contaminated gloves should be replaced. rgiene is a key element of effective hand care. to only be worn on clean hands. After using ds should be washed and dried thoroughly. Appli- non-perfumed moisturizer is recommended. bus contact we recommend gloves with break- e of more than 240 minutes with preference for > s where suitable gloves can be identified. For splash protection we recommend the same but nat suitable gloves offering this level of protection available and in this case a lower breakthrough acceptable so long as appropriate maintenance ment regimes are followed. Glove thickness is no lictor of glove resistance to a chemical as it is on the exact composition of the glove material. hess should be typically greater than 0.35 mm on the glove make and model.
Eye p	protection		s handled such that it could be splashed into eyes yewear is recommended.
Skin a	and body protection	work clothe	tion is not ordinarily required beyond standard s. ractice to wear chemical resistant gloves.
Prote	ctive measures		otective equipment (PPE) should meet recom- tional standards. Check with PPE suppliers.
Therr	nal hazards	: Not applical	ble
Envir	ronmental exposure of	controls	
Gene	eral advice	vant enviror of the enviror necessary, charged to municipal o discharge to Local guide	priate measures to fulfill the requirements of rele- mental protection legislation. Avoid contaminatio onment by following advice given in Section 6. If prevent undissolved material from being dis- waste water. Waste water should be treated in a r industrial waste water treatment plant before o surface water. lines on emission limits for volatile substances served for the discharge of exhaust air containing
ECTION	9. PHYSICAL AND C	HEMICAL PROPE	RTIES
Anno	arance	· liquid	

Appearance : liquid

- Colour clear :
- Odour : Slight hydrocarbon

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version 1.4	Revision Date: 04/20/2020		S Number: 0010028556	Print Date: 04/21/2020 Date of last issue: 11/07/2019
Odd	our Threshold	:	Data not availabl	e
pН		:	Not applicable	
pou	r point	:	Data not available	e
Initi rang	al boiling point and boiling ge	:	> 280 °C / 536 °F estimated value(s	
Flas	sh point	:	>= 200 °C / >= 39	92 °F
			Method: Unspeci	fied
Eva	poration rate	:	Data not available	e
Flar	mmability (solid, gas)	:	Data not available	e
	per explosion limit / upper nmability limit	:	Typical 10 %(V)	
	ver explosion limit / Lower nmability limit	:	Typical 1 %(V)	
Vap	oour pressure	:	< 0.5 Pa (20 °C /	68 °F)
			estimated value(s	s)
Rela	ative vapour density	:	> 1 estimated value(s	s)
Rela	ative density	:	0.864 (15.0 °C / 8	59.0 °F)
Der	nsity	:	864 kg/m3 (15.0 Method: DIN EN	
	ubility(ies) Water solubility	:	negligible	
:	Solubility in other solvents	:	Data not available	e
	tition coefficient: n- anol/water	:	log Pow: > 6 (based on inform	ation on similar products)
Aut	o-ignition temperature	:	> 320 °C / 608 °F	=
Dec	composition temperature	:	Data not availabl	e
	cosity √iscosity, dynamic	:	Data not availabl	e
v	Viscosity, kinematic	:	220 mm2/s (40.0	°C / 104.0 °F)
			Method: ASTM D	0445

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Versi 1.4	on Revision Date: 04/20/2020		S Number: 0010028556	Print Date: 04/21/2020 Date of last issue: 11/07/2019
	Explosive properties	:	Not classified	
	Oxidizing properties	:	Data not availab	le
	Conductivity		This material is r	not expected to be a static accumulator.
SEC	TION 10. STABILITY AND R	EAC	ΤΙVITY	
	Reactivity	:		s not pose any further reactivity hazards in listed in the following sub-paragraph.
	Chemical stability	:	Stable.	
	Possibility of hazardous reac- tions	• :	Reacts with stron	ng oxidising agents.
	Conditions to avoid	:	Extremes of tem	perature and direct sunlight.
	Incompatible materials		Strong oxidising	agents

Incompatible materials		Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
		whole, father than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on availa-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:	Print D
1.4	04/20/2020	800010028556	Date c

Print Date: 04/21/2020 Date of last issue: 11/07/2019

ble data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity	
Product:	
	: Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are

not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:	Print Date: 04/21/2020
1.4	04/20/2020	800010028556	Date of last issue: 11/07

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

issue: 11/07/2019

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity	
Product: Toxicity to fish (Acute toxici- : ty)	Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other : aquatic invertebrates (Acute toxicity)	Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae (Acute tox- : icity)	Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

rsion I	Revision Date: 04/20/2020		DS Number: 0010028556	Print Date: 04/21/2020 Date of last issue: 11/07/2019
			Based on availa	ble data, the classification criteria are not me
Toxic icity)	ity to fish (Chronic tox-	:	Remarks: Data	not available
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)		:	Remarks: Data	not available
Toxicity to microorganisms (Acute toxicity)		:	Remarks: Data	not available
Persi	stence and degradabili	ity		
Produ	uct:			
Biode	gradability	:	Major constituer	eadily biodegradable. hts are inherently biodegradable, but contain t may persist in the environment.
Bioad	ccumulative potential			
Prod	uct:			
Bioac	cumulation	:	Remarks: Conta cumulate.	ins components with the potential to bioac-
Mobi	lity in soil			
Prod	uct:			
Mobil	ity	:		l under most environmental conditions. t will adsorb to soil particles and will not be
			Remarks: Floats	s on water.
Othe	r adverse effects			
Prod	uct:			
Additi matio	onal ecological infor- n	:	ozone creation Product is a mix	ozone depletion potential, photochemical potential or global warming potential. ture of non-volatile components, which will r ir in any significant quantities under normal e.
			Poorly soluble n	nixture

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version 1.4	Revision Date: 04/20/2020	SDS Nu 8000100		Print Date: 04/21/2020 Date of last issue: 11/07/2019
		dete ods	rmine the pro n compliance ot dispose in	cal properties of the material generated to oper waste classification and disposal meth- e with applicable regulations. to the environment, in drains or in water
		grou	nd water, or l	ould not be allowed to contaminate soil or be disposed of into the environment. sed product is dangerous waste.
Contar	ninated packaging	to a the c Disp	recognized c collector or co osal should b	dance with prevailing regulations, preferably ollector or contractor. The competence of ontractor should be established beforehand. be in accordance with applicable regional, il laws and regulations.
Local Remar	legislation ks			be in accordance with applicable regional, Il laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:	Print Date: 04/21/2020
1.4	04/20/2020	800010028556	Date of last issue: 11/07/2019

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

		<u> </u>	
Components	CAS-No.	Component TPQ (lbs)	
SARA 302 Extremely Hazardous Substances Threshold Planning Quantity			

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards	No SARA Hazards
----------------------	-----------------

SARA 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis)
	reporting levels established by SARA Title III, Section 313.

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Xylene, mixed isomers 1330-20-7 0 %

US State Regulations

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

Abbreviations and Acronyms	:	The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:	Print Date: 04/21/2020
1.4	04/20/2020	800010028556	Date of last issue: 11/07/2019
		Carriage of Dar AICS = Australi ASTM = Americ BEL = Biologica BTEX = Benze CAS = Chemica CEFIC = Europ CLP = Classific COC = Clevela DIN = Deutsche DMEL = Derive DNEL = Derive DNEL = Derive DNEL = Canada EC = European EC50 = Effectiv ECETOC = Eur gy Of Chemical ECHA = Europe EINECS = The Chemical Subs EL50 = Effectiv ENCS = Japan Inventory EWC = Europe GHS = Globally Labelling of Ch IARC = Internat IC50 = Inhibitor IL50 = Inhibitor IL50 = Inhibitor IDS0 = Inhibitor IDS0 = Inhibitor IDS0 = Lethal I CS0 = Lethal I UL/EL/IL = Leth LL50 = Lethal I MARPOL = Inter Pollution From NOEC/NOEL = served Effect L OE_HPV = Occ PBT = Persiste PICCS = Philip Substances PNEC = Predic REACH = Regi Chemicals RID = Regulatic gerous Goods I	es Institut fur Normung d Minimal Effect Level d No Effect Level Domestic Substance List commission re Concentration fifty opean Center on Ecotoxicology and Toxicolo- s ean Chemicals Agency European Inventory of Existing Commercial tances e Loading fifty ese Existing and New Chemical Substances an Waste Code r Harmonised System of Classification and emicals tional Agency for Research on Cancer ional Agency for Research on Cancer ional Agency for Research on Cancer ional Air Transport Association y Concentration fifty y Level fifty tional Maritime Dangerous Goods Chemicals Inventory te of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. al Loading/Effective Loading/Inhibitory loading .oading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume nt, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical ted No Effect Concentration stration Evaluation And Authorisation Of

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GXV 220

Version	Revision Date:	SDS Number:	Print Date: 04/21/2020
1.4	04/20/2020	800010028556	Date of last issue: 11/07/2019

STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	04/20/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN