

READILY BIODEGRADABLE, INDUSTRIAL ISO 320 GEAR OIL

Description

RSC *EnviroLogic*[®] GO 320 is a readily biodegradable gear oil for use in industrial applications. RSC *EnviroLogic*[®] GO 320 is an ISO 320 viscosity grade, AGMA 6EP oil, having the highest anti-wear/extreme pressure properties, excellent corrosion and rust protection, and outstanding system cleanliness characteristics. The excellent performance characteristics of RSC *EnviroLogic*[®] GO 320 make it suitable in a wide variety of industrial gear applications where incidental exposure of the oil to the environment is of concern. Examples are off-shore oil and gas, marine transportation & construction, steel milling, mining, and power utility operations. In addition, it can directly replace petroleum oil based products of the same viscosity, yet has reduced environmental impact in the event of a leak or spill, as it is readily biodegradable and non-sheening*.

RSC *EnviroLogic*[®] GO 320 Series meets most stringent extreme FZG wear/extreme pressure test combinations of temperature, speed and pressure.

It is an Environmentally Acceptable Lubricant (EAL) compliant with 2013 US EPA Vessel General Permit (VGP).

RSC *EnviroLogic*[®] GO Series meets the requirements for various manufacturers. Visit our [website](#) or contact customer service for a full list of OEM approvals.

Property	Method	Spec.	Result
Kinematic Viscosity	D445		
At 40°C, cSt		288.0 – 352.0	320
At 100°C, cSt			41
Viscosity Index	D2270		>175
Density (60°F), g/cm ³	D4052		0.85
Pour Point, °C	D97	-9 min.	-36
Flash Point (COC), °C	D92		180
Copper Corrosion 3 Hrs. @ 100°C	D130	1b min.	1b
Steel Pin Corrosion (4 hours, 140°F)	D665		
Deionized Water		Pass	Pass
Synthetic Salt Water		Pass	Pass
Foam Properties	D892		
Sequence I, mL	Tendency/Stability	50/0	10/0
Sequence II, mL	Tendency/Stability	50/0	10/0
Sequence III, mL	Tendency/Stability	50/0	10/0

READILY BIODEGRADABLE, INDUSTRIAL ISO 320 GEAR OIL

Property	Method	Spec.	Result
Demulse Properties (54°C) Oil / Water / Emulsion Minutes	D1401	30 max.	40 / 40 / 0 10
TOST Oxidation Hours to TAN of 2.0 mg KOH/g	D943		>1500 ---
Air Release @ 90°C	D3427 9 max.		8.0
Four Ball EP Weld Load LWI, kg	D2783 250 min. 45 min.		315 48.7
Four Ball Wear 54°C/1800 rpm/20 kg/1 Hr.	D4172 Mod. Scar, mm		0.34
Timken Wear OK Load, lbs. Fail Load, lbs.	D2782 60 min. ---		> 60 > 65
FZG (Pass Stage	D5182		>14
Gear Oil Oxidation Δ 100°C K.V. @ 312 Hrs.	D2893B 6% max.		4.2%
Elastomer Compatibility Buna N (100°C 168 Hours) Viton (150°C 168 Hours)	D471 D471		Pass Pass
Biodegradability	D7373	60% min.	> 60
Ecotoxicity Fathead minnow Daphnia Algae	OECD 203 OECD 202 OECD 201	>100mg/L >100mg/L >100mg/L	> 1000 mg/L > 130 mg/L > 120 mg/L

* CFR40 Part 435B

NOTICE: While this information is presented in good faith and believed to be accurate, RSC Bio Solutions does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and RSC Bio Solutions disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

Updated: 12/21/16

For more information about RSC Bio Solutions, visit us at rscbio.com or call +1 704.684.6100.



KEEP MOVING. FORWARD.

rscbio.com



600 Radiator Road
Indian Trail, NC 28079-7643
800.661.3558
+1 704.684.6100

EnviroLogic® is a registered trademark of RSC Bio Solutions.
Copyright© 2016. RSC Bio Solutions. All Rights Reserved.