According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version	Revision Date:	SDS Number:	Print Date: 10/14/2020				
1.1	10/13/2020	800010042432	Date of last issue: 08/17/2020				
SECTION 1. IDENTIFICATION							

Product name : Shell Omala S3 W 150

Product code : 001I5528

Manufacturer or supplier's details

Manufacturer/Supplier	: Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA
SDS Request	: (+1) 877-276-7285
Customer Service	:

Emergency telephone number

Spill Information	: 877-504-9351
Health Information	: 877-242-7400

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms	: No Hazard Symbol required	
Signal word	: No signal word	
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria. 	
Precautionary statements	 Prevention: No precautionary phrases. Response: 	
	No precautionary phrases.	
	Storage: No precautionary phrases.	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version	Revision Date:	SDS Number:	Print Date: 10/14/2020
1.1	10/13/2020	800010042432	Date of last issue: 08/17/2020

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture :		Mixture
-----------------------	--	---------

Chemical nature	:	Blend of polyalkylene glycol and additives.
-----------------	---	---

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Polyether phosphate		Not Assigned	1 - 2.49

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Indication of any immediate medical attention and special treatment needed	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Vers 1.1	sion	Revision Date: 10/13/2020		0S Number: 0010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
	Suitable	e extinguishing media	:		y or fog. Dry chemical powder, carbon diox- may be used for small fires only.
	Unsuita media	able extinguishing	:	Do not use water	in a jet.
	Specific fighting	c hazards during fire-	:	A complex mixture gases (smoke). Carbon monoxide occurs.	istion products may include: e of airborne solid and liquid particulates and may be evolved if incomplete combustion tic and inorganic compounds.
	Specific ods	c extinguishing meth-	:	5 5	measures that are appropriate to local cir- he surrounding environment.
	Special for firef	l protective equipment ighters	:	gloves are to be w large contact with Breathing Appara a confined space.	equipment including chemical resistant yorn; chemical resistant suit is indicated if spilled product is expected. Self-Contained tus must be worn when approaching a fire in Select fire fighter's clothing approved to s (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

Technical measures :		Use local exhaust ventilation if there is risk of inhalation of	
----------------------	--	---	--

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Versi 1.1	on Revision Date: 10/13/2020		0S Number: 0010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
			sessment of local	aerosols. on in this data sheet as input to a risk as- circumstances to help determine appropri- fe handling, storage and disposal of this
Advice on safe handling		:	Avoid inhaling var When handling pr worn and proper h	oduct in drums, safety footwear should be nandling equipment should be used. of any contaminated rags or cleaning mate-
ŀ	Avoidance of contact	:	Strong oxidising a	gents.
-	Further information on stor- age stability	:	place.	htly closed and in a cool, well-ventilated led and closable containers.
			Store at ambient t	emperature.
F	Packaging material	:	Suitable material: steel or high dens Unsuitable materi	
(Container Advice	:		ainers should not be exposed to high tem- e of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-	-	
		late matter)		

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Meth-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version	Revision Date:	SDS Number:	Print Date: 10/14/2020
1.1	10/13/2020	800010042432	Date of last issue: 08/17/2020

ods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is
	greater potential for airborne concentrations to be generated.
	 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.
Personal protective equipment	
Respiratory protection :	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precau- tions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentra- tions to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the spe- cific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

ersion I	Revision Date: 10/13/2020		Number: 0042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
		>6	5°C (149°F)].
	l protection emarks	gld US su gld us gld ca Fo Gl ca Fo thr 48 sh rea tim a q de Gl	oves approve S: F739) mad itable chemic oves Suitabil age, e.g. free stance of glov ove suppliers ersonal hygie oves must of oves, hands tion of a non or continuous ough time of 0 minutes wi ort-term/spla cognize that ay not be avai ne maybe ac d replaceme good predictor pendent on to ove thicknes	ontact with the product may occur the use of ed to relevant standards (e.g. Europe: EN374, de from the following materials may provide cal protection. PVC, neoprene or nitrile rubber ity and durability of a glove is dependent on quency and duration of contact, chemical re- ve material, dexterity. Always seek advice from s. Contaminated gloves should be replaced. ene is a key element of effective hand care. nly be worn on clean hands. After using should be washed and dried thoroughly. Appli- -perfumed moisturizer is recommended. a contact we recommend gloves with break- f more than 240 minutes with preference for > here suitable gloves can be identified. For ash protection we recommend the same but suitable gloves offering this level of protection ailable and in this case a lower breakthrough ceptable so long as appropriate maintenance ent regimes are followed. Glove thickness is not or of glove resistance to a chemical as it is the exact composition of the glove material. s should be typically greater than 0.35 mm the glove make and model.
Eye p	protection			andled such that it could be splashed into eyes wear is recommended.
Skin a	and body protection	wo	ork clothes.	is not ordinarily required beyond standard ice to wear chemical resistant gloves.
Prote	ective measures			ctive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.
Therr	mal hazards	: No	ot applicable	
Envir	ronmental exposure o	ontrols		
Gene	eral advice	va of ch mu dis Lo	nt environme the environn cessary, pre arged to was unicipal or in scharge to su cal guideline	ate measures to fulfill the requirements of rele- ental protection legislation. Avoid contaminatio nent by following advice given in Section 6. If vent undissolved material from being dis- ste water. Waste water should be treated in a dustrial waste water treatment plant before urface water. es on emission limits for volatile substances ved for the discharge of exhaust air containing

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

vapour.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Vers 1.1	sion	Revision Date: 10/13/2020		S Number: 0010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
	Appear	ance	:	no data available	
	Colour		:	Not applicable	
	Odour		:	Slight hydrocarbo	on
	Odour ⁻	Threshold	:	Data not availabl	e
	рН		:	Not applicable	
	pour po	bint	:	Method: Unspeci Not applicable	fied
	Initial b range	oiling point and boiling	:	> 280 °C / 536 °F estimated value(s	
	Flash p	oint	:	225 °C / 437 °F	
				Method: ASTM D	92 (COC)
	Evapor	ation rate	:	Data not availabl	e
	Flamma	ability (solid, gas)	:	Data not availabl	e
		explosion limit / upper bility limit	:	Typical 10 %(V)	
		explosion limit / Lower bility limit	:	Typical 1 %(V)	
	Vapour	pressure	:	< 0.5 Pa (20 °C /	68 °F)
				estimated value(5)
	Relative	e vapour density	:	> 1 estimated value(s	3)
	Relative	e density	:	1.0379 (15.0 °C /	′ 59.0 °F)
	Density	,	:	1,038 kg/m3 (15. Method: ASTM D	
	Solubili Wat	ty(ies) er solubility	:	soluble	
	Solu	bility in other solvents	:	Data not availabl	e
	Partition octanol	n coefficient: n- /water	:	Data not availabl	e
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	-
	Decom	position temperature	:	Data not availabl	e

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Versio 1.1	n Revision Date: 10/13/2020		S Number: 0010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020			
Viscosity Viscosity, dynamic		:	Data not availab	le			
	Viscosity, kinematic	:	146.0 mm2/s (40.0 °C / 104.0 °F)				
			Method: ASTM [Method: ASTM D445			
			30.0 mm2/s (100) °C / 212 °F)			
			Method: ASTM	D445			
E	xplosive properties	:	Not classified				
0	Oxidizing properties		Data not available				
C	onductivity	:	This material is r	not expected to be a static accumulator.			
SECTI	ON 10. STABILITY AND R	EAC	ΤΙVITY				
R	eactivity	:		s not pose any further reactivity hazards in listed in the following sub-paragraph.			
С	hemical stability	:	Stable.				

,		
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a
	whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Ρ	ro	du	ct:	

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version	Revision Date:	SDS Number:	Print Date: 10/14/2020
1.1	10/13/2020	800010042432	Date of last issue: 08/17/2020

 Acute dermal toxicity
 : LD50 (Rabbit): > 5,000 mg/kg

 Remarks: Low toxicity:
 Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version	Revision Date:	SDS Number:	Print Date: 10/14/2020
1.1	10/13/2020	800010042432	Date of last issue: 08/17/2020

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

÷

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on product data, a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity <u>Product:</u> Toxicity to fish (Acute toxici- ty)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.

Toxicity to daphnia and other :

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

rsion	Revision Date: 10/13/2020		0S Number: 0010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
aquat toxicit	ic invertebrates (Acute y)		Remarks: LL/EL Practically non to Based on availa	
Toxic icity)	ity to algae (Acute tox-	:	Remarks: LL/EL Practically non to Based on availa	5
Toxic icity)	ity to fish (Chronic tox-	:	Remarks: Data r	not available
	ity to daphnia and other ic invertebrates (Chron- icity)	:	Remarks: Data r	not available
	ity to microorganisms e toxicity)	:	Remarks: Data r	not available
Persi	stence and degradabili	ity		
<u>Produ</u> Biode	u <u>ct:</u> gradability	:	Remarks: Readi	ly biodegradable.
Bioad	cumulative potential			
<u>Produ</u> Bioac	u <u>ct:</u> cumulation	:	Remarks: Does	not bioaccumulate.
Mobi	lity in soil			
Prod	uct:			
Mobil	ity	:		under most environmental conditions. will adsorb to soil particles and will not be
Othe	adverse effects			
Prod	uct:			
Additi matio	onal ecological infor- n	:	ozone creation p Product is a mix	zone depletion potential, photochemical optential or global warming potential. ture of non-volatile components, which will not ir in any significant quantities under normal e.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version 1.1	Revision Date: 10/13/2020		S Number: 010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
			determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses	
			ground water, or	ould not be allowed to contaminate soil or be disposed of into the environment. sed product is dangerous waste.
Conta	minated packaging	: Dispose in accordance with prevailing regulations, p to a recognized collector or contractor. The compete the collector or contractor should be established before Disposal should be in accordance with applicable re- national, and local laws and regulations.		ollector or contractor. The competence of ontractor should be established beforehand. De in accordance with applicable regional,
Local Rema	legislation rks		•	be in accordance with applicable regional, Il laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Phosphoric acid	7664-38-2	5000	*

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version	Revision Date:	SDS Number:	Print Date: 10/14/2020
1.1	10/13/2020	800010042432	Date of last issue: 08/17/2020

*: Calculated RQ exceeds reasonably attainable upper limit. Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

 Phosphoric acid
 7664-38-2
 0.009 %

US State Regulations

Pennsylvania Right To Know

Propan-2-ol

67-63-0

California Prop. 65

WARNING: This product can expose you to chemicals including distillates (petroleum), hydrotreated light, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	Not established.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Version 1.1	Revision Date: 10/13/2020	SDS Number: 800010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
OSHA		 USA. Occupation its for Air Conta 8-hour, time-wei 8-hour time wei The standard al 	ighted average ghted average obreviations and acronyms used in this docu- ked up in reference literature (e.g. scientific
		Hygienists ADR = Europea Carriage of Dan AICS = Australia ASTM = America BEL = Biologica BTEX = Benze CAS = Chemica CEFIC = Europe CLP = Classifica COC = Clevelar DIN = Deutsche DMEL = Derive DNEL = Derive DNEL = Derive DNEL = Canada EC = European EC50 = Effective ECHA = European EC50 = Effective ENCS = The Chemical Subst EL50 = Effective ENCS = Japane Inventory EWC = European GHS = Globally Labelling of Che IARC = Internati IC50 = Inhibitory IMDG = Internati IC50 = Lethal C LD50 = Lethal C LD50 = Lethal L MARPOL = Internati Pollution From S	es Institut fur Normung d Minimal Effect Level d No Effect Level Domestic Substance List Commission e Concentration fifty opean Center on Ecotoxicology and Toxicolo- sean Chemicals Agency European Inventory of Existing Commercial ances e Loading fifty ese Existing and New Chemical Substances an Waste Code Harmonised System of Classification and emicals ional Agency for Research on Cancer onal Air Transport Association y Concentration fifty / Level fifty tional Maritime Dangerous Goods Chemicals Inventory e of Petroleum test method N° 346 for the f polycyclic aromatics DMSO-extractables existing Chemicals Inventory Concentration fifty Ose fifty per cent. al Loading/Effective Loading/Inhibitory loading oading fifty rnational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 150

Versior 1.1	n Revision Date: 10/13/2020	SDS Number: 800010042432	Print Date: 10/14/2020 Date of last issue: 08/17/2020
		PBT = Persisten PICCS = Philipp Substances PNEC = Predicte REACH = Regis Chemicals RID = Regulation gerous Goods by SKIN_DES = Sk STEL = Short tel TRA = Targeted TSCA = US Tox TWA = Time-We	in Designation rm exposure limit Risk Assessment ic Substances Control Act
A	vertical bar () in the left ma	rgin indicates an ame	ndment from the previous version.
со	ources of key data used to mpile the Safety Data neet	sources of inform	are from, but not limited to, one or more nation (e.g. toxicological data from Shell material suppliers' data, CONCAWE, EU

Revision Date : 10/13/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IUCLID date base, EC 1272 regulation, etc).

US / EN