According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.1	08/06/2020	800010042375	Date of last issue: 08/06/2020

SECTION 1. IDENTIFICATION

Product name : Shell Omala S3 W 100

Product code : 001I5471

Manufacturer or supplier's details

Manufacturer/Supplier	: Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA
SDS Request	: (+1) 877-276-7285
Customer Service	:

Emergency telephone number

Spill Information	: 877-504-9351
Health Information	: 877-242-7400

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention: No precautionary phrases.
		Deenenee
		Response:
		No precautionary phrases.
		•
		No precautionary phrases.
		No precautionary phrases. Storage:
		No precautionary phrases. Storage: No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.1	08/06/2020	800010042375	Date of last issue: 08/06/2020

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Blend of polyalkylene glycol and additives.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Polyether phosphate		Not Assigned	1 - 2.49

** polymer exempt.

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Indication of any immediate medical attention and special treatment needed	:	Treat symptomatically.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.1	08/06/2020	800010042375	Date of last issue: 08/06/2020

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Versi 1.1	ion Revision Date: 08/06/2020	-	0S Number: 0010042375	Print Date: 10/28/2020 Date of last issue: 08/06/2020
Technical measures		:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine approprate controls for safe handling, storage and disposal of this material.	
Advice on safe handling		:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate rials in order to prevent fires.	
	Avoidance of contact	:	Strong oxidising a	gents.
	Further information on stor- age stability	:	place.	htly closed and in a cool, well-ventilated led and closable containers.
			Store at ambient t	emperature.
	Packaging material	:	Suitable material: steel or high dens Unsuitable materi	
	Container Advice	:		ainers should not be exposed to high tem- e of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Meth-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.1	08/06/2020	800010042375	Date of last issue: 08/06/2020

ods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.
Personal protective equipment	
Respiratory protection :	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

ersion 1	Revision Date: 08/06/2020	SDS Number: 80001004237	
		>65°C (14	9°F)].
Hand	protection		
Re	emarks	gloves app US: F739) suitable ch gloves Sui usage, e.g sistance o glove supp Personal h Gloves mu gloves, ha cation of a For contin through tir 480 minute short-term recognize may not bu time mayb and replac a good pre dependen Glove thic	nd contact with the product may occur the use of proved to relevant standards (e.g. Europe: EN374, made from the following materials may provide nemical protection. PVC, neoprene or nitrile rubber tability and durability of a glove is dependent on . frequency and duration of contact, chemical re- f glove material, dexterity. Always seek advice from oliers. Contaminated gloves should be replaced. Aggiene is a key element of effective hand care. Ist only be worn on clean hands. After using nds should be washed and dried thoroughly. Appli- non-perfumed moisturizer is recommended. Jours contact we recommend gloves with break- ne of more than 240 minutes with preference for > es where suitable gloves can be identified. For /splash protection we recommend the same but that suitable gloves offering this level of protection e available and in this case a lower breakthrough e acceptable so long as appropriate maintenance ement regimes are followed. Glove thickness is not edictor of glove resistance to a chemical as it is to n the exact composition of the glove material. Kness should be typically greater than 0.35 mm on the glove make and model.
Eye p	protection		is handled such that it could be splashed into eyes, eyewear is recommended.
Skin a	and body protection	work cloth	ction is not ordinarily required beyond standard es. practice to wear chemical resistant gloves.
Prote	ective measures		protective equipment (PPE) should meet recom- ational standards. Check with PPE suppliers.
Therr	nal hazards	: Not applic	able
Envir	ronmental exposure o	controls	
Gene	eral advice	vant enviro of the enviro necessary charged to municipal discharge Local guid	opriate measures to fulfill the requirements of rele- onmental protection legislation. Avoid contamination ronment by following advice given in Section 6. If , prevent undissolved material from being dis- o waste water. Waste water should be treated in a for industrial waste water treatment plant before to surface water. elines on emission limits for volatile substances oserved for the discharge of exhaust air containing

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

vapour.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

/ersion .1	Revision Date: 08/06/2020		S Number: 0010042375	Print Date: 10/28/2020 Date of last issue: 08/06/2020
Арреа	irance	:	no data available	
Coloui	r	:	Not applicable	
Odour	Threshold	:	Data not availabl	e
рН		:	Not applicable	
pour p	oint	:	Method: Unspect Not applicable	fied
Initial I range	poiling point and boiling	:	> 280 °C / 536 °F estimated value(
Flash	point	:	225 °C / 437 °F	
			Method: ASTM D	092 (COC)
Evapo	ration rate	:	Data not availabl	e
Flamm	nability (solid, gas)	:	Data not availabl	e
	explosion limit / upper ability limit	:	Typical 10 %(V)	
	explosion limit / Lower ability limit	:	Typical 1 %(V)	
Vapou	ir pressure	:	< 0.5 Pa (20 °C /	68 °F)
			estimated value(s)
Relativ	ve vapour density	:	> 1 estimated value(s)
Relativ	ve density	:	1.0372 (15.0 °C /	/ 59.0 °F)
Densit	У	:	1,037.2 kg/m3 (1 Method: ASTM [
	lity(ies) ater solubility	:	negligible	
Sol	lubility in other solvents	:	Data not availabl	e
	on coefficient: n- bl/water	:	log Pow: > 6 (based on inform	ation on similar products)
Auto-ię	gnition temperature	:	> 320 °C / 608 °F	=
	nposition temperature	:	Data not availabl	e
Viscos Vis	sity cosity, dynamic	:	Data not availabl	e

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version 1.1	Revision Date: 08/06/2020	SDS Number: 800010042375	Print Date: 10/28/2020 Date of last issue: 08/06/2020
Vis	scosity, kinematic	: 103 mm2/s (/ Method: AST	40.0 °C / 104.0 °F) M D445
		21.6 mm2/s ((100 °C / 212 °F)
Funda	- i	Method: AST	
	sive properties zing properties	: Not classified	-
	uctivity		is not expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise,
	the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:
1.1	08/06/2020	800010042375

Print Date: 10/28/2020 Date of last issue: 08/06/2020

Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Remarks: Non mutagenic, Based on available data, the classi-2 fication criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity	

Product:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.1	08/06/2020	800010042375	Date of last issue: 08/06/2020

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity	
Product: Toxicity to fish (Acute toxici- : ty)	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other : aquatic invertebrates (Acute	Remarks: LL/EL/IL50 > 100 mg/l

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version 1.1	Revision Date: 08/06/2020		0S Number: 0010042375	Print Date: 10/28/2020 Date of last issue: 08/06/2020
toxici	ity)		Practically non to Based on availabl	kic: le data, the classification criteria are not met.
Toxic icity)	city to algae (Acute tox-	:	Remarks: LL/EL/I Practically non to Based on availabl	
Toxic icity)	city to fish (Chronic tox-	:	Remarks: Data no	ot available
aqua	city to daphnia and other tic invertebrates (Chron- cicity)	:	Remarks: Data no	ot available
	city to microorganisms te toxicity)	:	Remarks: Data no	ot available
Pers	istence and degradabili	ity		
Prod	luct:			
	egradability	:	Major constituents	dily biodegradable. s are inherently biodegradable, but contains may persist in the environment.
Bioa	ccumulative potential			
Prod	luct:			
Bioad	ccumulation	:	Remarks: Contair cumulate.	as components with the potential to bioac-
Mobi	ility in soil			
Prod	luct:			
Mobi	lity	:		under most environmental conditions. vill adsorb to soil particles and will not be
			Remarks: Floats of	on water.
Othe	er adverse effects			
Prod	luct:			
	tional ecological infor-	:	ozone creation po Product is a mixtu	one depletion potential, photochemical itential or global warming potential. ire of non-volatile components, which will not in any significant quantities under normal
			Poorly soluble mix Causes physical f	xture. ouling of aquatic organisms.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.1	08/06/2020	800010042375	Date of last issue: 08/06/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	F
1.1	08/06/2020	800010042375	D

Print Date: 10/28/2020 Date of last issue: 08/06/2020

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Phosphoric acid	7664-38-2	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: No SARA Hazards	
SARA 313	: This material does not contain any chemical components known CAS numbers that exceed the threshold (De Mini reporting levels established by SARA Title III, Section 31	imis)

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Phosphoric acid	7664-38-2	0.009 %
-----------------	-----------	---------

US State Regulations

Pennsylvania Right To Know

Propan-2-ol

67-63-0

California Prop. 65

WARNING: This product can expose you to chemicals including distillates (petroleum), hydrotreated light, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	Not established.
TSCA	:	All components listed.
DSL	:	Not established.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	S
1.1	08/06/2020	8

SDS Number: Print Date: 10/2 300010042375 Date of last iss

Print Date: 10/28/2020 Date of last issue: 08/06/2020

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

ACGIH OSHA Z-1 ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms	······································	USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants 8-hour, time-weighted average 8-hour time weighted average The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
		ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Chemicals Agency EINECS = The European Inventory of Existing Commercial Chemical Substances EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substances Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer IATA = International Agency for Research on Cancer

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 W 100

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.1	08/06/2020	800010042375	Date of last issue: 08/06/2020
		determination of KECI = Korea B LC50 = Lethal 0 LD50 = Lethal 1 LL/EL/IL = Leth LL50 = Lethal L MARPOL = Inte Pollution From NOEC/NOEL = served Effect L OE_HPV = Occ PBT = Persiste PICCS = Philip Substances PNEC = Predic REACH = Regi Chemicals RID = Regulatin gerous Goods I SKIN_DES = S STEL = Short to TRA = Targeter TSCA = US To TWA = Time-W	ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume nt, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical ted No Effect Concentration stration Evaluation And Authorisation Of ons Relating to International Carriage of Dan-

A vertical bar (|) in the left margin indicates an amendment from the previous version.

compile the Safety Data s Sheet H	he quoted data are from, but not limited to, one or more ources of information (e.g. toxicological data from Shell lealth Services, material suppliers' data, CONCAWE, EU JCLID date base, EC 1272 regulation, etc).
--------------------------------------	---

Revision Date : 08/06/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN