PURITY TM/MC FG PAG GEAR OIL 150



00003009244			
ersion 2.3		Revision Date 2022/08/16	Print Date 2022/08/16
ECTION 1. IDENTIFICATION			
Product name	:	PURITY MMC FG PAG GEAR OIL	150
Product code	:	PFPG150P20, PFPG150DRX, PF	PG150
Manufacturer or supplier		ails Petro-Canada America Lubricants 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555	LLC
Emergency telephone nu	mber		
Emergency telephone number	:		al telephone directory for
Recommended use of the	e che	mical and restrictions on use	
Recommended use	:	PURITY FG PAG Gear Oils are us industrial gear applications for both industrial applications.	
Prepared by	:	Product Safety: +1 905-491-0565	
ECTION 2. HAZARDS IDENT GHS classification in acc 1910.1200)		TION	nication Standard (29 CFR
Not a hazardous substance	e or m	ixture.	
GHS label elements			
Not a hazardous substance	e or m	ixture.	
Other hazards			
None known.			
IARC		No component of this product pres	ent at levels greater than

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

PURITY TM/MC FG PAG GEAR OIL 150

000003009244

Version 2.3

Revision Date 2022/08/16

Print Date 2022/08/16

Components

No hazardous ingredients

SECTION 4. FIRST AID MEASURES				
If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.			
In case of skin contact	 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. 			
In case of eye contact	 Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention. 			
If swallowed	 Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice. 			
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.			

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	:	Use personal protective equipment.
protective equipment and		Ensure adequate ventilation.

PURITY TM/MC FG PAG GEAR OIL 150



000003009244

Version 2.3		Revision Date 2022/08/16	Print Date 2022/08/16
emergency procedures		Evacuate personnel to safe areas. Material can create slippery conditions Mark the contaminated area with signs unauthorized personnel. Only qualified personnel equipped with equipment may intervene.	and prevent access to
Environmental precautions	:	Do not allow uncontrolled discharge of environment.	product into the
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if sa Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.	ife to do so.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures	:	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
		contaminants.

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust
		ventilation is provided or exposure assessment demonstrates
		that exposures are within recommended exposure guidelines.

PURITY TM/MC FG PAG GEAR OIL 150



000003009244

Version 2.3		Revision Date 2022/08/16	Print Date 2022/08/16
		Respirator selection must be base exposure levels, the hazards of th working limits of the selected resp	e product and the safe
Filter type	:	organic vapour filter	
Hand protection Material	:	neoprene, nitrile, polyvinyl alcoho	I (PVA), Viton [®] .
Remarks	:	Chemical-resistant, impervious gla approved standard should be wor chemical products if a risk assess necessary.	n at all times when handling
Eye protection	:	Wear face-shield and protective s problems.	uit for abnormal processing
Skin and body protection	:	Choose body protection in relation concentration and amount of dang the specific work-place.	
Protective measures	:	Wash contaminated clothing befo	re re-use.
Hygiene measures	:	Remove and wash contaminated including the inside, before re-use Wash face, hands and any expos handling.).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	clear
Odour	:	mild
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-40 °C (-40 °F) No data available
Flash point	:	268 °C (514 °F) Method: Cleveland open cup
Fire Deint		
Fire Point	:	No data available
Evaporation rate	:	No data available No data available
	•	

PURITY TM/MC FG PAG GEAR OIL 150



000003009244

Version 2.3		Revision Date 2022/08/16	Print Date 2022/08/16
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	1.0586 kg/l (15 °C / 59 °F)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	150 cSt (40 °C / 104 °F)	
		28.3 cSt (100 °C / 212 °F)	
Explosive properties	:	Do not pressurize, cut, weld, braze, so expose containers to heat or sources of	

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

	Information on likely routes of exposure			
	Eye contact Ingestion Inhalation Skin contact			
	Acute toxicity			
	Product:			
	Acute oral toxicity	:	Remarks: No data available	
	Acute inhalation toxicity	:	Remarks: No data available	
	Acute dermal toxicity	:	Remarks: No data available	
tor	net: lubricants netro-canada com/s	de		D

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

PURITY TM/MC FG PAG GEAR OIL 150

000003009244

Version 2.3



Print Date 2022/08/16

Skin corrosion/irritation

Product:

Remarks

: No data available

Serious eye damage/eye irritation

Product:

Remarks

: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

<u>Product:</u> Toxicity to fish		Remarks: No data available
	•	
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradabili	ty	
Product:		
Biodegradability	:	Remarks: No data available
Bioaccumulative potential		

No data available

PURITY TM/MC FG PAG GEAR OIL 150

000003009244

Version 2.3

Revision Date 2022/08/16

Print Date 2022/08/16

Mobility in soil No data available

Other adverse effects

Other adverse effec

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

-	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm. For more information go to www.P65Warnings.ca.gov.			
The components of this product are reported in the following inventories:				
DSL :	On the inventory, or in compliance with the inventory			
TSCA :	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.			
IECSC :	On the inventory, or in compliance with the inventory			

PURITY TM/MC FG PAG GEAR OIL 150

000003009244


Version 2.3

Print Date 2022/08/16


SECTION 16. OTHER INFORMATION

Further information





HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization

PURITY TM/MC FG PAG GEAR OIL 150



000003009244

Version 2.3	Revision Date 2022/08/16	Print Date 2022/08/16

Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date	:	2022/08/16

: yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Date format