According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version 1.1	Revision Date: 11/14/2019		lumber: 0031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018	
SECTION	1. IDENTIFICATION				
Produ	uct name	: She	ell Rotella N	IP Grease	
Product code		: 001	001G8045		
Manu	ufacturer or supplier	s details			
Manufacturer/Supplier			ell Oil Prod) Box 4427	ucts US	

PO Box 4427 Houston TX 77210-4427 USA SDS Request : (+1) 877-276-7285 Customer Service :

Emergency telephone number

	•	
Spill Information	:	877-504-9351
Health Information	:	877-242-7400

Recommended use of the chemical and restrictions on use

Recommended use : Automotive and industrial grease.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements		
Hazard pictograms	No Hazard Symbol required	
Signal word	: No signal word	
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS crit 	eria.
Precautionary statements		
	 Prevention: No precautionary phrases. Response: No precautionary phrases. 	
	No precautionary phrases. Response:	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date:	SDS Number:	Print
1.1	11/14/2019	800010031983	Date

Print Date: 11/15/2019 Date of last issue: 09/14/2018

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: A lubricating grease containing highly-refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Zinc naphthenate	Naphthenic	12001-85-3	0.1 - 0.99
	acids, zinc		
	salts		
Bismuth Naphthenate	Naphthenic	85736-59-0	0.1 - 0.99
	acids, bismuth		
	salts		
Naphthenic acid	Naphthenic	1338-24-5	0.1 - 0.99
	acids		
Alkyl thiadiazole	2,5-	13539-13-4	0.01 - 0.09
	bis(octyldithio)-		
	1,3,4-		
	thiadiazole		

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
		When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version 1.1	Revision Date: 11/14/2019		OS Number: 0010031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018
			rinsing. If persistent irritati	on occurs, obtain medical attention.
lf swa	allowed	:		tment is necessary unless large quantities owever, get medical advice.
and e	Most important symptoms and effects, both acute and delayed		Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.	
Prote	Protection of first-aiders			ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings.
medi	Indication of any immediate medical attention and special treatment needed		Treat symptomation	cally.
			vention and possi age and loss of fu Because entry wo ousness of the un determine the extu anaesthetics or ho can contribute to s surgical decompre eign material shou	ection injuries require prompt surgical inter- bly steroid therapy, to minimise tissue dam- nction. bunds are small and do not reflect the seri- derlying damage, surgical exploration to ent of involvement may be necessary. Local of soaks should be avoided because they swelling, vasospasm and ischaemia. Prompt ession, debridement and evacuation of for- uld be performed under general anaesthet- oration is essential.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date: 11/14/2019	SDS Number:	Print Date: 11/15/2019
1.1		800010031983	Date of last issue: 09/14/2018

Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Methods and materials for containment and cleaning up	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Additional advice	:	For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date:	SDS Number:	Print Date: 11/15/2019
1.1	11/14/2019	800010031983	Date of last issue: 09/14/2018

peratures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version 1.1	Revision Date: 11/14/2019	SDS Number: 800010031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018
		nance. Retain drain do subsequent reo Always observe washing hands drinking, and/o protective equip	e good personal hygiene measures, such as after handling the material and before eating, r smoking. Routinely wash work clothing and oment to remove contaminants. Discard con- ing and footwear that cannot be cleaned.
			luct's semi-solid consistency, generation of s is unlikely to occur.
Pers	onal protective equip	oment	
	iratory protection	: No respiratory conditions of us In accordance tions should be If engineering of tions to a level select respirato cific conditions Check with res Where air-filter priate combina Select a filter s	with good industrial hygiene practices, precau- taken to avoid breathing of material. controls do not maintain airborne concentra- which is adequate to protect worker health, any protection equipment suitable for the spe- of use and meeting relevant legislation. piratory protective equipment suppliers. ing respirators are suitable, select an appro- tion of mask and filter. uitable for the combination of organic gases and particles [Type A/Type P boiling point
Llaved			
	l protection emarks	gloves approve US: F739) mad suitable chemic gloves Suitabili usage, e.g. free sistance of glov glove suppliers Personal hygie Gloves must or gloves, hands s cation of a non- For continuous through time of 480 minutes wh short-term/spla recognize that s may not be ava time maybe act and replaceme a good predictor	Intact with the product may occur the use of ad to relevant standards (e.g. Europe: EN374, le from the following materials may provide cal protection. PVC, neoprene or nitrile rubber ty and durability of a glove is dependent on quency and duration of contact, chemical re- ve material, dexterity. Always seek advice from . Contaminated gloves should be replaced. ne is a key element of effective hand care. Ny be worn on clean hands. After using should be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > nere suitable gloves can be identified. For sh protection we recommend the same but suitable gloves offering this level of protection ilable and in this case a lower breakthrough ceptable so long as appropriate maintenance nt regimes are followed. Glove thickness is not or of glove resistance to a chemical as it is he exact composition of the glove material.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version 1.1	Revision Date: 11/14/2019	SDS Number: 800010031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018			
			s should be typically greater than 0.35 mm he glove make and model.			
Eye p	protection		If material is handled such that it could be splashed into eyes, protective eyewear is recommended.			
Skin a	and body protection	work clothes.	Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.			
Prote	ctive measures		Personal protective equipment (PPE) should meet recom- mended national standards. Check with PPE suppliers.			
Thern	nal hazards	: Not applicable	: Not applicable			
Envir	onmental exposure o	controls				
General advice		vant environme of the environm necessary, pre charged to was municipal or in discharge to su Local guideline	te measures to fulfill the requirements of rele- ental protection legislation. Avoid contamination nent by following advice given in Section 6. If vent undissolved material from being dis- ste water. Waste water should be treated in a dustrial waste water treatment plant before urface water. es on emission limits for volatile substances ved for the discharge of exhaust air containing			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Semi-solid at ambient temperature.
Colour	:	brown
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
Melting / freezing point	:	Not applicable
Initial boiling point and boiling range	:	Data not available
Flash point	:	Method: ASTM D92 (COC) Not applicable
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Vers 1.1	sion	Revision Date: 11/14/2019		S Number: 0010031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018
		explosion limit / Lower bility limit	:	Typical 1 %(V)	
	Vapour	pressure	:	< 0.5 Pa (20 °C /	68 °F)
				estimated value(5)
	Relative	e vapour density	:	> 1 estimated value(state)	5)
	Relative	e density	:	1.000 (15.0 °C /	59.0 °F)
	Density	,	:	1,000 kg/m3 (15. Method: Unspeci	
	Solubili Wat	ty(ies) er solubility	:	negligible	
	Solu	bility in other solvents	:	Data not availabl	e
	Partition octanol	n coefficient: n- /water		log lon i o	ation on similar products)
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	-
	Decom	position temperature	:	Data not availabl	e
	Viscosi Visc	ty :osity, dynamic	:	Data not availabl	e
	Visc	osity, kinematic	:	Not applicable	
	Explosi	ve properties	:	Not classified	
	Oxidizir	ng properties	:	Data not availabl	e
	Conduc	ctivity	:	This material is n	ot expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.

_

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Vers 1.1	ion Revision Date: 11/14/2019	SDS Number: 800010031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018
	Hazardous decomposition products	: No decomp	position if stored and applied as directed.
SEC	TION 11. TOXICOLOGICAL	NFORMATION	
	Basis for assessment	the toxicolog the data pre	given is based on data on the components and gy of similar products.Unless indicated otherwise, sented is representative of the product as a er than for individual component(s).
	Skin and eye contact are the accidental ingestion.	o on likely routes of exposure e contact are the primary routes of exposure although exposure may occur following ngestion.	
	Acute toxicity		
	Product:		
	Acute oral toxicity	: LD50 (rat): : Remarks: L Based on a	
	Acute inhalation toxicity	: Remarks: B are not met	ased on available data, the classification criteria
	Acute dermal toxicity	Remarks: L	it): > 5,000 mg/kg ow toxicity: /ailable data, the classification criteria are not met.
	Skin corrosion/irritation		

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Naphthenic acid:

Remarks: May cause an allergic skin reaction in sensitive individuals.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date:	SDS Number:	Print Date: 11/15/2019
1.1	11/14/2019	800010031983	Date of last issue: 09/14/2018

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date:	SDS Number:
1.1	11/14/2019	800010031983

Toxicity to fish (Chronic tox-

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

Toxicity to microorganisms

icity)

ic toxicity)

(Acute toxicity)

Print Date: 11/15/2019 Date of last issue: 09/14/2018

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION Basis for assessment : Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract). Ecotoxicity Product: Toxicity to fish (Acute toxici-Remarks: LL/EL/IL50 > 100 mg/l ty) Practically non toxic: Based on available data, the classification criteria are not met. Toxicity to daphnia and other : aquatic invertebrates (Acute Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: toxicity) Based on available data, the classification criteria are not met. Toxicity to algae (Acute toxicity) Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.

11/16

Remarks: Data not available

Remarks: Data not available

Remarks: Data not available

2

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Versio 1.1	on Revision Date: 11/14/2019		DS Number: 0010031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018
F	Persistence and degradabil	lity		
<u>F</u>	Product:			
E	Biodegradability :		Major constituents	dily biodegradable. s are inherently biodegradable, but contains may persist in the environment.
E	Bioaccumulative potential			
<u>P</u>	Product:			
E	Bioaccumulation	:	Remarks: Contair cumulate.	is components with the potential to bioac-
N	lobility in soil			
E	Product:			
N	<i>l</i> obility	:		olid under most environmental conditions. vill adsorb to soil particles and will not be
			Remarks: Floats of	on water.
c	Other adverse effects			
<u> </u>	Product:			
	Additional ecological infor- nation	:	ozone creation po Product is a mixtu	one depletion potential, photochemical tential or global warming potential. Ire of non-volatile components, which will not in any significant quantities under normal
			Poorly soluble mix Causes physical f	xture. ouling of aquatic organisms.
				ot cause chronic toxicity to aquatic organ- tions less than 1 mg/l.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues		Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	9	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date:	SDS Number:	Print Date: 11/15/2019
1.1	11/14/2019	800010031983	Date of last issue: 09/14/2018
Cont	aminated packaging	to a recognized the collector or c Disposal should	rdance with prevailing regulations, preferably collector or contractor. The competence of contractor should be established beforehand. be in accordance with applicable regional, cal laws and regulations.
Loca	I l legislation	•	be in accordance with applicable regional,
Rem	arks		al laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Naphthenic acid	1338-24-5	100	*

*: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date:	SDS Number:	Print Date: 11/15/2019
1.1	11/14/2019	800010031983	Date of last issue: 09/14/2018

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Naphthenic acid	1338-24-5	0.135 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Highly refined mineral oil	64742-52-5
Zinc naphthenate	12001-85-3
Naphthenic acid	1338-24-5

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

California List of Hazardous Substances

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
---	------------

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-
		its for Air Contaminants

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version 1.1	Revision Date: 11/14/2019	SDS Number: 800010031983	Print Date: 11/15/2019 Date of last issue: 09/14/2018
OSH/	H / TWA A Z-1 / TWA eviations and Acronyms	: 8-hour time we : The standard a ment can be lo	eighted average eighted average abbreviations and acronyms used in this docu- boked up in reference literature (e.g. scientific ad/or websites.
		Hygienists ADR = Europer Carriage of Da AICS = Austra ASTM = Amer BEL = Biologic BTEX = Benz CAS = Chemic CEFIC = Europ CLP = Classifi COC = Clevela DIN = Deutsch DMEL = Derive DNEL = Derive DNEL = Derive DNEL = Derive DNEL = Derive DSL = Canada EC = Europea EC50 = Effecti ECETOC = Eu gy Of Chemica ECHA = Europe Chemical Subs EL50 = Effecti ENCS = Japar Inventory EWC = Europea GHS = Globall Labelling of CH IARC = Interna IC50 = Inhibito IMDG = Intern INV = Chinese IP346 = Institut determination KECI = Korea LC50 = Lethal LD50 = Lethal LD50 = Lethal MARPOL = Interna NOEC/NOEL = served Effect I OE_HPV = OC PBT = Persiste	es Institut fur Normung ed Minimal Effect Level ed No Effect Level a Domestic Substance List in Commission ve Concentration fifty iropean Center on Ecotoxicology and Toxicolo- als bean Chemicals Agency e European Inventory of Existing Commercial stances ve Loading fifty nese Existing and New Chemical Substances ean Waste Code y Harmonised System of Classification and nemicals ational Agency for Research on Cancer tional Air Transport Association rry Concentration fifty ry Level fifty ational Maritime Dangerous Goods c Chemicals Inventory ute of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. hal Loading/Effective Loading/Inhibitory loading Loading fifty ternational Convention for the Prevention of Ships = No Observed Effect Concentration / No Ob-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella MP Grease

Version	Revision Date:	SDS Number:	Print Date: 11/15/2019	
1.1	11/14/2019	800010031983	Date of last issue: 09/14/2018	

Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Revision Date : 11/14/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN