According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version 1.0	Revision Date: 09/02/2020	SDS Number: 800010042413	Print Date: 09/03/2020 Date of last issue: -
SECTION	1. IDENTIFICATION		
Produ	uct name	: Shell Omala S	3 A 320
Produ	uct code	: 00115509	
Manu	afacturer or supplier	's details	
Manu	ifacturer/Supplier	: Shell Oil Prod PO Box 4427 Houston TX 7 USA	
	Request omer Service	: (+1) 877-276-7 :	285
Spill I	r gency telephone nu Information h Information	mber : 877-504-9351 : 877-242-7400	
	mmended use of the mmended use	e chemical and restric	ctions on use
	2. HAZARDS IDENT	IFICATION	
	classification in acc .1200)	ordance with the OSI	HA Hazard Communication Standard (29 CFR
Skin	sensitisation	: Category 1	
GHS	label elements		
Haza	rd pictograms		

Signal word	:	Warning
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: H317 May cause an allergic skin reaction. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention:
		P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version Revision Date: 1.0 09/02/2020

SDS Number: 800010042413

Print Date: 09/03/2020 Date of last issue: -

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water and soap. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label: Contains Oxazoline derivative.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Blend of polyalkylene glycol and additives.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Oxazoline derivative	4-ethyl-2-(8- heptadecenyl)- 2-oxazoline-4- methanol	68140-98-7	0.1 - 0.9
Triazole derivative	1H- Benzotriazole- 1- methanamine, N,N-bis(2- ethylhexyl)-ar- methyl-	94270-86-7	0.1 - 0.24

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Versi 1.0	ion	Revision Date: 09/02/2020		S Number: 0010042413	Print Date: 09/03/2020 Date of last issue: -	
I	In case of eye contact		:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.		
I	lf swalld	owed	:		tment is necessary unless large quantities wever, get medical advice.	
á	Most important symptoms and effects, both acute and delayed		:	may include itchin Oil acne/folliculitis of black pustules a	(allergic skin reaction) signs and symptoms g and/or a rash. signs and symptoms may include formation and spots on the skin of exposed areas. ult in nausea, vomiting and/or diarrhoea.	
I	Protecti	on of first-aiders	:		ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings.	
r	medica	on of any immediate attention and special nt needed	:	Treat symptomatio	cally.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :	Avoid contact with skin and eyes.
tive equipment and emer-	
gency procedures	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version 1.0	Revision Date: 09/02/2020		DS Number: 0010042413	Print Date: 09/03/2020 Date of last issue: -		
Environmental precautions		:	: Local authorities should be advised if significant spillages cannot be contained.			
	Methods and materials for containment and cleaning up		Prevent from spre or other containm Reclaim liquid dire Soak up residue v	It. Avoid accidents, clean up immediately. ading by making a barrier with sand, earth ent material. ectly or in an absorbent. vith an absorbent such as clay, sand or other and dispose of properly.		
Additio	nal advice	:	see Section 8 of t	selection of personal protective equipment his Safety Data Sheet. disposal of spilled material see Section 13 of sheet.		

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version	Revision Date:	SDS Number:	Print Date: 09/03/2020
1.0	09/02/2020	800010042413	Date of last issue: -

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
		Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
		General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version 1.0	Revision Date: 09/02/2020		0S Number: 0010042413	Print Date: 09/03/2020 Date of last issue: -
			nance. Retain drain do subsequent red Always observe washing hands drinking, and/or protective equip	e good personal hygiene measures, such as after handling the material and before eating, r smoking. Routinely wash work clothing and oment to remove contaminants. Discard con- ing and footwear that cannot be cleaned.
Perso	onal protective equip	ment		
Resp	iratory protection	:	conditions of us In accordance	protection is ordinarily required under normal se. with good industrial hygiene practices, precau- taken to avoid breathing of material.
	protection emarks	:	gloves approve US: F739) mad suitable chemic gloves Suitabili usage, e.g. free sistance of glov glove suppliers Personal hygie Gloves must or gloves, hands s cation of a non- For continuous through time of 480 minutes wh short-term/spla recognize that may not be ava time maybe acc and replaceme a good predicto dependent on t	ntact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide cal protection. PVC, neoprene or nitrile rubber ty and durability of a glove is dependent on quency and duration of contact, chemical re- ve material, dexterity. Always seek advice from . Contaminated gloves should be replaced. ne is a key element of effective hand care. Ny be worn on clean hands. After using should be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > nere suitable gloves can be identified. For sh protection we recommend the same but suitable gloves offering this level of protection ilable and in this case a lower breakthrough ceptable so long as appropriate maintenance int regimes are followed. Glove thickness is not or of glove resistance to a chemical as it is he exact composition of the glove material. s should be typically greater than 0.35 mm he glove make and model.
Eye p	protection	:	Wear full face s	shield if splashes are likely to occur.
Skin	and body protection	:		resistant gloves/gauntlets and boots. Where g, also wear an apron.
Prote	ctive measures	:		ctive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.
Therr	nal hazards	:	Not applicable	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version	Revision Date:	SDS Number:
1.0	09/02/2020	800010042413

Print Date: 09/03/2020 Date of last issue: -

Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

:	no data available
:	Not applicable
:	Data not available
:	Not applicable
:	Method: Unspecified Not applicable
:	> 280 °C / 536 °F estimated value(s)
:	Method: Unspecified Not applicable
:	Data not available
:	Data not available
:	Typical 10 %(V)
:	Typical 1 %(V)
:	< 0.5 Pa (20 °C / 68 °F)
	estimated value(s)
:	> 1 estimated value(s)
:	0.997 (15.0 °C / 59.0 °F)
:	997 kg/m3 (15.0 °C / 59.0 °F) Method: ASTM D4052

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Vers 1.0	sion	Revision Date: 09/02/2020		S Number: 010042413	Print Date: 09/03/2020 Date of last issue: -
		ity(ies) ter solubility	:	negligible	
	Sol	ubility in other solvents	:	Data not available	9
		on coefficient: n- I/water	:	log Pow: > 6 (based on inform	ation on similar products)
	Auto-ig	gnition temperature	:	> 320 °C / 608 °F	
	Decomposition temperature		:	Data not available	9
	Viscosity Viscosity, dynamic		:	Data not available	e
	Viscosity, kinematic		:	319 mm2/s (40.0	°C / 104.0 °F)
				Method: ASTM D	445
				45 mm2/s (100 °C	C / 212 °F)
				Method: ASTM D	445
	Explos	ive properties	:	Not classified	
	Oxidizi	ing properties	:	Data not available	9
	Condu	ctivity	:	This material is n	ot expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment		Information given is based on data on the components and
		the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a
		whole, rather than for individual component(s).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version	Revision Date:	SDS Number:	Print Date: 09/03/2020
1.0	09/02/2020	800010042413	Date of last issue: -

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Expected to be a skin sensitizer.

Components:

Triazole derivative:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version	Revision Date:	SDS Number:	Print Date: 09/03/2020
1.0	09/02/2020	800010042413	Date of last issue: -

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

÷

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

rsion	Revision Date: 09/02/2020		0S Number: 0010042413	Print Date: 09/03/2020 Date of last issue: -
Basis for assessment		:	for this product. Information give and the ecotoxic Unless indicated tive of the produ ponent(s).(LL/E	data have not been determined specifically n is based on a knowledge of the components cology of similar products. I otherwise, the data presented is representa- ct as a whole, rather than for individual com- _/IL50 expressed as the nominal amount of I to prepare aqueous test extract).
Ecoto	xicity			
<u>Produ</u> Toxicit ty)	<u>ct:</u> y to fish (Acute toxici-	:	Practically non t	/IL50 > 100 mg/l oxic: ble data, the classification criteria are not met.
	ty to daphnia and other c invertebrates (Acute /)	:	Practically non t	/IL50 > 100 mg/I oxic: ble data, the classification criteria are not met
Toxicit icity)	y to algae (Acute tox-	:	Practically non t	/IL50 > 100 mg/I oxic: ble data, the classification criteria are not met.
Toxicit icity)	ty to fish (Chronic tox-	:	Remarks: Data	not available
	ty to daphnia and other c invertebrates (Chron- city)	:	Remarks: Data	not available
	y to microorganisms toxicity)	:	Remarks: Data	not available
<u>Comp</u>	onents:			
	le derivative: tor (Acute aquatic tox-	:	1	
Persis	stence and degradabili	ity		
<u>Produ</u>	<u>ct:</u>			
Biode	gradability	:	Major constituer	eadily biodegradable. hts are inherently biodegradable, but contains t may persist in the environment.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Vers 1.0	sion	Revision Date: 09/02/2020		0S Number: 0010042413	Print Date: 09/03/2020 Date of last issue: -	
	Bioaco	cumulative potential				
	Produ	ct:				
	Bioaccumulation		:	Remarks: Contains components with the potential to bioac- cumulate.		
	Mobili	ty in soil				
	Produ	<u>ct:</u>				
	Mobility		:		der most environmental conditions. I adsorb to soil particles and will not be	
				Remarks: Floats of	on water.	
	Other adverse effects					
	Produ	ct:				
	Additio mation	nal ecological infor-	:	ozone creation po Product is a mixtu	one depletion potential, photochemical stential or global warming potential. are of non-volatile components, which will not in any significant quantities under normal	
				Poorly soluble mix Causes physical f	xture. ouling of aquatic organisms.	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks :	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version	Revision Date:	SDS Number:
1.0	09/02/2020	800010042413

Print Date: 09/03/2020 Date of last issue: -

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Respiratory or skin sensitisation
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

Diphenylamine

122-39-4

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

Version	Revision Date:	SDS Number:	Print Date: 09/03/2020
1.0	09/02/2020	800010042413	Date of last issue: -

California Prop. 65

WARNING: This product can expose you to chemicals including distillates (petroleum), hydrotreated light, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	Not established.
TSCA	:	All components listed.
DSL	:	Not established.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 2, 1, 0 tivity)

Full text of other abbreviations

ACGIH OSHA Z-1 ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms	:	USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants 8-hour, time-weighted average 8-hour time weighted average The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites. ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty
--	---	---

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S3 A 320

LL50 = Lethal Loading fifty MARPOL = International Convention for the Prevention of Pollution From Ships NOEC/NOEL = No Observed Effect Concentration / No Ob- served Effect Level	Version 1.0	Revision Date: 09/02/2020	SDS Number:Print Date: 09/03/2020800010042413Date of last issue: -
TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative			gy Of Chemicals ECHA = European Chemicals Agency EINECS = The European Inventory of Existing Commercial Chemical Substances EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substances Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer IATA = International Agency for Research on Cancer IATA = International Agency for Research on Cancer IATA = International Air Transport Association IC50 = Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG = International Maritime Dangerous Goods INV = Chinese Chemicals Inventory IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration fifty LD50 = Lethal Loading/Effective Loading/Inhibitory loading LL50 = Lethal Loading/Effective Loading/Inhibitory loading LL50 = Lethal Loading fifty MARPOL = International Convention for the Prevention of Pollution From Ships NOEC/NOEL = No Observed Effect Concentration / No Ob- served Effect Level OE_HPV = Occupational Exposure - High Production Volume PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dan- gerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 09/02/2020

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Shell Omala S3 A 320

Version	Revision Date:	SDS Number:	Print
1.0	09/02/2020	800010042413	Date

Print Date: 09/03/2020 Date of last issue: -

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN