# PURITY TM/MC FG PAG GEAR OIL 460



00003009246			
/ersion 2.3		Revision Date 2022/08/16	Print Date 2022/08/16
ECTION 1. IDENTIFICATION			
Droduct nome			460
Product name	•	PURITY TMMC FG PAG GEAR OIL	400
Product code	:	PFPG460P20, PFPG460DRX, PFI	PG460
Manufacturer or supplier's		ails Petro-Canada America Lubricants 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555	LLC
Emergency telephone nur	mber		
Emergency telephone num- ber		CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult loca emergency number(s).	al telephone directory for
Recommended use of the	chei	nical and restrictions on use	
Recommended use	:	PURITY FG PAG Gear Oils are us industrial gear applications for both industrial applications.	
Prepared by	:	Product Safety: +1 905-491-0565	
ECTION 2. HAZARDS IDENTI GHS classification in acco 1910.1200)	-	TION nce with the OSHA Hazard Commu	nication Standard (29 CF
Not a hazardous substance	or m	ixture.	
GHS label elements			
Not a hazardous substance	or m	ixture.	
Other hazards			

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

# PURITY TM/MC FG PAG GEAR OIL 460

#### 000003009246

Version 2.3

Revision Date 2022/08/16

Print Date 2022/08/16

### Components

No hazardous ingredients

SECTION 4. FIRST AID MEASUR	RES
If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	<ul> <li>In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.</li> <li>Wash skin thoroughly with soap and water or use recognized skin cleanser.</li> <li>Wash clothing before reuse.</li> <li>Seek medical advice.</li> </ul>
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.</li> <li>Obtain medical attention.</li> </ul>
If swallowed	<ul> <li>Rinse mouth with water.</li> <li>DO NOT induce vomiting unless directed to do so by a physician or poison control center.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>Seek medical advice.</li> </ul>
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :	Use personal protective equipment.
tive equipment and emer-	Ensure adequate ventilation.

# PURITY TM/MC FG PAG GEAR OIL 460



#### 000003009246

Version 2.3		Revision Date 2022/08/16	Print Date 2022/08/16	
gency procedures		Evacuate personnel to safe areas. Material can create slippery conditions Mark the contaminated area with signs unauthorized personnel. Only qualified personnel equipped with equipment may intervene.	and prevent access to	
Environmental precautions	:	Do not allow uncontrolled discharge of ronment.	product into the envi-	
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if sa Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.	afe to do so.	

#### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures	:	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
		contaminants.

#### Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust
		ventilation is provided or exposure assessment demonstrates
		that exposures are within recommended exposure guidelines.

# PURITY TM/MC FG PAG GEAR OIL 460



#### 000003009246

Version 2.3		Revision Date 2022/08/16	Print Date 2022/08/16
		Respirator selection must be based on exposure levels, the hazards of the pro working limits of the selected respirato	oduct and the safe
Filter type	:	organic vapour filter	
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PV	A), Viton <sup>®</sup> .
Remarks	:	Chemical-resistant, impervious gloves approved standard should be worn at a chemical products if a risk assessment essary.	all times when handling
Eye protection	:	Wear face-shield and protective suit fo problems.	r abnormal processing
Skin and body protection	:	Choose body protection in relation to it tration and amount of dangerous subst	
Protective measures	:	Wash contaminated clothing before re-	-use.
Hygiene measures	:	Remove and wash contaminated cloth ing the inside, before re-use. Wash face, hands and any exposed sh handling.	

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	clear
Odour	:	mild
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-35 °C (-31 °F) No data available
Flash point	:	265 °C (509 °F) Method: Cleveland open cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available

# PURITY TM/MC FG PAG GEAR OIL 460



#### 000003009246

Version 2.3	F	Revision Date 2022/08/16	Print Date 2022/08/16
Upper explosion limit / Upper flammability limit	: N	lo data available	
Lower explosion limit / Lower flammability limit	: N	lo data available	
Vapour pressure	: N	lo data available	
Relative vapour density	: N	lo data available	
Relative density	: N	lo data available	
Density	: 1	.0768 kg/l (15 °C / 59 °F)	
Solubility(ies)			
Water solubility	: ir	nsoluble	
Partition coefficient: n- octanol/water	: N	lo data available	
Viscosity Viscosity, kinematic	: 4	460 cSt (40 °C / 104 °F)	
	7	77.3 cSt (100 °C / 212 °F)	
Explosive properties		Do not pressurize, cut, weld, braze, sol bose containers to heat or sources of i	

#### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

#### SECTION 11. TOXICOLOGICAL INFORMATION

	Information on likely routes of exposure				
	Eye contact Ingestion Inhalation Skin contact				
	Acute toxicity				
	Product:				
	Acute oral toxicity	:	Remarks: No data available		
	Acute inhalation toxicity	:	Remarks: No data available		
	Acute dermal toxicity	:	Remarks: No data available		
tor	net: lubricants petro-canada com/s	de		c	

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

# PURITY TM/MC FG PAG GEAR OIL 460

#### 000003009246

Version 2.3



Print Date 2022/08/16

# Skin corrosion/irritation

#### Product:

Remarks

: No data available

#### Serious eye damage/eye irritation

#### Product:

Remarks

: No data available

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

# STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

Product:		
Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradabili	ity	
Product:		
Biodegradability	:	Remarks: No data available
Bioaccumulative potential		

No data available

# PURITY TM/MC FG PAG GEAR OIL 460

#### 000003009246

Version 2.3

Revision Date 2022/08/16

Print Date 2022/08/16

# Mobility in soil

No data available

Other adverse effects

No data available

#### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Offer surplus and non-recyclable solutions to a licensed disposal company.</li> <li>Waste must be classified and labelled prior to recycling or disposal.</li> <li>Send to a licensed waste management company.</li> <li>Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.</li> </ul>

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### **National Regulations**

49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

California Prop. 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm. For more information go to www.P65Warnings.ca.gov.	
The components of this product are reported in the following inventories:		
DSL :	On the inventory, or in compliance with the inventory	
TSCA :	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.	
IECSC :	On the inventory, or in compliance with the inventory	

# PURITY TM/MC FG PAG GEAR OIL 460

#### 000003009246


Version 2.3

Print Date 2022/08/16

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**





HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Con-

# PURITY TM/MC FG PAG GEAR OIL 460



#### 000003009246

Version 2.3	Revision Date 2022/08/16	Print Date 2022/08/16
trol Act (United States);	UN - United Nations; UNRTDG - United N	ations Recommendations on
the Transport of Dangero	ous Goods; vPvB - Very Persistent and Very	Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/08/16 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN