According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Rotella T1 30

| Version<br>1.0                  | Revision Date:<br>06/03/2019                              | SDS Number:<br>800010035375                            | Print Date: 06/04/2019<br>Date of last issue: - |
|---------------------------------|---|--|---|
| SECTION                         | 1. IDENTIFICATION   |  |   |
| Product name                    |   | : Shell Rotella T                                      | 1 30  |
| Product code                    |   | : 001H5090   |   |
| Manu                            | facturer or supplier's                                    | details  |   |
| Manufacturer/Supplier           |   | : Shell Oil Proc<br>PO Box 4427<br>Houston TX 7<br>USA |   |
| SDS Request<br>Customer Service |   | : (+1) 877-276-7<br>:                                  | 7285  |
| Spill I                         | <b>gency telephone num</b><br>nformation<br>h Information | ber<br>: 877-504-9351<br>: 877-242-7400                |   |
|                                 | mmended use of the ommended use                           | chemical and restri<br>: Engine oil.                   | ctions on use                                   |

### SECTION 2. HAZARDS IDENTIFICATION

### GHS classification in accordance with 29 CFR 1910.1200

Based on available data this substance / mixture does not meet the classification criteria.

| GHS label elements       |                          |   |
|--------------------------|--------------------------|---|
| Hazard pictograms        | : No                     | Hazard Symbol required  |
| Signal word              | : No                     | o signal word   |
| Hazard statements        | No<br>HE<br>No<br>EN     | HYSICAL HAZARDS:<br>ot classified as a physical hazard under GHS criteria.<br>EALTH HAZARDS:<br>ot classified as a health hazard under GHS criteria.<br>NVIRONMENTAL HAZARDS:<br>ot classified as an environmental hazard under GHS criteria. |
|                          |                          |   |
| Precautionary statements | N<br>Re                  | <b>revention:</b><br>lo precautionary phrases.<br><b>esponse:</b><br>lo precautionary phrases.  |
| Precautionary statements | N<br>Re<br>N<br>St       | lo precautionary phrases.<br>esponse:   |
| Precautionary statements | N<br>Re<br>N<br>St<br>Di | lo precautionary phrases.<br>esponse:<br>lo precautionary phrases.<br>torage:   |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Rotella T1 30

| Version | Revision Date: | SDS Number:  | Print Date: 06/04/2019 |
|---------|----------------|--------------|------------------------|
| 1.0     | 06/03/2019     | 800010035375 | Date of last issue: -  |

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

### Hazardous components

| Chemical name   | Synonyms  | CAS-No.    | Concentration (% w/w) |
|---|---|------------|-----------------------|
| Phosphorodithioic<br>acid, mixed O,O-<br>bis(2-ethylhexyl and<br>iso-Bu and iso-Pr)<br>esters, zinc salts | Phosphorodi-<br>thioic acid,<br>mixed O,O-<br>bis(2-ethylhexyl<br>and iso-Bu and<br>iso-Pr) esters,<br>zinc salts | 85940-28-9 | 1 - 2.4               |

### SECTION 4. FIRST-AID MEASURES

| If inhaled  | : | No treatment necessary under normal conditions of use.<br>If symptoms persist, obtain medical advice.   |
|---|---|---|
| In case of skin contact                                     | : | Remove contaminated clothing. Flush exposed area with wa-<br>ter and follow by washing with soap if available.<br>If persistent irritation occurs, obtain medical attention.              |
| In case of eye contact                                      | : | Flush eye with copious quantities of water.<br>Remove contact lenses, if present and easy to do. Continue<br>rinsing.<br>If persistent irritation occurs, obtain medical attention.       |
| If swallowed  | : | In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.  |
| Most important symptoms and effects, both acute and delayed | : | Oil acne/folliculitis signs and symptoms may include formation<br>of black pustules and spots on the skin of exposed areas.<br>Ingestion may result in nausea, vomiting and/or diarrhoea. |
| Protection of first-aiders                                  | : | When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.                               |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Rotella T1 30

| Version | Revision Date:   | SDS Number:      | Print Date: 06/04/2019 |  |
|---------|--|------------------|------------------------|--|
| 1.0     | 06/03/2019   | 800010035375     | Date of last issue: -  |  |
| medic   | ation of any immediate<br>cal attention and special<br>nent needed | : Treat symptoma | tically.               |  |

### SECTION 5. FIRE-FIGHTING MEASURES

| Suitable extinguishing media                  | : | Foam, water spray or fog. Dry chemical powder, carbon diox-<br>ide, sand or earth may be used for small fires only.   |
|---|---|---|
| Unsuitable extinguishing media                | : | Do not use water in a jet.  |
| Specific hazards during fire-<br>fighting     | : | Hazardous combustion products may include:<br>A complex mixture of airborne solid and liquid particulates and<br>gases (smoke).<br>Carbon monoxide may be evolved if incomplete combustion<br>occurs.<br>Unidentified organic and inorganic compounds.  |
| Specific extinguishing meth-<br>ods           | : | Use extinguishing measures that are appropriate to local cir-<br>cumstances and the surrounding environment.  |
| Special protective equipment for firefighters | : | Proper protective equipment including chemical resistant<br>gloves are to be worn; chemical resistant suit is indicated if<br>large contact with spilled product is expected. Self-Contained<br>Breathing Apparatus must be worn when approaching a fire in<br>a confined space. Select fire fighter's clothing approved to<br>relevant Standards (e.g. Europe: EN469). |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protec-<br>tive equipment and emer-<br>gency procedures | : | Avoid contact with skin and eyes.  |
|---|---|--|
| Environmental precautions   | : | Use appropriate containment to avoid environmental contami-<br>nation. Prevent from spreading or entering drains, ditches or<br>rivers by using sand, earth, or other appropriate barriers.  |
|   |   | Local authorities should be advised if significant spillages cannot be contained.  |
| Methods and materials for containment and cleaning up                         | : | Slippery when spilt. Avoid accidents, clean up immediately.<br>Prevent from spreading by making a barrier with sand, earth<br>or other containment material.<br>Reclaim liquid directly or in an absorbent.<br>Soak up residue with an absorbent such as clay, sand or other<br>suitable material and dispose of properly. |
| Additional advice   | : | For guidance on selection of personal protective equipment   |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T1 30

| Version<br>1.0 | Revision Date:<br>06/03/2019              | -    | S Number:<br>0010035375                                       | Print Date: 06/04/2019<br>Date of last issue: -   |
|----------------|---|------|---|---|
|                |   |      |   | this Safety Data Sheet.<br>disposal of spilled material see Chapter 13 of<br>Sheet.   |
| SECTIO         | ON 7. HANDLING AND ST                     | FORA | AGE   |   |
| Te             | chnical measures                          | :    | vapours, mists or<br>Use the information<br>sessment of local | t ventilation if there is risk of inhalation of<br>aerosols.<br>on in this data sheet as input to a risk as-<br>circumstances to help determine appropri-<br>ife handling, storage and disposal of this |
| Ad             | vice on safe handling                     | :    | Avoid inhaling va<br>When handling pr<br>worn and proper      | or repeated contact with skin.<br>bour and/or mists.<br>roduct in drums, safety footwear should be<br>nandling equipment should be used.<br>of any contaminated rags or cleaning mate-<br>event fires.  |
| Av             | oidance of contact                        | :    | Strong oxidising a  | igents.   |
| Pro            | oduct Transfer                            | :    |   | and bonding procedures should be used nsfer operations to avoid static accumulation.  |
|                | rther information on stor-<br>e stability | :    | place.  | ghtly closed and in a cool, well-ventilated led and closable containers.  |
|                |   |      | Store at ambient  | temperature.  |
| Pa             | ckaging material                          | :    | Suitable material:<br>steel or high dens<br>Unsuitable materi |   |
| Co             | ntainer Advice                            | :    |   | ainers should not be exposed to high tem-<br>e of possible risk of distortion.  |

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

| Components        | CAS-No.      | Value type<br>(Form of<br>exposure) | Control parame-<br>ters / Permissible<br>concentration | Basis    |
|-------------------|--------------|-------------------------------------|--|----------|
| Oil mist, mineral | Not Assigned | TWA (Mist)                          | 5 mg/m3  | OSHA Z-1 |
| Oil mist, mineral |              | TWA (Inhal-                         | 5 mg/m3  | ACGIH    |
|                   |              | able fraction)                      |  |          |

### **Biological occupational exposure limits**

No biological limit allocated.

### Monitoring Methods

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Rotella T1 30

| Version | Revision Date: | SDS Number:  | Print Date: 06/04/2019 |
|---------|----------------|--------------|------------------------|
| 1.0     | 06/03/2019     | 800010035375 | Date of last issue: -  |

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

| Engineering measures | : | The level of protection and types of controls necessary will<br>vary depending upon potential exposure conditions. Select<br>controls based on a risk assessment of local circumstances.<br>Appropriate measures include:<br>Adequate ventilation to control airborne concentrations.  |
|----------------------|---|--|
|                      |   | Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.  |
|                      |   | <ul> <li>General Information:</li> <li>Define procedures for safe handling and maintenance of controls.</li> <li>Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.</li> <li>Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.</li> <li>Drain down system prior to equipment break-in or maintenance.</li> <li>Retain drain downs in sealed storage pending disposal or subsequent recycle.</li> <li>Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.</li> <li>Practice good housekeeping.</li> </ul> |

### Personal protective equipment

| tions sl | rdance with good industrial hygiene practices, precau-<br>nould be taken to avoid breathing of material.<br>neering controls do not maintain airborne concentra- |
|----------|--|
|----------|--|

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Rotella T1 30

| ersion<br>.0 | Revision Date:<br>06/03/2019 | SDS Number<br>80001003537   |   |
|--------------|------------------------------|---|---|
|              |                              | select res<br>cific cond<br>Check wit<br>Where air<br>priate cor<br>Select a f  | level which is adequate to protect worker health,<br>piratory protection equipment suitable for the spe-<br>itions of use and meeting relevant legislation.<br>h respiratory protective equipment suppliers.<br>-filtering respirators are suitable, select an appro-<br>nbination of mask and filter.<br>ilter suitable for the combination of organic gases<br>urs [Type A/Type P boiling point >65°C (149°F)].   |
|              | protection                   |   |   |
| Re           | marks                        | gloves ap<br>US: F739<br>suitable c<br>gloves Su<br>usage, e.g<br>sistance c<br>glove sup<br>Personal<br>Gloves m<br>gloves, ha<br>cation of a<br>For contir<br>through ti<br>480 minut<br>short-term<br>recognize<br>may not b<br>time may<br>and repla<br>a good pr<br>depender<br>Glove thio | nd contact with the product may occur the use of<br>proved to relevant standards (e.g. Europe: EN374,<br>) made from the following materials may provide<br>hemical protection. PVC, neoprene or nitrile rubber<br>itability and durability of a glove is dependent on<br>g. frequency and duration of contact, chemical re-<br>of glove material, dexterity. Always seek advice from<br>pliers. Contaminated gloves should be replaced.<br>hygiene is a key element of effective hand care.<br>ust only be worn on clean hands. After using<br>ands should be washed and dried thoroughly. Appli-<br>a non-perfumed moisturizer is recommended.<br>nuous contact we recommend gloves with break-<br>me of more than 240 minutes with preference for ><br>tes where suitable gloves can be identified. For<br>n/splash protection we recommend the same but<br>that suitable gloves offering this level of protection<br>be available and in this case a lower breakthrough<br>be acceptable so long as appropriate maintenance<br>cement regimes are followed. Glove thickness is not<br>edictor of glove resistance to a chemical as it is<br>at on the exact composition of the glove material.<br>ckness should be typically greater than 0.35 mm<br>g on the glove make and model. |
| Еуе рі       | rotection                    |   | l is handled such that it could be splashed into eyes, eyewear is recommended.  |
| Skin a       | nd body protection           | work cloth  | ection is not ordinarily required beyond standard<br>nes.<br>practice to wear chemical resistant gloves.  |
| Protec       | tive measures                |   | protective equipment (PPE) should meet recom-<br>national standards. Check with PPE suppliers.  |
| Therm        | al hazards                   | : Not applic  | cable   |
| Enviro       | onmental exposure o          | ontrols   |   |
| Gener        | al advice                    |   | ropriate measures to fulfill the requirements of rele-  |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Rotella T1 30

| Version<br>1.0 | Revision Date:<br>06/03/2019                   |      | S Number:<br>0010035375                   | Print Date: 06/04/2019<br>Date of last issue: -   |
|----------------|--|------|---|---|
|                |  |      | discharge to surfa<br>Local guidelines of | strial waste water treatment plant before<br>ce water.<br>on emission limits for volatile substances<br>for the discharge of exhaust air containing |
| SECTIO         | ON 9. PHYSICAL AND CHE                         | EMIC | CAL PROPERTIES                            | 6   |
| Ар             | pearance                                       | :    | Liquid at room te                         | mperature.  |
| Co             | lour   | :    | amber                                     |   |
| Oc             | lour   | :    | Slight hydrocarbo                         | on  |
| Oc             | lour Threshold                                 | :    | Data not availabl                         | e   |
| pН             | I  | :    | Not applicable                            |   |
| ро             | ur point                                       | :    | -24 °C / -11 °F<br>Method: ASTM D         | 97  |
|                | tial boiling point and boiling<br>nge          | :    | > 280 °C / 536 °F<br>estimated value(     |   |
| Fla            | ash point                                      | :    | 210 °C / 410 °F                           |   |
|                |  |      | Method: ASTM D                            | 92 (COC)  |
| Ev             | aporation rate                                 | :    | Data not availabl                         | e   |
| Fla            | ammability (solid, gas)                        | :    | Data not availabl                         | e   |
|                | per explosion limit / upper<br>mmability limit | :    | Typical 10 %(V)                           |   |
|                | wer explosion limit / Lower<br>mmability limit | :    | Typical 1 %(V)                            |   |
| Va             | pour pressure                                  | :    | < 0.5 Pa (20 °C /                         | 68 °F)  |
|                |  |      | estimated value(                          | 5)  |
| Re             | lative vapour density                          | :    | > 1<br>estimated value(                   | 5)  |
| Re             | lative density                                 | :    | 0.887 (15.0 °C /                          | 59.0 °F)  |
| De             | ensity   | :    | 887 kg/m3 (15.0<br>Method: ASTM D         |   |
| So             | lubility(ies)<br>Water solubility              | :    | negligible                                |   |
|                | Solubility in other solvents                   | :    | Data not availabl                         | e   |
|                |  |      |   |   |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Rotella T1 30

| Version<br>1.0 | Revision Date:<br>06/03/2019          |   | S Number:<br>0010035375 | Print Date: 06/04/2019<br>Date of last issue: - |
|----------------|---------------------------------------|---|-------------------------|---|
| oct            | rtition coefficient: n-<br>anol/water | : | (based on inform        | ation on similar products)                      |
| Au             | to-ignition temperature               | : | > 320 °C / 608 °F       | -   |
| De             | composition temperature               | : | Data not availabl       | e   |
| Vis            | cosity<br>Viscosity, dynamic          | : | Data not availabl       | e   |
|                | Viscosity, kinematic                  |   | 107 mm2/s (40.0         | °C / 104.0 °F)                                  |
|                |                                       |   | Method: ASTM E          | 0445  |
|                |                                       |   | 11.9 mm2/s (100         | °C / 212 °F)                                    |
|                |                                       |   | Method: ASTM E          | 0445  |
| Ex             | plosive properties                    | : | Not classified          |   |
| Ox             | idizing properties                    | : | Data not availabl       | e   |
| Co             | nductivity                            | : | This material is r      | ot expected to be a static accumulator.         |

### SECTION 10. STABILITY AND REACTIVITY

| Reactivity                              | : | The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. |
|---|---|--|
| Chemical stability                      | : | Stable.  |
| Possibility of hazardous reac-<br>tions | : | Reacts with strong oxidising agents.   |
| Conditions to avoid                     | : | Extremes of temperature and direct sunlight.   |
| Incompatible materials                  | : | Strong oxidising agents.   |
| Hazardous decomposition products        | : | No decomposition if stored and applied as directed.  |

### SECTION 11. TOXICOLOGICAL INFORMATION

| Basis for assessment | : | Information given is based on data on the components and<br>the toxicology of similar products.Unless indicated otherwise,<br>the data presented is representative of the product as a<br>whole rather than for individual component(s) |
|----------------------|---|---|
|                      |   | whole, rather than for individual component(s).   |

### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T1 30

| Version<br>1.0 | Revision Date:<br>06/03/2019 |   | 0S Number:<br>0010035375                            | Print Date: 06/04/2019<br>Date of last issue: -   |
|----------------|------------------------------|---|---|---|
| Produ          | ict:                         |   |   |   |
| Acute          | oral toxicity                | : | LD50 (rat): > 5,<br>Remarks: Low<br>Based on availa |   |
| Acute          | inhalation toxicity          | : | Remarks: Base are not met.                          | ed on available data, the classification criteria |
| Acute          | dermal toxicity              | : | LD50 (Rabbit):<br>Remarks: Low<br>Based on availa   |   |

### Skin corrosion/irritation

### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

### Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

### Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

### Carcinogenicity

### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Rotella T1 30

| Version<br>1.0 | Revision Date:<br>06/03/2019   | SDS Number:<br>800010035375   | Print Date: 06/04/2019<br>Date of last issue: -  |  |  |  |  |
|----------------|--|---|--|--|--|--|--|
|                |  |   |  |  |  |  |  |
| OSH            | A  |   | this product present at levels greater than or n OSHA's list of regulated carcinogens.           |  |  |  |  |
| NTP            |  | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |  |  |  |  |  |
| Repro          | oductive toxicity  |   |  |  |  |  |  |
| <u>Produ</u>   | <u>ict:</u>  |   |  |  |  |  |  |
|                |  |   | a developmental toxicant., Does not impair<br>on available data, the classification criteria are |  |  |  |  |
| ѕтот           | - single exposure  |   |  |  |  |  |  |
| <u>Produ</u>   | Product:   |   |  |  |  |  |  |
| Rema           | Remarks: Based on available data, the classification criteria are not met. |   |  |  |  |  |  |
| ѕтот           | - repeated exposure  |   |  |  |  |  |  |
| <u>Produ</u>   | Product:   |   |  |  |  |  |  |

Remarks: Based on available data, the classification criteria are not met.

### Aspiration toxicity

### Product:

Not an aspiration hazard.

### **Further information**

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

### SECTION 12. ECOLOGICAL INFORMATION

| Basis for assessment | : Ecotoxicological data have not been determined specifically |
|----------------------|---|
|                      | for this product.   |
|                      | Information given is based on a knowledge of the components   |
|                      | and the ecotoxicology of similar products.                    |
|                      | Unless indicated otherwise, the data presented is representa- |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Rotella T1 30

| rsion                         | Revision Date:<br>06/03/2019                                |     | 0S Number:<br>0010035375                                    | Print Date: 06/04/2019<br>Date of last issue: -   |
|-------------------------------|---|-----|---|---|
|                               |   |     | ponent(s).(LL/EL/   | t as a whole, rather than for individual com-<br>IL50 expressed as the nominal amount of<br>to prepare aqueous test extract). |
| Ecoto                         | xicity  |     |   |   |
| <u>Produ</u><br>Toxici<br>ty) | <b>ict:</b><br>ty to fish (Acute toxici-                    | :   | Remarks: LL/EL/I<br>Practically non to:<br>Based on availab |   |
|                               | ty to daphnia and other<br>c invertebrates (Acute<br>y)     | :   | Remarks: LL/EL/I<br>Practically non to:<br>Based on availab |   |
| Toxici<br>icity)              | ty to algae (Acute tox-                                     | :   | Remarks: LL/EL/I<br>Practically non to:<br>Based on availab |   |
| Toxici<br>icity)              | ty to fish (Chronic tox-                                    | :   | Remarks: Data no  | ot available  |
|                               | ty to daphnia and other<br>c invertebrates (Chron-<br>city) | :   | Remarks: Data no  | ot available  |
|                               | ty to microorganisms<br>toxicity)                           | :   | Remarks: Data no  | ot available  |
| Persis                        | stence and degradabili                                      | ity |   |   |
| <u>Produ</u><br>Biode         | <b>ict:</b><br>gradability                                  | :   | Major constituents  | dily biodegradable.<br>s are inherently biodegradable, but contains<br>may persist in the environment.                        |
| Bioac                         | cumulative potential  |     |   |   |
| <u>Produ</u>                  | -   |     |   |   |
|                               | cumulation  | :   | Remarks: Contair cumulate.                                  | ns components with the potential to bioac-  |
| Mobil                         | ity in soil   |     |   |   |
| <u>Produ</u>                  | ict:  |     |   |   |
| Mobili                        | ty  | :   |   | under most environmental conditions.<br>will adsorb to soil particles and will not be   |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T1 30

| Vers<br>1.0 | sion                                     | Revision Date:<br>06/03/2019 |     | S Number:<br>0010035375   | Print Date: 06/04/2019<br>Date of last issue: -  |  |  |  |
|-------------|--|------------------------------|-----|---|--|--|--|--|
|             |  |                              |     | Remarks: Floats   | on water.  |  |  |  |
|             | Other                                    | adverse effects              |     |   |  |  |  |  |
|             | Produ                                    | ct.                          |     |   |  |  |  |  |
|             | Additional ecological infor- :<br>mation |                              |     | Does not have ozone depletion potential, photochemical<br>ozone creation potential or global warming potential.<br>Product is a mixture of non-volatile components, which will not<br>be released to air in any significant quantities under normal<br>conditions of use. |  |  |  |  |
|             |  |                              |     | Poorly soluble mi<br>Causes physical f  | xture.<br>ouling of aquatic organisms.   |  |  |  |
|             |  |                              |     |   | ot cause chronic toxicity to aquatic organ-<br>tions less than 1 mg/l.   |  |  |  |
| SEC         | CTION 1                                  | 3. DISPOSAL CONSI            | DER | ATIONS  |  |  |  |  |
|             | Dispos                                   | sal methods                  |     |   |  |  |  |  |
|             |  | from residues                | :   | toxicity and physic<br>determine the pro-<br>ods in compliance  | e if possible.<br>ility of the waste generator to determine the<br>cal properties of the material generated to<br>per waste classification and disposal meth-<br>e with applicable regulations.<br>to the environment, in drains or in water |  |  |  |
|             |  |                              |     | ground water, or l  | ould not be allowed to contaminate soil or<br>be disposed of into the environment.<br>sed product is dangerous waste.  |  |  |  |
|             | Contar                                   | ninated packaging            | :   | to a recognized c<br>the collector or cc<br>Disposal should b   | lance with prevailing regulations, preferably<br>ollector or contractor. The competence of<br>ontractor should be established beforehand.<br>be in accordance with applicable regional,<br>I laws and regulations.                           |  |  |  |
|             | Local Remar                              | l <b>egislation</b><br>ks    | :   |   | e in accordance with applicable regional,<br>I laws and regulations.   |  |  |  |

### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

### US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

### International Regulations

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T1 30

| Version | Revision Date: | SDS Number:  |
|---------|----------------|--------------|
| 1.0     | 06/03/2019     | 800010035375 |

Print Date: 06/04/2019 Date of last issue: -

### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code** Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

\*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

| SARA 311/312 Hazards | : | No SARA Hazards  |            |                   |
|----------------------|---|--|------------|-------------------|
| SARA 313             | : | The following components are subject to reporting levels e tablished by SARA Title III, Section 313:   |            | orting levels es- |
|                      |   | Phosphorodithioic acid,<br>mixed O,O-bis(2-<br>ethylhexyl and iso-Bu and<br>iso-Pr) esters, zinc salts | 85940-28-9 | >= 1 - < 5 %      |

#### **Clean Water Act**

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

#### US State Regulations

#### Pennsylvania Right To Know

| Distillates (petroleum), hydrotreated heavy paraffinic<br>Distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-54-7<br>64742-65-0 |
|---|--------------------------|
| Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-   | 85940-28-9               |
| Bu and iso-Pr) esters, zinc salts   |                          |
| Distillates (petroleum), hydrotreated light   | 64742-47-8               |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Rotella T1 30

| Version | Revision Date: | SDS Number:  | Print Date: 06/04/2019 |
|---------|----------------|--------------|------------------------|
| 1.0     | 06/03/2019     | 800010035375 | Date of last issue: -  |

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy paraffinic64742-54-7Distillates (petroleum), solvent-dewaxed heavy paraffinic64742-65-0Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-85940-28-9Bu and iso-Pr) esters, zinc salts85940-28-9

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

| The components of this product are reported in the following inventories: |   |  |  |  |  |
|---|---|--|--|--|--|
| EINECS  | : | All components listed or polymer exempt. |  |  |  |

| EINECS | : | All components listed or polymer exe |
|--------|---|--------------------------------------|
| TSCA   | : | All components listed.               |
| DSL    | : | All components listed.               |

### **SECTION 16. OTHER INFORMATION**

#### Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

#### Full text of other abbreviations

| ACGIH<br>OSHA Z-1<br>ACGIH / TWA<br>OSHA Z-1 / TWA<br>Abbreviations and Acronyms | : | USA. ACGIH Threshold Limit Values (TLV)<br>USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-<br>its for Air Contaminants<br>8-hour, time-weighted average<br>8-hour time weighted average<br>The standard abbreviations and acronyms used in this docu-<br>ment can be looked up in reference literature (e.g. scientific<br>dictionaries) and/or websites.   |
|--|---|---|
|  |   | ACGIH = American Conference of Governmental Industrial<br>Hygienists<br>ADR = European Agreement concerning the International<br>Carriage of Dangerous Goods by Road<br>AICS = Australian Inventory of Chemical Substances<br>ASTM = American Society for Testing and Materials<br>BEL = Biological exposure limits<br>BTEX = Benzene, Toluene, Ethylbenzene, Xylenes<br>CAS = Chemical Abstracts Service<br>CEFIC = European Chemical Industry Council<br>CLP = Classification Packaging and Labelling<br>COC = Cleveland Open-Cup<br>DIN = Deutsches Institut fur Normung |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Rotella T1 30

| Version | Revision Date: | SDS Number:  | Print Date: 06/04/2019  |
|---------|----------------|--|---|
| 1.0     | 06/03/2019     | 800010035375   | Date of last issue: -   |
|         |                | DNEL = Derive<br>DSL = Canada<br>EC = Europear<br>EC50 = Effectiv<br>ECETOC = Eu<br>gy Of Chemica<br>ECHA = Europ<br>EINECS = The<br>Chemical Subs<br>EL50 = Effectiv<br>ENCS = Japan<br>Inventory<br>EWC = Europe<br>GHS = Globally<br>Labelling of Ch<br>IARC = Interna<br>IATA = Interna<br>IC50 = Inhibitor<br>IL50 = Inhibitor<br>IMDG = Interna<br>INV = Chinese<br>IP346 = Institu<br>determination of<br>KECI = Korea<br>LC50 = Lethal<br>LD50 = Lethal<br>LL/EL/IL = Leth<br>LL50 = Lethal<br>LL/EL/IL = Leth<br>LD50 = Lethal<br>INV = Oci<br>PBT = Persiste<br>PICCS = Philip<br>Substances<br>PNEC = Predic<br>REACH = Reg<br>Chemicals<br>RID = Regulati<br>gerous Goods<br>SKIN_DES = S<br>STEL = Short t<br>TRA = Targete<br>TSCA = US To<br>TWA = Time-W | ve Concentration fifty<br>ropean Center on Ecotoxicology and Toxicolo-<br>ls<br>ean Chemicals Agency<br>European Inventory of Existing Commercial<br>stances<br>ve Loading fifty<br>tese Existing and New Chemical Substances<br>an Waste Code<br>y Harmonised System of Classification and<br>temicals<br>tional Agency for Research on Cancer<br>tional Agency for Research on Cancer<br>tional Air Transport Association<br>ry Concentration fifty<br>y Level fifty<br>ational Maritime Dangerous Goods<br>Chemicals Inventory<br>the of Petroleum test method N° 346 for the<br>of polycyclic aromatics DMSO-extractables<br>Existing Chemicals Inventory<br>Concentration fifty<br>Dose fifty per cent.<br>hal Loading/Effective Loading/Inhibitory loading<br>Loading fifty<br>ernational Convention for the Prevention of<br>Ships<br>No Observed Effect Concentration / No Ob-<br>tevel<br>cupational Exposure - High Production Volume<br>ent, Bioaccumulative and Toxic<br>opine Inventory of Chemicals and Chemical<br>cted No Effect Concentration<br>istration Evaluation And Authorisation Of<br>ons Relating to International Carriage of Dan- |

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to : compile the Safety Data Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T1 30

| Version | Revision Date: | SDS Number:  | Print Date: 06/04/2019 |
|---------|----------------|--------------|------------------------|
| 1.0     | 06/03/2019     | 800010035375 | Date of last issue: -  |
|         |                |              |                        |

IUCLID date base, EC 1272 regulation, etc).

Revision Date : 06/03/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN