According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version 1.2	Revision Date: 01/02/2020	SDS Number: 800010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019	
SECTION	1. IDENTIFICATION			
Produ	uct name	: Shell Tellus S4	VE 46	
Produ	uct code	: 001F8443		
Manu	afacturer or supplier'	s details		
Manu	facturer/Supplier	: Shell Oil Prod PO Box 4427 Houston TX 7 USA		
	Request omer Service	: (+1) 877-276-7 :	285	
Spill I		mber : 877-504-9351 : 877-242-7400		
	mmended use of the mmended use	e <b>chemical and restric</b> : Hydraulic oil	ctions on use	

## SECTION 2. HAZARDS IDENTIFICATION

## GHS classification in accordance with 29 CFR 1910.1200

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements Hazard pictograms :	No Hazard Symbol required
Signal word	No signal word
Hazard statements	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	<b>Prevention:</b> No precautionary phrases.
	<b>Response:</b> No precautionary phrases.
	Storage: No precautionary phrases.
	Disposal:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version	Revision Date:	SDS Number:
1.2	01/02/2020	800010034922

Print Date: 01/03/2020 Date of last issue: 09/30/2019

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Blend of polyolefins and additives.

## Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Distillates (Fischer - Tropsch), heavy, C18-50 – branched, cyclic and linear	Distillates (Fischer- Tropsch), heavy, C18-50- branched, cy- clic and linear	848301-69-9	85 - 95
		91273-04-0	0.01 - 0.05

### **SECTION 4. FIRST-AID MEASURES**

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
		When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Tellus S4 VE 46

Vers 1.2	sion	Revision Date: 01/02/2020		9S Number: 0010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019
		nportant symptoms ects, both acute and d	:	of black pustules a Ingestion may res Local necrosis is a	signs and symptoms may include formation and spots on the skin of exposed areas. ult in nausea, vomiting and/or diarrhoea. evidenced by delayed onset of pain and ew hours following injection.
	Protect	ion of first-aiders	:		ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings.
	medica	on of any immediate I attention and special ent needed	:	Treat symptomation	cally.
				vention and possil age and loss of fu Because entry wo ousness of the un determine the external anaesthetics or ho can contribute to s surgical decompre- eign material should	ection injuries require prompt surgical inter- bly steroid therapy, to minimise tissue dam- nction. unds are small and do not reflect the seri- derlying damage, surgical exploration to ent of involvement may be necessary. Local ot soaks should be avoided because they swelling, vasospasm and ischaemia. Prompt ession, debridement and evacuation of for- uld be performed under general anaesthet- oration is essential.

## SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media :	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing : media	:	Do not use water in a jet.
Specific hazards during fire- : fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- : ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment : for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Tellus S4 VE 46

Version	Revision Date:	SDS Number:	Print Date: 01/03/2020
1.2	01/02/2020	800010034922	Date of last issue: 09/30/2019

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

### SECTION 7. HANDLING AND STORAGE

Technical measures :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact :	Strong oxidising agents.
Further information on stor- : age stability	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. Store at ambient temperature.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version 1.2	Revision Date: 01/02/2020	SDS Number: 800010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019
Packa	aging material		ial: For containers or container linings, use mild ensity polyethylene. terial: PVC.
Conta	ainer Advice		ontainers should not be exposed to high tem- use of possible risk of distortion.

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

## Biological occupational exposure limits

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
		Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
		General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective

Drain down system prior to equipment break-in or mainte-

equipment, local exhaust ventilation.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version 1.2	Revision Date: 01/02/2020	SDS Number: 800010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019
		subsequent Always obse washing har drinking, and protective ed taminated cl	downs in sealed storage pending disposal or recycle. erve good personal hygiene measures, such as nds after handling the material and before eating, d/or smoking. Routinely wash work clothing and quipment to remove contaminants. Discard con- othing and footwear that cannot be cleaned. od housekeeping.
Person	al protective equi	pment	
Respira	atory protection	conditions of In accordance tions should If engineering tions to a leve select respir cific condition Check with r Where air-fill priate combine Select a filte	ce with good industrial hygiene practices, precau- be taken to avoid breathing of material. In g controls do not maintain airborne concentra- vel which is adequate to protect worker health, atory protection equipment suitable for the spe- ns of use and meeting relevant legislation. respiratory protective equipment suppliers. tering respirators are suitable, select an appro- ination of mask and filter. r suitable for the combination of organic gases and particles [Type A/Type P boiling point
	narks	gloves appro US: F739) m suitable che gloves Suita usage, e.g. f sistance of g glove supplie Personal hyg Gloves must gloves, hand cation of a n For continue through time 480 minutes short-term/s recognize th may not be a time maybe and replacen a good pred dependent of Glove thickn	contact with the product may occur the use of byed to relevant standards (e.g. Europe: EN374, nade from the following materials may provide mical protection. PVC, neoprene or nitrile rubber bility and durability of a glove is dependent on frequency and duration of contact, chemical re- glove material, dexterity. Always seek advice from ers. Contaminated gloves should be replaced. giene is a key element of effective hand care. t only be worn on clean hands. After using ds should be washed and dried thoroughly. Appli- on-perfumed moisturizer is recommended. bus contact we recommend gloves with break- e of more than 240 minutes with preference for > where suitable gloves can be identified. For plash protection we recommend the same but at suitable gloves offering this level of protection available and in this case a lower breakthrough acceptable so long as appropriate maintenance ment regimes are followed. Glove thickness is not ictor of glove resistance to a chemical as it is on the exact composition of the glove material. tess should be typically greater than 0.35 mm on the glove make and model.
Eye pro	otection	: If material is	handled such that it could be splashed into eyes,

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Tellus S4 VE 46

Version 1.2	Revision Date: 01/02/2020	SDS Number: Print Date: 01/03/2020 B00010034922 Date of last issue: 09/30/201	9
		protective eyewear is recommended.	
Skin a	and body protection	<ul> <li>Skin protection is not ordinarily required beyond work clothes.</li> <li>It is good practice to wear chemical resistant global</li> </ul>	
Prote	ctive measures	: Personal protective equipment (PPE) should me mended national standards. Check with PPE su	
Therr	nal hazards	: Not applicable	
Envir	onmental exposure c	trols	
Gene	ral advice	<ul> <li>Take appropriate measures to fulfill the requirer vant environmental protection legislation. Avoid of the environment by following advice given in necessary, prevent undissolved material from b charged to waste water. Waste water should be municipal or industrial waste water treatment pla discharge to surface water. Local guidelines on emission limits for volatile s must be observed for the discharge of exhaust a vapour.</li> </ul>	contamination Section 6. If eing dis- treated in a ant before ubstances

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	colourless
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-48 °C / -54 °F Method: ISO 3016
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	260 °C / 500 °F
		Method: ASTM D92 (COC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower	:	Typical 1 %(V)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Tellus S4 VE 46

Versioi 1.2	n	Revision Date: 01/02/2020		S Number: 010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019
fla	ammal	pility limit			
Va	apour	pressure	:	< 0.5 Pa (20 °C /	68 °F)
				estimated value(	3)
R	elative	vapour density	:	> 1 estimated value(	5)
R	elative	density	:	0.832 (15.0 °C /	59.0 °F)
De	ensity		:	832 kg/m3 (15.0 Method: ISO 121	
So	olubilit Wate	y(ies) er solubility	:	negligible	
	Solu	bility in other solvents	:	Data not availabl	e
	artitior ctanol/	n coefficient: n- water	:	log Pow: > 6 (based on inform	ation on similar products)
Au	uto-igr	nition temperature	:	> 320 °C / 608 °F	-
De	ecomp	oosition temperature	:	Data not availabl	e
Vi	iscosit Visco	y osity, dynamic	:	Data not availabl	e
	Visco	osity, kinematic	:	46 mm2/s (40.0 °	C / 104.0 °F)
				Method: ISO 310	4
				8.7 mm2/s (100 °	C / 212 °F)
				Method: ISO 310	4
E	xplosiv	ve properties	:	Not classified	
O	xidizin	g properties	:	Data not availabl	e
C	onduc	tivity	:	This material is n	ot expected to be a static accumulator.

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version 1.2	Revision Date: 01/02/2020	SDS Number: 800010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019
	itions to avoid npatible materials	: Extremes of te : Strong oxidisir	emperature and direct sunlight.
Hazar produ	rdous decomposition	: No decompos	ition if stored and applied as directed.

## SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a
		whole, rather than for individual component(s).

### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Acute toxicity

## Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

#### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

### Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

### Components:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version	Revision Date:	SDS Number:	Print Date: 01/03/2020
1.2	01/02/2020	800010034922	Date of last issue: 09/30/2019

#### Triazole derivative:

Remarks: May cause an allergic skin reaction in sensitive individuals.

#### Germ cell mutagenicity

#### Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

#### Carcinogenicity

### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

### Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

### STOT - single exposure

## Product:

Remarks: Based on available data, the classification criteria are not met.

÷

### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

### Aspiration toxicity

### Product:

Not an aspiration hazard.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version	Revision Date:
1.2	01/02/2020

SDS Number: 800010034922 Print Date: 01/03/2020 Date of last issue: 09/30/2019

### Further information

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

### SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity		
Product: Toxicity to fish (Acute toxici- ty)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other aquatic invertebrates (Acute toxicity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae (Acute tox- icity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chron-ic toxicity)	:	Remarks: Data not available
Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Versio 1.2	n Revision Date: 01/02/2020		DS Number: 0010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019
<u>C</u> (	omponents:			
M	<b>Triazole derivative:</b> M-Factor (Acute aquatic tox- icity)		1	
Pe	Persistence and degradability			
<u>Pı</u>	roduct:			
Bi	Biodegradability		Major constituents	dily biodegradable. s are inherently biodegradable, but contains may persist in the environment.
Bioaccumulative potential				
<u>Pı</u>	roduct:			
Bi	Bioaccumulation Mobility in soil		Remarks: Contair cumulate.	is components with the potential to bioac-
М				
<u>P</u> 1	roduct:			
М	lobility	:		Inder most environmental conditions. vill adsorb to soil particles and will not be
			Remarks: Floats of	on water.
O	ther adverse effects			
<u>P</u> 1	roduct:			
	dditional ecological infor- ation	:	ozone creation po Product is a mixtu	one depletion potential, photochemical itential or global warming potential. Ire of non-volatile components, which will not in any significant quantities under normal
			Poorly soluble mix Causes physical f	cture. ouling of aquatic organisms.

## SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>Recover or recycle if possible.</li> <li>It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.</li> <li>Do not dispose into the environment, in drains or in water courses</li> </ul>

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version 1.2	Revision Date: 01/02/2020	SDS Number: 800010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019		
		ground water	ct should not be allowed to contaminate soil or , or be disposed of into the environment. or used product is dangerous waste.		
Contaminated packaging		to a recognize the collector o Disposal sho	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.		
<b>Local</b> Rema	legislation rks	•	uld be in accordance with applicable regional, local laws and regulations.		

## SECTION 14. TRANSPORT INFORMATION

#### **National Regulations**

### US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

#### International Regulations

### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### **SECTION 15. REGULATORY INFORMATION**

### EPCRA - Emergency Planning and Community Right-to-Know Act

\*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

#### SARA 311/312 Hazards : No SARA Hazards

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

ersion 2	Revision Date: 01/02/2020	SDS Number: 800010034922	Print Date: 01/0 Date of last issu	
SAR	A 313	known CAS nu	imbers that exceed	/ chemical components wi the threshold (De Minimis RA Title III, Section 313.
	n Water Act			
	product does not contain on 311, Table 117.3.	ain any Hazardous Ch	emicals listed under	r the U.S. CleanWater Act
US S	tate Regulations			
Penn	<b>sylvania Right To K</b> i Distillates (petrol Zinc dialkyldithio	eum), hydrotreated lig	ht paraffinic	64742-55-8 4259-15-8
This p	ornia Prop. 65 product does not conta ts, or any other reprod		wn to State of Califo	ornia to cause cancer, birth
Califo	ornia List of Hazardo Distillates (petrol	ous Substances eum), hydrotreated lig	ht paraffinic	64742-55-8
The r	r regulations: egulatory information s material.	is not intended to be c	omprehensive. Oth	er regulations may apply
The c	•	oroduct are reported : All component	<b>in the following in</b> s listed or polymer e	
	A	: All component	s listed.	
TSCA				

## **Further information**

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

## Full text of other abbreviations

Abbreviations and Acronyms :	The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
	ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version 1.2	Revision Date: 01/02/2020	SDS Number: 800010034922	Print Date: 01/03/2020 Date of last issue: 09/30/2019
		BTEX = Benze CAS = Chemic CEFIC = Europ CLP = Classific COC = Clevela DIN = Deutsch DMEL = Derive DNEL = Derive DSL = Canada EC = Europear EC50 = Effectiv ECETOC = Eu gy Of Chemica ECHA = Europ EINECS = The Chemical Subs EL50 = Effectiv ENCS = Japan Inventory EWC = Europe GHS = Globally Labelling of Ch IARC = Interna IATA = Internat IC50 = Inhibitor IL50 = Inhibitor IMDG = Internat INV = Chinese IP346 = Institu determination of KECI = Korea I LC50 = Lethal LL/EL/IL = Leth LD50 = Lethal UD50 = Lethal UD50 = Lethal UD50 = Lethal EL50 = Lethal CS0 = Lethal CS0	es Institut fur Normung ad Minimal Effect Level d No Effect Level Domestic Substance List o Commission ve Concentration fifty ropean Center on Ecotoxicology and Toxicolo- ls ean Chemicals Agency European Inventory of Existing Commercial stances re Loading fifty ese Existing and New Chemical Substances an Waste Code y Harmonised System of Classification and emicals tional Agency for Research on Cancer tional Agency for Research on Cancer tional Agency for Research on Cancer tional Air Transport Association ry Concentration fifty y Level fifty ational Maritime Dangerous Goods Chemicals Inventory te of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. hal Loading/Effective Loading/Inhibitory loading Loading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume int, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical ted No Effect Concentration stration Evaluation And Authorisation Of
		vPvB = very Pe	ersistent and very Bioaccumulative

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Tellus S4 VE 46

Version	Revision Date:	SDS Number:	Print Date: 01/03/2020
1.2	01/02/2020	800010034922	Date of last issue: 09/30/2019

A vertical bar () in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	01/02/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN