According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version 1.2	Revision Date: 08/17/2020	SDS Number: 800010026865	Print Date: 09/25/2020 Date of last issue: 04/22/2020						
SECTION	SECTION 1. IDENTIFICATION								
Produ	uct name	: Shell Rotella T	5 15W-40						
Product code		: 001F8906							
Manu	Manufacturer or supplier's details								
Manu	facturer/Supplier	: Shell Oil Proc PO Box 4427 Houston TX 7 USA							
SDS Request Customer Service		: (+1) 877-276- <sup>-</sup> :	7285						
Spill I	gency telephone num nformation h Information	nber : 877-504-9351 : 877-242-7400							
	mmended use of the mmended use	chemical and restri : Engine oil.	ctions on use						

#### SECTION 2. HAZARDS IDENTIFICATION

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements		
Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	<b>Revision Date:</b>
1.2	08/17/2020

SDS Number: 800010026865

Print Date: 09/25/2020 Date of last issue: 04/22/2020

#### Disposal:

No precautionary phrases.

#### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance / Mixture : Mixture

Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.	
		* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0,	

53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8.

#### Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Zinc dialkyldithio- phosphate	Phosphorodi- thioic acid, mixed O,O- bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	1 - 2.4
Alkylated phenol ester		125643-61-0	< 3
Alkaryl amine	bis(nonylphenyl )amine	36878-20-3	< 3
Alkyl phenate alka- noate		Not Assigned	< 3
Phosphorodithioic acid, mixed O,O- bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	Phosphorodi- thioic acid, mixed O,O- bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	85940-28-9	< 3
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Not Assigned	0 - 90

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020		
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020		
SECTION 4. FIRST-AID MEASURES					

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin co	ntact :	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye cor	ntact :	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important sy and effects, both a delayed	•	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-	aiders :	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Indication of any in medical attention treatment needed		Treat symptomatically.

#### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.	
Unsuitable extinguishing media	:	Do not use water in a jet.	
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.	
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.	
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020

relevant Standards (e.g. Europe: EN469).

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions		Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

#### SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version 1.2	Revision Date: 08/17/2020	SDS Number: 800010026865	Print Date: 09/25/2020 Date of last issue: 04/22/2020
		Store at ambier	nt temperature.
Packaging material			al: For containers or container linings, use mild nsity polyethylene. erial: PVC.
Conta	iner Advice		ontainers should not be exposed to high tem- use of possible risk of distortion.

#### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		
Distillates (petroleum), hy- drotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
Distillates (petroleum), hy-		TWA (Inhal-	5 mg/m3	ACGIH
drotreated heavy paraffinic		able particu-		
		late matter)		
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	TWA (Mist)	5 mg/m3	OSHA Z-1
Distillates (petroleum), solvent-		TWA (Inhal-	5 mg/m3	ACGIH
dewaxed heavy paraffinic		able particu-		
		late matter)		
Distillates (petroleum), hy-	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
drotreated light paraffinic				
Distillates (petroleum), hy-		TWA (Inhal-	5 mg/m3	ACGIH
drotreated light paraffinic		able particu-		
		late matter)		
Distillates (petroleum), solvent-	64742-65-0	TWA (Mist)	5 mg/m3	OSHA Z-1
dewaxed heavy paraffinic				
Distillates (petroleum), solvent-		TWA (Inhal-	5 mg/m3	ACGIH
dewaxed heavy paraffinic		able particu-		
		late matter)		

#### Components with workplace control parameters

#### **Biological occupational exposure limits**

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

**General Information:** 

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

Respiratory protection	<ul> <li>No respiratory protection is ordinarily required under normal conditions of use.</li> </ul>
	In accordance with good industrial hygiene practices, precau- tions should be taken to avoid breathing of material.
	If engineering controls do not maintain airborne concentra-
	tions to a level which is adequate to protect worker health,
	select respiratory protection equipment suitable for the spe-
	cific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.
	Where air-filtering respirators are suitable, select an appro-
	priate combination of mask and filter.
	Select a filter suitable for the combination of organic gases

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version 1.2	Revision Date: 08/17/2020	SDS Number: 800010026865	Print Date: 09/25/2020 Date of last issue: 04/22/2020
		and vapours a >65°C (149°F	and particles [Type A/Type P boiling point )].
Hand	d protection		
R	emarks	gloves approv US: F739) ma suitable chem gloves Suitab usage, e.g. fre sistance of glo glove supplier Personal hygi Gloves must o gloves, hands cation of a no For continuou through time of 480 minutes v short-term/spl recognize tha may not be av time maybe a and replacem a good predic dependent on Glove thickne	contact with the product may occur the use of red to relevant standards (e.g. Europe: EN374, de from the following materials may provide ical protection. PVC, neoprene or nitrile rubber lity and durability of a glove is dependent on equency and duration of contact, chemical re- ove material, dexterity. Always seek advice from s. Contaminated gloves should be replaced. ene is a key element of effective hand care. only be worn on clean hands. After using should be washed and dried thoroughly. Appli- n-perfumed moisturizer is recommended. s contact we recommend gloves with break- of more than 240 minutes with preference for > where suitable gloves can be identified. For ash protection we recommend the same but t suitable gloves offering this level of protection vailable and in this case a lower breakthrough cceptable so long as appropriate maintenance ent regimes are followed. Glove thickness is not tor of glove resistance to a chemical as it is the exact composition of the glove material. ss should be typically greater than 0.35 mm the glove make and model.
Eye	protection		andled such that it could be splashed into eyes, wear is recommended.
Skin	and body protection	work clothes.	n is not ordinarily required beyond standard standard standard standard standard resistant gloves.
Prote	ective measures	•	ective equipment (PPE) should meet recom- nal standards. Check with PPE suppliers.
Ther	mal hazards	: Not applicable	

#### Environmental exposure controls

General advice :	Take appropriate measures to fulfill the requirements of rele- vant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being dis- charged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
------------------	---

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	Clear amber
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-39 °C / -38 °F Method: ASTM D97
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	230 °C / 446 °F
		Method: ASTM D92 (COC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F)
		estimated value(s)
Relative vapour density	:	> 1 estimated value(s)
Relative density	:	0.873 (15 °C / 59 °F)
Density	:	873 kg/m3 (15.0 °C / 59.0 °F) Method: ASTM D4052
Solubility(ies) Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n- octanol/water	:	log Pow: > 6 (based on information on similar products)
Auto-ignition temperature	:	> 320 °C / 608 °F
Decomposition temperature	:	Data not available

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version 1.2	Revision Date: 08/17/2020		9S Number: 0010026865	Print Date: 09/25/2020 Date of last issue: 04/22/2020
	osity iscosity, dynamic iscosity, kinematic	:	Data not availab 14.5 mm2/s (100 Method: ASTM [	) °C / 212 °F)
Explo	osive properties	:	Not classified	
Oxid	zing properties	:	Data not availab	le
Cond	luctivity	:	This material is r	not expected to be a static accumulator.
SECTION	10. STABILITY AND F	REAC	TIVITY	
Read	tivity	:		s not pose any further reactivity hazards in listed in the following sub-paragraph.
Cher	nical stability	:	Stable.	

Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

#### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and
		the toxicology of similar products.Unless indicated otherwise,
		the data presented is representative of the product as a
		whole, rather than for individual component(s).

#### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

Product:	
Acute oral toxicity	<ul> <li>LD50 (rat): &gt; 5,000 mg/kg</li> <li>Remarks: Low toxicity:</li> <li>Based on available data, the classification criteria are not met.</li> </ul>
Acute inhalation toxicity	: Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	F
1.2	08/17/2020	800010026865	[

Print Date: 09/25/2020 Date of last issue: 04/22/2020

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

#### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

#### Components:

#### Zinc dialkyldithiophosphate:

Remarks: Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

#### Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

#### Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

#### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020

equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### **Reproductive toxicity**

#### Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

#### STOT - single exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

1

#### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Aspiration toxicity

Product: Not an aspiration hazard.

#### Further information

#### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

#### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment	<ul> <li>Ecotoxicological data have not been determined specifically for this product.</li> <li>Information given is based on a knowledge of the components and the ecotoxicology of similar products.</li> <li>Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).</li> </ul>

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

sion	Revision Date: 08/17/2020	-	9S Number: 0010026865	Print Date: 09/25/2020 Date of last issue: 04/22/2020
Ecoto	xicity			
Produ	ict:			
	ty to fish (Acute toxici-	:	Practically non	L/IL50 > 100 mg/I toxic: able data, the classification criteria are not m
	ty to daphnia and other c invertebrates (Acute y)	:	Practically non	L/IL50 > 100 mg/l toxic: able data, the classification criteria are not m
Toxicit icity)	ty to algae (Acute tox-	:	Practically non	L/IL50 > 100 mg/l toxic: able data, the classification criteria are not m
Toxicit icity)	ty to fish (Chronic tox-	:	Remarks: Data	not available
	ty to daphnia and other c invertebrates (Chron- city)	:	Remarks: Data	not available
	ty to microorganisms e toxicity)	:	Remarks: Data	not available
Persis	stence and degradabili	ity		
<u>Produ</u> Biodeç	<u>ict:</u> gradability	:	Major constitue	readily biodegradable. ents are inherently biodegradable, but contain at may persist in the environment.
Bioac	cumulative potential			
<u>Produ</u> Bioaco	i <u>ct:</u> cumulation	:	Remarks: Con cumulate.	tains components with the potential to bioac-
Mobili	ity in soil			
<u>Produ</u>	ict:			
Mobilit		:		id under most environmental conditions. it will adsorb to soil particles and will not be
			Remarks: Floa	ts on water.
Other	adverse effects			
	ict:			

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version 1.2	Revision Date: 08/17/2020	SDS Number: 800010026865	Print Date: 09/25/2020 Date of last issue: 04/22/2020
Additic matior	onal ecological infor- )	ozone creation p Product is a mixt	zone depletion potential, photochemical otential or global warming potential. ure of non-volatile components, which will not r in any significant quantities under normal
		Poorly soluble m Causes physical	ixture. fouling of aquatic organisms.
			not cause chronic toxicity to aquatic organ- ations less than 1 mg/l.

#### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	toxicity and physical p determine the proper ods in compliance with	oossible. of the waste generator to determine the roperties of the material generated to waste classification and disposal meth- h applicable regulations. e environment, in drains or in water
	ground water, or be di	not be allowed to contaminate soil or sposed of into the environment. product is dangerous waste.
Contaminated packaging	to a recognized collec the collector or contra	e with prevailing regulations, preferably tor or contractor. The competence of ctor should be established beforehand. accordance with applicable regional, <i>y</i> s and regulations.
Local legislation Remarks	Disposal should be in national, and local law	accordance with applicable regional, /s and regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **National Regulations**

#### US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### **SECTION 15. REGULATORY INFORMATION**

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
fumaric acid	110-17-8	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

- SARA 311/312 Hazards : No SARA Hazards
- SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Phosphorodithioic acid, mixed O,O-bis(2- ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	85940-28-9	>= 1 - < 5 %
Zinc dialkyldithiophos- phate	134759-18-5	>= 1 - < 5 %
Zinc dialkyldithiophos- phate	93819-94-4	>= 1 - < 5 %
Zinc dialkyldithiophos- phate	113706-15-3	>= 1 - < 5 %

#### **Clean Water Act**

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Ethylenediamine (SVHC)	107-15-3	0.003 %
fumaric acid	110-17-8	0.1554 %

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020

#### **US State Regulations**

#### Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso- Bu and iso-Pr) esters, zinc salts Distillates (petroleum), solvent-dewaxed heavy paraffinic	85940-28-9 64742-65-0
Zinc dialkyldithiophosphate	93819-94-4
Zinc dialkyldithiophosphate	113706-15-3
Zinc dialkyldithiophosphate	134759-18-5
fumaric acid	110-17-8
diphenylamine	122-39-4

#### California Prop. 65

WARNING: This product can expose you to chemicals including Ethanediol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### **California List of Hazardous Substances**

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-	85940-28-9
Bu and iso-Pr) esters, zinc salts	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Zinc dialkyldithiophosphate	93819-94-4
Zinc dialkyldithiophosphate	113706-15-3
Zinc dialkyldithiophosphate	134759-18-5

#### California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

#### **SECTION 16. OTHER INFORMATION**

#### Further information

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

#### Full text of other abbreviations

ACGIH :	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1 :	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-
	its for Air Contaminants
ACGIH / TWA :	8-hour, time-weighted average
OSHA Z-1 / TWA :	8-hour time weighted average
Abbreviations and Acronyms :	The standard abbreviations and acronyms used in this docu-
	ment can be looked up in reference literature (e.g. scientific
	dictionaries) and/or websites.
	ACGIH = American Conference of Governmental Industrial
	Hygienists
	ADR = European Agreement concerning the International
	Carriage of Dangerous Goods by Road
	AICS = Australian Inventory of Chemical Substances
	ASTM = American Society for Testing and Materials
	BEL = Biological exposure limits
	BTEX = Benzene, Toluene, Ethylbenzene, Xylenes
	CAS = Chemical Abstracts Service
	CEFIC = European Chemical Industry Council
	CLP = Classification Packaging and Labelling
	COC = Cleveland Open-Cup
	DIN = Deutsches Institut fur Normung
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	DSL = Canada Domestic Substance List
	EC = European Commission EC50 = Effective Concentration fifty
	ECETOC = European Center on Ecotoxicology and Toxicolo-
	gy Of Chemicals
	ECHA = European Chemicals Agency
	EINECS = The European Inventory of Existing Commercial
	Chemical Substances
	EL50 = Effective Loading fifty
	ENCS = Japanese Existing and New Chemical Substances
	Inventory
	EWC = European Waste Code
	GHS = Globally Harmonised System of Classification and
	Labelling of Chemicals
	IARC = International Agency for Research on Cancer
	IATA = International Air Transport Association
	IC50 = Inhibitory Concentration fifty
	IL50 = Inhibitory Level fifty
	IMDG = International Maritime Dangerous Goods
	INV = Chinese Chemicals Inventory
	IP346 = Institute of Petroleum test method N° 346 for the
	determination of polycyclic aromatics DMSO-extractables
	KECI = Korea Existing Chemicals Inventory
	LC50 = Lethal Concentration fifty
	LD50 = Lethal Dose fifty per cent.
	LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Rotella T5 15W-40

Version	Revision Date:	SDS Number:	Print Date: 09/25/2020
1.2	08/17/2020	800010026865	Date of last issue: 04/22/2020
		Pollution From NOEC/NOEL = served Effect L OE_HPV = Ocd PBT = Persiste PICCS = Philip Substances PNEC = Predic REACH = Regi Chemicals RID = Regulatid gerous Goods SKIN_DES = S STEL = Short to TRA = Targete TSCA = US To TWA = Time-W	ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume ont, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical eted No Effect Concentration stration Evaluation And Authorisation Of ons Relating to International Carriage of Dan-

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to : compile the Safety Data Sheet	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
---	--

Revision Date : 08/17/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN