ENDURATEX	TM/MC WG 460
------------------	--------------

000003000462

Version 2.6

Revision Date 2022/07/11



Print Date 2022/07/11

SECTION 1. IDENTIFICATION

Product name	:	ENDURATEX TM/MC WG 460
Product code	:	ENTW460P20, ENTW460DRM, ENTW460, ENTW460DCT
Manufacturer or supplier's de	ta	nils
		Petro-Canada America Lubricants LLC
		2828 N. Harwood St., Suite 1300
		Dallas TX 75201
		United States
Talanhana		
relephone	•	1-214-871-3555
Emergency telephone numbe	٩r	

Emergency telephone	:	CHEMTREC: 1-800-424-9300;
number		Poison Control Centre: Consult local telephone directory for
		emergency number(s).

Recommended use of the chemical and restrictions on use					
Recommended use	:	Enduratex WG Oils are used in the lubrication of industrial worm gear reducers, wet stream cylinder lubrication and high pressure wet gas compressors. They are also used for plain or anti-friction bearings operating under slow speed, high temperature, high pressure conditions.			

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

ENDURATEX TM/MC WG 460

000003000462

Version 2.6

Revision Date 2022/07/11 Print Date 2022/07/11

Chemical name	CAS-No.	Concentration (% w/w)
Residual oils (petroleum), solvent deasphalted; Baseoil — unspecified	64741-95-3	50 - 70
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	30 - 50
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	30 - 50
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high- viscosity; Baseoil — unspecified	72623-85-9	10 - 20

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	Nove to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.	
In case of skin contact	n case of contact, immediately flush skin with plenty of or at least 15 minutes while removing contaminated clu and shoes. Vash skin thoroughly with soap and water or use recog kin cleanser. Vash clothing before reuse. Seek medical advice.	othing
In case of eye contact	Remove contact lenses. Rinse immediately with plenty of water, also under the or at least 15 minutes. Dbtain medical attention.	eyelids,
If swallowed	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a hysician or poison control center. Never give anything by mouth to an unconscious perso Seek medical advice.	
Most important symptoms and effects, both acute and delayed	First aider needs to protect himself.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media :	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing : media	No information available.
Specific hazards during : firefighting	Cool closed containers exposed to fire with water spray.
Hazardous combustion :	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur
Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.	Page: 2 / 10 Petro-Canada Lubricants is a HF Sinclair brand



ENDURATEX TM/MC WG 460



000003000462

Version 2.6		Revision Date 2022/07/11	Print Date 2022/07/11
products		oxides (SOx), smoke and irritating vapours as products of incomplete combustion.	
Further information	:	Prevent fire extinguishing water from or water or the ground water system.	contaminating surface

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

	-			
Components	CAS-No.	Value type	Control	Basis
Internet: lubricants.petro-canada.com/sds	3			Page: 3 / 10
Trademarks are owned or used under license.			Petro-Canada Lubricants	is a HF Sinclair brand

ENDURATEX TM/MC WG 460

000003000462

Version 2.6

Revision Date 2022/07/11

Print Date 2022/07/11

51011 2.10			T fint Du		
		(Form of exposure)	parameters / Permissible concentration		
Residual oils (petroleum), solvent deasphalted; Baseoil — unspecified	64741-95-3	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH	
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH	
		TWA (Mist)	5 mg/m3	OSHA Z-1	
		TWA (Mist)	5 mg/m3	OSHA P0	
		TWA (Mist)	5 mg/m3	NIOSH REL	
		ST (Mist)	10 mg/m3	NIOSH REL	
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH	
		TWA (Mist)	5 mg/m3	OSHA Z-1	
		TWA (Mist)	5 mg/m3	OSHA P0	
		TWA (Mist)	5 mg/m3	NIOSH REL	
		ST (Mist)	10 mg/m3	NIOSH REL	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified	72623-85-9	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH	
		TWA (Mist)	5 mg/m3	OSHA Z-1	
		TWA (Mist)	5 mg/m3	OSHA P0	
		TWA (Mist)	5 mg/m3	NIOSH REL	
		ST (Mist)	10 mg/m3	NIOSH REL	
Engineering measures		ifficient to contro	ments. Good genera I worker exposure to		
Personal protective equipment	nt				
Respiratory protection	ventilation is that exposur Respirator se exposure lev	provided or exp es are within rec election must be	less adequate local osure assessment d ommended exposur based on known or of the product and t respirator.	emonstrates e guidelines. anticipated	
Filter type	organic vapo	our filter			
Hand protection Material	neoprene, ni	trile, polyvinyl al	cohol (PVA), Viton [®] .		
Remarks	approved sta	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.			
Eye protection	problems.	hield and protect	ive suit for abnorma		
not: lubricanta notra canada com/ad	•			$D_{\alpha\alpha\alpha} / / / 1$	



ENDURATEX TM/MC WG 460



000003000462

Version 2.6		Revision Date 2022/07/11	Print Date 2022/07/11
Skin and body protection	:	Choose body protection in relation to its concentration and amount of dangerous the specific work-place.	
Protective measures	:	Wash contaminated clothing before re-u	ise.
Hygiene measures	:	Remove and wash contaminated clothir including the inside, before re-use. Wash face, hands and any exposed ski handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	Dark greenish amber
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-3 °C (27 °F) No data available
Flash point	:	311 °C (592 °F) Method: Cleveland open cup
Fire Point	:	331 °C (628 °F)
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.904 kg/l (15 °C / 59 °F)
Solubility(ies)		

ENDURATEX TM/MC WG 460



000003000462

Version 2.6	Revision Date 2022/07/11	Print Date 2022/07/11
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity Viscosity, kinematic	: 444 cSt (40 °C / 104 °F)	
	28.6 cSt (100 °C / 212 °F)	
Explosive properties	: Do not pressurize, cut, weld, brain expose containers to heat or source to heat or	

SECTION 10. STABILITY AND REACTIVITY


Reactivity	:	Stable at normal ambient temperature and pressure.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents, acids, alkalis and reducing agents.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely route Eye contact Ingestion Inhalation Skin contact	s of exposure
Acute toxicity	
Product:	
Acute oral toxicity	: Remarks: No data available
Acute inhalation toxicity	: Remarks: No data available
Acute dermal toxicity	: Remarks: No data available
<u>Components:</u> Distillates (petroleum), hyd Acute oral toxicity	drotreated heavy paraffinic; Baseoil — unspecified: : LD50 (Rat): > 5,000 mg/kg,
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,
Distillates (petroleum), sol	vent-dewaxed heavy paraffinic; Baseoil — unspecified:

ENDURATEX TM/MC WG 460

000003000462



Ecotoxicity

Product:			
Toxicity to fish	:	Remarks: No data available	
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available	
Toxicity to algae/aquatic plants	:	Remarks: No data available	
Internet: lubricants.petro-canada.com/s Trademarks are owned or used under license.	sds		P



ENDURATEX TM/MC WG 460

000003000462



Version 2.6

	Toxicity to microorganisms	:	Remarks: No data available
	Persistence and degradabil	lity	
	Product:		
	Biodegradability	:	Remarks: No data available
	Bioaccumulative potential No data available		
	Mobility in soil No data available		
	Other adverse effects		
	No data available		
SEC	ECTION 13. DISPOSAL CONSIDERATIONS		

Disposal methods

Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
		of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

benzene

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include: 71-43-2

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

ENDURATEX TM/MC WG 460



000003000462

Version 2.6		Revision Date 2022/07/11	Print Date 2022/07/11
The components of this prod	luc	t are reported in the following invento	ories:
DSL	:	On the inventory, or in compliance with	the inventory
TSCA	:	All chemical substances in this product TSCA Inventory or are in compliance w exemption.	
IECSC	:	On the inventory, or in compliance with	the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704: HMIS® IV: Flammability HEALTH FLAMMABILITY 1 Health Instability 1 0 PHYSICAL HAZARD 0 HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "* Special hazard represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH NIOSH REL		USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits
OSHA P0		USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -

ENDURATEX TM/MC WG 460

000003000462

Version 2.6

Revision Date 2022/07/11

Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/07/11 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/07/11