| ENDURATEX | ^{™/MC} WG | 680 |
|------------------|--------------------|-----|
|------------------|--------------------|-----|

000003000463

| Version 2.6 | 2.6 Revision Date 2022/07/11 Print Date | |
|--------------------------------|--|----------------------|
| SECTION 1. IDENTIFICATION | | |
| Product name : | ENDURATEX TM/MC WG 680 | |
| Product code : | ENTW680BLK, ENTW680, ENTW680 | ORM |
| Manufacturer or supplier's det | ails Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555 | |
| Emergency telephone number | | |
| Emergency telephone num- : ber | CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local tel emergency number(s). | ephone directory for |

| Recommended use of the chemical and restrictions on use | | | | |
|---|---|---|--|--|
| Recommended use | : | Enduratex WG Oils are used in the lubrication of industrial worm gear reducers, wet stream cylinder lubrication and high pressure wet gas compressors. They are also used for plain or anti-friction bearings operating under slow speed, high temperature, high pressure conditions. | | |
| Prepared by | : | Product Safety: +1 905-491-0565 | | |

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

| IARC | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC. |
|------|--|
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. |
| NTP | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

ENDURATEX TM/MC WG 680

000003000463

Version 2.6

Revision Date 2022/07/11

Print Date 2022/07/11

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| Residual oils (petroleum), solvent deasphalted; Baseoil — unspecified | 64741-95-3 | 50 - 70 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified | 64742-65-0 | 30 - 50 |
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | 64742-54-7 | 1 - 5 |
| Lubricating oils (petroleum), C20-50, hy- drotreated neutral oil-based, high- viscosity; Baseoil — unspecified | 72623-85-9 | 1 - 5 |

SECTION 4. FIRST AID MEASURES

| If inhaled | : | Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice. |
|---|---|--|
| In case of skin contact | : | In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. |
| In case of eye contact | : | Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention. |
| If swallowed | : | Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice. |
| Most important symptoms and effects, both acute and delayed | : | First aider needs to protect himself. |

SECTION 5. FIREFIGHTING MEASURES

| Suitable extinguishing media : | Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. |
|--|--|
| Unsuitable extinguishing : media | No information available. |
| Specific hazards during fire- : fighting | Cool closed containers exposed to fire with water spray. |
| Hazardous combustion prod- : | Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur |
| Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. | Page: 2 / 10 Petro-Canada Lubricants is a HF Sinclair brand |

ENDURATEX TM/MC WG 680



000003000463

| Version 2.6 | | Revision Date 2022/07/11 | Print Date 2022/07/11 |
|---------------------|---|---|--------------------------|
| ucts | | oxides (SOx), smoke and irritatin incomplete combustion. | g vapours as products of |
| Further information | : | Prevent fire extinguishing water f water or the ground water system | |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protec- : tive equipment and emer- gency procedures | Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene. |
|---|---|
| Environmental precautions : | If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for : containment and cleaning up | Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities. |

SECTION 7. HANDLING AND STORAGE

| Advice on protection against fire and explosion | : | None known. |
|---|---|--|
| Advice on safe handling | : | For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use. |
| Conditions for safe storage | : | Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light. |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type | Control parame- | Basis |
|---|---------|------------|-------------------------|------------------------|
| Internet: lubricants.petro-canada.com/sds | | | Page: 3 / 10 | |
| Trademarks are owned or used under license. | | | Petro-Canada Lubricants | is a HF Sinclair brand |

ENDURATEX TM/MC WG 680

000003000463

Version 2.6

Revision Date 2022/07/11

Print Date 2022/07/11

| | | (Form of | ters / Permissible | |
|-----------------------------------|------------|---------------|--------------------|-----------|
| | | exposure) | concentration | |
| Residual oils (petroleum), sol- | 64741-95-3 | TWA (Inhal- | 5 mg/m3 | ACGIH |
| vent deasphalted; Baseoil — | | able particu- | | |
| unspecified | | late matter) | | |
| Distillates (petroleum), solvent- | 64742-65-0 | TWA (Inhal- | 5 mg/m3 | ACGIH |
| dewaxed heavy paraffinic; | | able particu- | | |
| Baseoil — unspecified | | late matter) | | |
| | | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | NIOSH REL |
| | | ST (Mist) | 10 mg/m3 | NIOSH REL |
| Distillates (petroleum), hy- | 64742-54-7 | TWA (Inhal- | 5 mg/m3 | ACGIH |
| drotreated heavy paraffinic; | | able particu- | | |
| Baseoil — unspecified | | late matter) | | |
| | | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | NIOSH REL |
| | | ST (Mist) | 10 mg/m3 | NIOSH REL |
| Lubricating oils (petroleum), | 72623-85-9 | TWA (Inhal- | 5 mg/m3 | ACGIH |
| C20-50, hydrotreated neutral | | able particu- | | |
| oil-based, high-viscosity; | | late matter) | | |
| Baseoil — unspecified | | , | | |
| i. | | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | NIOSH REL |
| | | ST (Mist) | 10 mg/m3 | NIOSH REL |

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

| · · · · · · · · · · · · · · · · · · · | | | |
|---------------------------------------|---|---|--|
| Respiratory protection | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. | |
| Filter type | : | organic vapour filter | |
| Hand protection Material | : | neoprene, nitrile, polyvinyl alcohol (PVA), Viton®. | |
| Remarks | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. | |
| Eye protection | : | Wear face-shield and protective suit for abnormal processing problems. | |
| Skin and body protection | : | Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place. | |



ENDURATEX TM/MC WG 680



000003000463

| Version 2.6 | | Revision Date 2022/07/11 | Print Date 2022/07/11 |
|---------------------|---|--|-----------------------|
| Protective measures | : | Wash contaminated clothing before re- | -use. |
| Hygiene measures | : | Remove and wash contaminated cloth ing the inside, before re-use. Wash face, hands and any exposed sk handling. | |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | : | viscous liquid |
|---|---|---|
| Colour | : | Dark greenish amber |
| Odour | : | Mild petroleum oil like. |
| Odour Threshold | : | No data available |
| рН | : | No data available |
| Pour point Boiling point/boiling range | : | 0 °C (32 °F) No data available |
| Flash point | : | 313 °C (595 °F) Method: Cleveland open cup |
| Fire Point | : | 339 °C (642 °F) |
| Evaporation rate | : | No data available |
| Flammability | : | Low fire hazard. This material must be heated before ignition will occur. |
| Auto-Ignition Temperature | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | 0.911 kg/l (15 °C / 59 °F) |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Partition coefficient: n- octanol/water | : | No data available |

ENDURATEX TM/MC WG 680



000003000463

| Version 2.6 | Revision Date 2022/07/11 | Print Date 2022/07/11 |
|-----------------------------------|--|-----------------------|
| Viscosity Viscosity, kinematic | : 669.4 cSt (40 °C / 104 °F) | |
| | 36.5 cSt (100 °C / 212 °F) | |
| Explosive properties | : Do not pressurize, cut, weld, braz pose containers to heat or source | |

SECTION 10. STABILITY AND REACTIVITY

| l | Reactivity | : | Stable at normal ambient temperature and pressure. |
|---|---|---|---|
| (| Chemical stability | : | Stable under normal conditions. |
| | Possibility of hazardous reac- tions | : | Hazardous polymerisation does not occur. Stable under normal conditions. |
| (| Conditions to avoid | : | No data available |
| I | Incompatible materials | : | Reactive with oxidising agents, acids, alkalis and reducing agents. |
| | Hazardous decomposition products | : | May release COx, smoke and irritating vapours when heated to decomposition. |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| Eye contact |
|--------------|
| Ingestion |
| Inhalation |
| Skin contact |

Acute toxicity

| Product: | | |
|---|---------------|---|
| Acute oral toxicity | : | Remarks: No data available |
| Acute inhalation toxicity | : | Remarks: No data available |
| Acute dermal toxicity | : | Remarks: No data available |
| Components: | | |
| Distillates (petroleum), solve Acute oral toxicity | | -dewaxed heavy paraffinic; Baseoil — unspecified: LD50 (Rat): > 5,000 mg/kg, |
| | : | |
| Acute oral toxicity Acute dermal toxicity | : : otr | LD50 (Rat): > 5,000 mg/kg, |

ENDURATEX TM/MC WG 680

000003000463

| Version 2.6 | Revision Date 2022/07/11 | Print Date 2022/07/11 |
|----------------------------|--|-----------------------|
| | | |
| Baseoil — unspecified: | n), C20-50, hydrotreated neutral oil-ba | ised, high-viscosity; |
| Acute oral toxicity | : LD50 (Rat): > 5,000 mg/kg, | |
| Acute inhalation toxicity | : LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist | |
| Acute dermal toxicity | : LD50 (Rabbit): > 2,000 mg/kg, | |
| Skin corrosion/irritation | | |
| Product: | | |
| Remarks | : No data available | |
| Serious eye damage/eye ir | ritation | |
| Product: | | |
| Remarks | : No data available | |
| Respiratory or skin sensit | isation | |
| No data available | | |
| Germ cell mutagenicity | | |
| No data available | | |
| Carcinogenicity | | |
| No data available | | |
| Reproductive toxicity | | |
| No data available | | |
| STOT - single exposure | | |
| No data available | | |
| STOT - repeated exposure | | |
| No data available | | |
| | | |

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

| <u>Product:</u> Toxicity to fish | : | Remarks: No data available |
|---|---|----------------------------|
| Toxicity to daphnia and other aquatic invertebrates | : | Remarks: No data available |
| Toxicity to algae/aquatic plants | : | Remarks: No data available |
| Toxicity to microorganisms | : | Remarks: No data available |



ENDURATEX TM/MC WG 680

000003000463

Version 2.6

Revision Date 2022/07/11



Print Date 2022/07/11

Persistence and degradability Product: : Remarks: No data available Biodegradability **Bioaccumulative potential** No data available Mobility in soil No data available Other adverse effects No data available **SECTION 13. DISPOSAL CONSIDERATIONS Disposal methods** Waste from residues The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65 This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include: 71-43-2 benzene The components of this product are reported in the following inventories: DSL

On the inventory, or in compliance with the inventory :

Waste must be classified and labelled prior to recycling or

Dispose of product residue in accordance with the instructions

Send to a licensed waste management company.

of the person responsible for waste disposal.

ENDURATEX TM/MC WG 680



000003000463

| Version 2.6 | Revision Date 2022/07/11 | Print Date 2022/07/11 |
|-------------|---|-----------------------|
| TSCA | : All chemical substances in this proc TSCA Inventory or are in compliance exemption. | |
| IECSC | : On the inventory, or in compliance | with the inventory |

SECTION 16. OTHER INFORMATION

Further information NFPA 704: Health Flammability Health Instability Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

| ACGIH NIOSH REL | | USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits |
|--------------------|---|---|
| OSHA PO | | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| NIOSH REL / ST | : | STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday |
| OSHA P0 / TWA | : | 8-hour time weighted average |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification

ENDURATEX TM/MC WG 680

000003000463

Version 2.6

Revision Date 2022/07/11

System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

| For Copy of SDS | : | Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565 |
|------------------------------|---|--|
| Prepared by | : | Product Safety: +1 905-491-0565 |
| Revision Date Date format | : | 2022/07/11 yyyy/mm/dd |

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/07/11