PRECISION [™] SYNTHETIC EP00



000003001028

Version 2.8

Revision Date 2022/08/09

SECTION 1. IDENTIFICATION

Product name	:	PRECISION [™] SYNTHETIC EP00
Product code	:	PS00P17, PS00KGL, PS00, PS00DRL
Manufacturer or supplier's of Telephone		ails Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555
Emergency telephone numl Emergency telephone num- ber		CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).

Recommended use of the chemical and restrictions on use		
Recommended use	:	Precision Synthetic EP00 is a multi-service industrial and au- tomotive, high temperature synthetic EP grease. It is recom- mended for the following applications: The lubrication of all makes of truck trailer wheel-end bearings designed to use oil

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

and leaky gearcases subjected to high temperatures.

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

PRECISION [™] SYNTHETIC EP00



Version 2.8

Revision Date 2022/08/09

Print Date 2022/08/09

0......

Components		
Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50, hy- drotreated neutral oil-based; Baseoil — unspecified	72623-87-1	10 - 20
Residual oils (petroleum), solvent- dewaxed; Baseoil — unspecified	64742-62-7	5 - 10
Benzenamine, N-phenyl-, reaction prod- ucts with 2,4,4-trimethylpentene	68411-46-1	1 - 5
reaction mass of isomers of: C7-9-alkyl 3- (3,5-di-tert-butyl-4- hydroxyphenyl)propionate	125643-61-0	1 - 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

	Suitable extinguishing media	:	Use extinguishing measures that are appropriate to lo cumstances and the surrounding environment.	ocal cir-
	Unsuitable extinguishing media	:	No information available.	
	Specific hazards during fire-	:	Cool closed containers exposed to fire with water spr	ay.
Interr	net: lubricants.petro-canada.com/sc	ds		Page: 2 / 1



PRECISION [™] SYNTHETIC EP00



Version 2.8		Revision Date 2022/08/09	Print Date 2022/08/09
fighting			
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitroge oxides (SOx), phosphorus oxides (H2S), alkyl mercaptans, sulfides, pours as products of incomplete co	(POx), hydrogen sulphide smoke and irritating va-
Further information	:	Prevent fire extinguishing water from water or the ground water system.	5

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.



PRECISION [™] SYNTHETIC EP00



Version 2.8

Print Date 2022/08/09

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-87-1	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Residual oils (petroleum), sol- vent-dewaxed; Baseoil — un- specified	64742-62-7	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

	••••	
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection		
Hand protection		
Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection		Wear face-shield and protective suit for abnormal processing
	•	problems.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Protective measures	:	Wash contaminated clothing before re-use.
11		Device a set of the strategies of the balance of the set of the se
Hygiene measures	:	Remove and wash contaminated clothing and gloves, includ- ing the inside, before re-use.



PRECISION [™] SYNTHETIC EP00



Print Date 2022/08/09

000003001028

Version 2.8

		Revision Date 2022/06/09 Finit Date 2022/06/09
		Wash face, hands and any exposed skin thoroughly after handling.
ECTION 9. PHYSICAL AND CHE	EMI	CAL PROPERTIES
Appearance	:	Smooth, stringy, semi-fluid.
Colour	:	gold
Odour	:	Mild grease like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-33 °C (-27 °F)Base Fluid Blend
Boiling point/boiling range	:	No data available
Flash point	:	263 °C (505 °F) Method: Cleveland open cup Base Fluid Blend
Fire Point	:	291 °C (556 °F) Base Fluid Blend
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8817 kg/l (15 °C / 59 °F)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity Viscosity kinematic		456 cSt (40 °C / 104 °E)

Revision Date 2022/08/09

Viscosity, kinematic : 456 cSt (40 °C / 104 °F) Base Fluid Blend

PRECISION [™] SYNTHETIC EP00



000003001028

Version 2.8	Revision Date 2022/08/09	Print Date 2022/08/09
	42.9 cSt (100 °C / 212 °F) Base Fluid Blend	
Explosive properties :	Do not pressurize, cut, weld, braze, so pose containers to heat or sources of it	

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents, acids, alkalis and reducing agents.
Hazardous decomposition products	:	May release COx, NOx, SOx, POx, H2S, KOx, SbOx, sulfides, alkyl mercaptans, diphenylamine, alkenes, asphyxiants, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact		
Acute toxicity		
Product:		
Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available
<u>Components:</u> Lubricating oils (petroleum) fied:	, C	20-50, hydrotreated neutral oil-based; Baseoil — unspeci-
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,
Residual oils (petroleum), se Acute oral toxicity		ent-dewaxed; Baseoil — unspecified: LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist

PRECISION [™] SYNTHETIC EP00

000003001028

Version 2.8	Revision Date 2022/08/09	Print Date 2022/08/09
Acute dermal toxicity	: LD50 (Rabbit): > 3,000 mg/kg,	
Skin corrosion/irritation		
Skin corrosion/irritation		
Product:		
Remarks	: No data available	
Serious eye damage/eye i	rritation	
Product:		
Remarks	: No data available	
Respiratory or skin sensi	tisation	
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure	9	

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
u /·		ent-dewaxed; Baseoil — unspecified :
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other	:	EC50 (Daphnia (water flea)): > 100 mg/l

Page: 7 / 10 Petro-Canada Lubricants is a HF Sinclair brand



PRECISION [™] SYNTHETIC EP00



000003001028

Version 2.8	Revision Date 2022/08/09	Print Date 2022/08/09
aquatic invertebrates	Exposure time: 48 h	
Toxicity to algae/aquatic : plants	EC50 (algae): > 100 mg/l Exposure time: 72 h	
Persistence and degradability		
Product: Biodegradability :	Remarks: No data available	
Bioaccumulative potential No data available		
Mobility in soil No data available		
Other adverse effects		
No data available		
SECTION 13. DISPOSAL CONSIDE	RATIONS	

Disposal methods

Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal.
	Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to


PRECISION [™] SYNTHETIC EP00

000003001028

~ ~	
PETRO CANADA	

Version 2.8		Revision Date 2022/08/09	Print Date 2022/08/09
	naphthalene methanol	www.P65Warnings.ca.gov. The cho 91-20- 67-56-	3
The component	ts of this produc	t are reported in the following inv	entories:
DSL	:	On the inventory, or in compliance	with the inventory
TSCA	:	All chemical substances in this proc TSCA Inventory or are in compliance exemption.	
IECSC	:	On the inventory, or in compliance	with the inventory

SECTION 16. OTHER INFORMATION



Full text of other abbreviations

	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits
:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
:	8-hour, time-weighted average
:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
	8-hour time weighted average 8-hour time weighted average
	: : : : : : : : : : : : : : : : : : : :

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of

PRECISION [™] SYNTHETIC EP00

000003001028

Version 2.8

Revision Date 2022/08/09

the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic

Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globallv Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent. Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund

Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/08/09 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/08/09