# PURITY <sup>™</sup> FG2 CLEAR

### 000003001208

Version 2.7

Revision Date 2022/07/11



#### Print Date 2022/07/11

### **SECTION 1. IDENTIFICATION**

Product name :	PURITY ™ FG2 CLEAR
Product code :	PFGCL2P17, PFGCL2KGL, PFGCL2DRL, PFGCL2, PFGCL2C30
Manufacturer or supplier's det Telephone :	ails Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555
Emergency telephone number Emergency telephone num- : ber	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the cher	mical and restrictions on use
Recommended use :	PURITY FG Food Machinery Grease is a food grade grease.
	NSF H1 Registered.
	All components comply with FDA 21 CFR 178.3570 "Lubri- cants with Incidental Food Contact". It is intended for applica- tion on industrial and food equipment. It should not be added directly to the food product.
Prepared by :	Product Safety: +1 905-491-0565
	TION

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

### Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

# PURITY <sup>™</sup> FG2 CLEAR

### 000003001208

Version 2.7

Revision Date 2022/07/11

Print Date 2022/07/11

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)			
White mineral oil (petroleum)	8042-47-5	30 - 100			
Actual concentration is withheld as a trade secret					

#### SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxides (NOx), phosphorus oxides (POx), smoke and irritating vapours as products of

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.



# PURITY <sup>™</sup> FG2 CLEAR

### 000003001208



Version 2.7		Revision Date 2022/07/11	Print Date 2022/07/11
		incomplete combustion.	
Further information	:	Prevent fire extinguishing water from c water or the ground water system.	ontaminating surface

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

#### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
Internet: lubricants.petro-canada.com/sds	3			Page: 3 / 10
Trademarks are owned or used under license.			Petro-Canada Lubricants	is a HF Sinclair brand

# PURITY <sup>™</sup> FG2 CLEAR

### 000003001208

Version 2.7

#### Revision Date 2022/07/11

Print Date 2022/07/11

		(Form of exposure)	ters / Permissible concentration	
White mineral oil (petroleum)	8042-47-5	TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton <sup>®</sup> .
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Protective measures	:	Wash contaminated clothing before re-use.
Hygiene measures	:	Remove and wash contaminated clothing and gloves, includ- ing the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Semi-solid.
Colour	:	Clear.
Odour	:	Bland.
Odour Threshold	:	No data available



# PURITY <sup>™</sup> FG2 CLEAR

# 000003001208



Version 2.7		Revision Date 2022/07/11	Print Date 2022/07/11
рН	:	No data available	
Pour point	:	-12 °C (10 °F)Base Fluid Blend	
Boiling point/boiling range	:	No data available	
Flash point	:	245 °C (473 °F) Method: Cleveland open cup Base Fluid Blend	
Fire Point	:	267 °C (513 °F) Base Fluid Blend	
Evaporation rate	:	No data available	
Flammability	:	Low fire hazard. This material m will occur.	ust be heated before ignition
Auto-Ignition Temperature	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	0.8856 kg/l (15 °C / 59 °F)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	185 cSt (40 °C / 104 °F) Base Fluid Blend	
		18 cSt (100 °C / 212 °F) Base Fluid Blend	
Explosive properties	:	Do not pressurize, cut, weld, bra pose containers to heat or sourc	

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available

# PURITY <sup>™</sup> FG2 CLEAR



### 000003001208

Version 2.7		Revision Date 2022/07/11	Print Date 2022/07/11
Incompatible materials	:	Reactive with oxidising agents.	
Hazardous decomposition products	:	May release COx, smoke and irri to decomposition.	tating vapours when heated

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact		
Acute toxicity		
Product:		
Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Assessment: The substance or mixture has no acute dermal toxicity Remarks: No data available

#### Skin corrosion/irritation

#### Product:

#### Serious eye damage/eye irritation

#### Product:

Remarks

Respiratory or skin sensitisation

: No data available

No data available

# Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

# PURITY <sup>™</sup> FG2 CLEAR

### 000003001208

Version 2.7



Print Date 2022/07/11

### SECTION 12. ECOLOGICAL INFORMATION

	Ecotoxicity			
	<u>Product:</u> Toxicity to fish	:	Remarks: No data available	
	Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available	
	Toxicity to algae/aquatic plants	:	Remarks: No data available	
	Toxicity to microorganisms	:	Remarks: No data available	
	Persistence and degradabili	ty		
	Product:			
	Biodegradability	:	Remarks: No data available	
	<b>Bioaccumulative potential</b> No data available			
	Mobility in soil			
	No data available			
	Other adverse effects No data available			
-			ATIONS	 

#### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Offer surplus and non-recyclable solutions to a licensed disposal company.</li> <li>Waste must be classified and labelled prior to recycling or disposal.</li> <li>Send to a licensed waste management company.</li> <li>Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.</li> </ul>

### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### **National Regulations**

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

# PURITY <sup>™</sup> FG2 CLEAR

### 000003001208

Version 2.7

Revision Date 2022/07/11



Print Date 2022/07/11


### 49 CFR

Not regulated as a dangerous good

### **SECTION 15. REGULATORY INFORMATION**

California Prop. 65		in any chemicals known to State r, birth defects, or any other re- nformation go to
The components of this produ	reported in the followi	ing inventories:
DSL	he inventory, or in comp	liance with the inventory
TSCA		his product are either listed on the mpliance with a TSCA Inventory
IECSC	he inventory, or in comp	liance with the inventory
NZIoC	he inventory, or in comp	liance with the inventory
	IO: HSR002605, Lubrica 2020	ants (Low Hazard) Group Stand-

#### **SECTION 16. OTHER INFORMATION**





HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

# PURITY <sup>™</sup> FG2 CLEAR

### 000003001208



Version 2.7		Revision Date 2022/07/11	Print Date 2022/07/11
		values)	
OSHA Z-1	:	USA. Occupational Exposure Lim its for Air Contaminants	its (OSHA) - Table Z-1 Lim-
ACGIH / TWA	:	8-hour, time-weighted average	
NIOSH REL / TWA	:	Time-weighted average concentra workday during a 40-hour workwe	
NIOSH REL / ST	:	STEL - 15-minute TWA exposure at any time during a workday	that should not be exceeded
OSHA P0 / TWA	:	8-hour time weighted average	
OSHA Z-1 / TWA	:	8-hour time weighted average	

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response: EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/07/11 yyyy/mm/dd

PURITY <sup>™</sup> FG2 CLEAR

### 000003001208

Version 2.7

#### Revision Date 2022/07/11

PETRO-CANADA

Print Date 2022/07/11

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN