DURATAC [™] CHAIN OIL 150



000003001363

Version 3.5

Revision Date 2022/07/26

Print Date 2022/07/26

SECTION 1. IDENTIFICATION

Product name :	:	DURATAC ™ CHAIN OIL 150			
Product code :	:	DTAC150CBE, DTAC150IBC, DTAC150P20, DTAC150DRM, DTAC150DCT, DTAC150C16, DTAC150, DTAC150BLK			
Manufacturer or supplier's de	eta	ils			
		Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States			
Telephone :	:	1-214-871-3555			
Emergency telephone number					
Emergency telephone : number	•	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).			
Recommended use of the che	en	nical and restrictions on use			
Recommended use :	:	Duratac Chain Oils are used to lubricate chains, guide bars, journal bearings and sprockets of modern high-speed chain saws. They are used as "once through" lubricating oils where a tackifier is beneficial.			
Prepared by :	:	Product Safety: +1 905-491-0565			

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
ΝΤΡ	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

DURATAC [™] CHAIN OIL 150



000003001363

Version 3.5

Revision Date 2022/07/26

Print Date 2022/07/26

Components

Chemical name	CAS-No.	Concentration (% w/w)
Residual oils (petroleum), solvent- dewaxed; Baseoil — unspecified	64742-62-7	30 - 50
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified	64742-70-7	30 - 50
Residual oils (petroleum), solvent deasphalted; Baseoil — unspecified	64741-95-3	20 - 30
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	10 - 20
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	1 - 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.

DURATAC [™] CHAIN OIL 150



000003001363

Version 3.5		Revision Date 2022/07/26	Print Date 2022/07/26
Hazardous combustion products	:	Carbon oxides (CO, CO2), nitroge oxides (SOx), phosphorus oxides (H2S), smoke and irritating vapou combustion.	(POx), hydrogen sulphide
Further information	:	Prevent fire extinguishing water fr water or the ground water system	
SECTION 6. ACCIDENTAL RELI	EAS	E MEASURES	
Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment Ensure adequate ventilation. Evacuate personnel to safe areas Material can create slippery cond Mark the contaminated area with unauthorized personnel. Only qualified personnel equipped equipment may intervene.	s. itions. signs and prevent access to
Environmental precautions	:	If the product contaminates rivers respective authorities.	and lakes or drains inform
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillag Remove all sources of ignition. Soak up with inert absorbent mate Non-sparking tools should be use Ensure adequate ventilation. Contact the proper local authorities	erial. ed.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

DURATAC [™] CHAIN OIL 150



000003001363

Version 3.5

Revision Date 2022/07/26

Print Date 2022/07/26

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified	64742-62-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified	64742-70-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Residual oils (petroleum), solvent deasphalted; Baseoil — unspecified	64741-95-3	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

:

Respiratory protection: Use respiratory protection unless adequate local exhaust
ventilation is provided or exposure assessment demonstrates
that exposures are within recommended exposure guidelines.
Respirator selection must be based on known or anticipated
exposure levels, the hazards of the product and the safe
working limits of the selected respirator.

DURATAC [™] CHAIN OIL 150



000003001363

Version 3.5		Revision Date 2022/07/26	Print Date 2022/07/26
Filter type	:	organic vapour filter	
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (P	√A), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves approved standard should be worn at chemical products if a risk assessmer necessary.	all times when handling
Eye protection	:	Wear face-shield and protective suit for problems.	or abnormal processing
Skin and body protection	:	Choose body protection in relation to concentration and amount of dangero the specific work-place.	
Protective measures	:	Wash contaminated clothing before re	}-use.
Hygiene measures	:	Remove and wash contaminated cloth including the inside, before re-use. Wash face, hands and any exposed s handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Opaque, viscous liquid.
Colour	:	dark red
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-30 °C (-22 °F) No data available
Flash point	:	210 °C (410 °F) Method: Cleveland open cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower rnet: lubricants.petro-canada.com/se		No data available Page: 5 / Petro Canada Lubricante is a HE Sinclair b

DURATAC [™] CHAIN OIL 150

000003001363



Version 3.5	Revision Date 2022/07/26	Print Date 2022/07/26
flammability limit		
Vapour pressure Relative vapour density	: No data available : No data available	
Relative density	: No data available	
Density	: 0.8800 kg/l (15 °C / 59 °F)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity Viscosity, kinematic	: 150.0 cSt (40 °C / 104 °F)	
Explosive properties	 16.8 cSt (100 °C / 212 °F) Do not pressurize, cut, weld, braze expose containers to heat or source 	-

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents and reducing agents.
Hazardous decomposition products	:	May release COx, NOx, SOx, POx, H2S, asphyxiants, hydrocarbons, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	
Eve contact	

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

DURATAC [™] CHAIN OIL 150



000003001363

sion 3.5		Revision Date 2022/07/26	Print Date 2022/0
Components:			
	solv	ent-dewaxed; Baseoil — unspecifi	ed:
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity		LC50 (Rat): > 5.53 mg/l	
	-	Exposure time: 4 h	
		Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 3,000 mg/kg,	
Distillates (petroleum), so	lvent	-dewaxed heavy paraffinic; Baseoi	il — unspecified:
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Distillates (petroleum), hv	drotr	eated heavy paraffinic; Baseoil —	unspecified:
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute dermal toxicity		LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation			
Product:			
	:	No data available	
Remarks Serious eye damage/eye i	: rritati		
Remarks Serious eye damage/eye i Product:	: rritati	ion	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks Respiratory or skin sensi t	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks Respiratory or skin sensit No data available	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks Respiratory or skin sensit No data available Germ cell mutagenicity	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks Respiratory or skin sensit No data available Germ cell mutagenicity No data available	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks Respiratory or skin sensit No data available Germ cell mutagenicity No data available Carcinogenicity	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks Respiratory or skin sensit No data available Germ cell mutagenicity No data available Carcinogenicity No data available	:	ion No data available	
Remarks Serious eye damage/eye i <u>Product:</u> Remarks Respiratory or skin sensit No data available Germ cell mutagenicity No data available Carcinogenicity No data available	:	ion No data available	
Respiratory or skin sensit No data available Germ cell mutagenicity No data available Carcinogenicity No data available Reproductive toxicity No data available	:	ion No data available	
Remarks Serious eye damage/eye i Product: Remarks Respiratory or skin sensit No data available Germ cell mutagenicity No data available Carcinogenicity No data available Reproductive toxicity No data available STOT - single exposure	:	ion No data available	
Remarks Serious eye damage/eye i Product: Remarks Respiratory or skin sensit No data available Germ cell mutagenicity No data available Carcinogenicity No data available Reproductive toxicity	: tisatio	ion No data available	

DURATAC [™] CHAIN OIL 150

000003001363

Version 3.5



Print Date 2022/07/26

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity		
<u>Product:</u> Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
<u>Components:</u> Residual oils (petroleum), se Toxicity to fish	olvo :	ent-dewaxed; Baseoil — unspecified : LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/l Exposure time: 72 h
Persistence and degradabil	ity	
<u>Product:</u> Biodegradability	:	Remarks: No data available
Bioaccumulative potential No data available		
Mobility in soil No data available		
Other adverse effects No data available		
		ATIONS

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

DURATAC [™] CHAIN OIL 150

000003001363

Version 3.5

Revision Date 2022/07/26

Print Date 2022/07/26

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65 benzene	This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include: 71-43-2		
The components of this product are reported in the following inventories:			
DSL :	On the inventory, or in compliance with the inventory		
TSCA :	All chemical substances in this product are either listed TSCA Inventory or are in compliance with a TSCA Inversemption.		
EINECS :	On the inventory, or in compliance with the inventory		
IECSC :	On the inventory, or in compliance with the inventory		

SECTION 16. OTHER INFORMATION

Further information



DURATAC [™] CHAIN OIL 150

000003001363


Version 3.5

Revision Date 2022/07/26

1

1

0



Full text of other abbreviations

ACGIH NIOSH REL		USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA		8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response. Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect

DURATAC [™] CHAIN OIL 150



000003001363

Version 3.5

Revision Date 2022/07/26

Print Date 2022/07/26

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/07/26 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN