PETROGLIDE TM/MC 100

#### 000003000413

Version 3.3

Revision Date 2022/08/15



Print Date 2022/08/15

#### **SECTION 1. IDENTIFICATION**

Product name :				
Synonyms :	PETROGLIDE PREMIUM SAW GUIDE OIL 100			
Product code :	GLID100CBE, GLID100IBC, GLID100DRM, GLID100DCT, GLID100, GLID100BLK			
Manufacturer or supplier's def Telephone :	ails Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555			
Emergency telephone number	r			
Emergency telephone : number	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).			
Recommended use of the chemical and restrictions on use				
Recommended use :	Petroglide oils are designed to lubricate saw blades of multi- blade, gang saws and edgers.			
Prepared by :	Product Safety: +1 905-491-0565			

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)			
Skin sensitisation	:	Category 1	
GHS label elements Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	May cause an allergic skin reaction.	
Precautionary statements	:	<ul> <li>Prevention:</li> <li>Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.</li> <li>Contaminated work clothing must not be allowed out of the workplace.</li> <li>Wear protective gloves.</li> <li>Response:</li> <li>IF ON SKIN: Wash with plenty of soap and water.</li> <li>If skin irritation or rash occurs: Get medical advice/ attention.</li> <li>Wash contaminated clothing before reuse.</li> <li>Disposal:</li> </ul>	

## PETROGLIDE TM/MC 100

#### 000003000413



000003000413		
Version 3.3	Revision Date 2022/08/15	Print Date 2022/08/15
	Dispose of contents/ container to an ap plant.	proved waste disposal
<b>Other hazards</b> None known.		
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.	
OSHA	No component of this product present at levels greater the equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	No component of this product present a equal to 0.1% is identified as a known o by NTP.	

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

•		
Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50,	72623-87-1	50 - 70
hydrotreated neutral oil-based; Baseoil —		
unspecified		
Paraffin oils (petroleum), catalytic	64742-70-7	30 - 50
dewaxed heavy; Baseoil — unspecified		
Residual oils (petroleum), solvent-	64742-62-7	30 - 50
dewaxed; Baseoil — unspecified		
Distillates (petroleum), hydrotreated heavy	64742-54-7	1 - 5
paraffinic; Baseoil — unspecified		
2,5-bis(octyldithio)-1,3,4-thiadiazole	13539-13-4	0.1 - 1
		•

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

# PETROGLIDE TM/MC 100

#### 000003000413



Version 3.3	Revision Date 2022/08/15	Print Date 2022/08/15
	Obtain medical attention.	
If swallowed	<ul> <li>Rinse mouth with water.</li> <li>DO NOT induce vomiting unless directed to do so by a physician or poison control center.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>Seek medical advice.</li> </ul>	
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himse	elf.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	Carbon oxides (CO, CO2), sulphur oxides (SOx), sulphur compounds (H2S), silicon oxides (SiOx), hydrocarbons, metal oxides, alkyl mercaptans, sulfides, formaldehyde, smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

#### SECTION 7. HANDLING AND STORAGE

# PETROGLIDE TM/MC 100

#### 000003000413



Version 3.3		Revision Date 2022/08/15	Print Date 2022/08/15
Advice on protection against fire and explosion	: N	lone known.	
Advice on safe handling	<ul> <li>For personal protection see section 8.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>In case of insufficient ventilation, wear suitable respiratory equipment.</li> <li>Avoid contact with skin, eyes and clothing.</li> <li>Do not ingest.</li> <li>Keep away from heat and sources of ignition.</li> <li>Keep container closed when not in use.</li> </ul>		suitable respiratory ng. nition.
Conditions for safe storage	( 	Store in original container. Containers which are opened must be of ept upright to prevent leakage. Geep in a dry, cool and well-ventilated p Geep in properly labelled containers. To maintain product quality, do not stor unlight.	blace.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified	72623-87-1	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified	64742-70-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified	64742-62-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

# PETROGLIDE TM/MC 100



#### 000003000413

Varcian	22
Version	3.3

ersion 3.3	Revision Date 2022/08/15	Print Date	2022/08/15		
	TWA (Mist) TWA (Mist) TWA (Mist) ST (Mist)	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3	OSHA Z-1 OSHA P0 NIOSH REL NIOSH REL		
Engineering measures	No special ventilation require should be sufficient to contro contaminants.	ments. Good general	ventilation		
Personal protective equipment Respiratory protection :	t Use respiratory protection un ventilation is provided or exp that exposures are within rec Respirator selection must be exposure levels, the hazards working limits of the selected	osure assessment der ommended exposure based on known or ar of the product and the	monstrates guidelines. nticipated		
Filter type :	organic vapour filter	organic vapour filter			
Hand protection Material :	neoprene, nitrile, polyvinyl al	cohol (PVA), Viton <sup>®</sup> .			
Remarks :	Chemical-resistant, impervio approved standard should be chemical products if a risk as necessary.	e worn at all times whe	en handling		
Eye protection :	Wear face-shield and protect problems.	ive suit for abnormal p	processing		
Skin and body protection :	Choose body protection in re concentration and amount of the specific work-place.				
Protective measures :	Wash contaminated clothing	before re-use.			
Hygiene measures :	Remove and wash contamina including the inside, before re Wash face, hands and any e handling.	e-use.			

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	dark amber
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-36 °C (-33 °F) No data available

# PETROGLIDE TM/MC 100

#### 000003000413



Version 3.3		Revision Date 2022/08/15	Print Date 2022/08/15
Flash point	:	277 °C (531 °F) Method: Cleveland open cup	
Fire Point	:	No data available	
Evaporation rate	:	No data available	
Flammability	:	Low fire hazard. This material must b will occur.	e heated before ignition
Auto-Ignition Temperature	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	0.8593 kg/l (15 °C / 59 °F)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	108.1 cSt (40 °C / 104 °F)	
		14.1 cSt (100 °C / 212 °F)	
Explosive properties	:	Do not pressurize, cut, weld, braze, s expose containers to heat or sources	

## SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents, acids, alkalis and reducing agents.
Hazardous decomposition products	:	May release COx, SOx, H2S, sulfides, hydrocarbons, alkyl mercaptans, formaldehyde, methacrylate monomers, asphyxiants, smoke and irritating vapours when heated to decomposition.

PETROGLIDE TM/MC 100

#### 000003000413

Version 3.3

Revision Date 2022/08/15

PETRO-CANADA

Print Date 2022/08/15

#### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely rout	es of o	exposure
Eye contact Ingestion		
Inhalation		
Skin contact		
Acute toxicity		
Product:		
Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No data available
Acute dermal toxicity	:	Assessment: The substance or mixture has no acute dermal toxicity Remarks: No data available
Components:		
	m), C2	20-50, hydrotreated neutral oil-based; Baseoil —
unspecified: Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity		LC50 (Rat): > 5.2 mg/l
	•	Exposure time: 4 h
		Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,
Residual oils (petroleum),	, solve	ent-dewaxed; Baseoil — unspecified:
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 3,000 mg/kg,
Distillates (petroleum), hy Acute oral toxicity	vdrotre :	eated heavy paraffinic; Baseoil — unspecified: LD50 (Rat): > 5,000 mg/kg,
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,
Skin corrosion/irritation		
Product:		
Remarks	:	No data available
Serious eye damage/eye i	rritati	on
Product:		

#### Product:

## PETROGLIDE TM/MC 100

#### 000003000413

Version 3.3



Print Date 2022/08/15

## Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### **Reproductive toxicity**

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

#### Product:

Toxicity to fish	:	Remarks: No data available				
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available				
Toxicity to algae/aquatic plants	:	Remarks: No data available				
Toxicity to microorganisms	:	Remarks: No data available				
<u>Components:</u> Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified :						
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h				
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h				
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/l Exposure time: 72 h				
Persistence and degradability						
<u>Product:</u> Biodegradability	:	Remarks: No data available				

#### **Bioaccumulative potential**

No data available Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

## PETROGLIDE TM/MC 100

#### 000003000413

Version 3.3

Revision Date 2022/08/15



Print Date 2022/08/15

# Mobility in soil

No data available

## Other adverse effects

No data available

#### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

-			
Wast	e from residues	:	The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### **National Regulations**

49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

California Prop. 65	This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects of other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include:	or	
1-chloro-2,3-epc	oxypropane 106-89-8		
The components of this product are reported in the following inventories:			
DSL :	On the inventory, or in compliance with the inventory		
TSCA :	All chemical substances in this product are either listed o TSCA Inventory or are in compliance with a TSCA Invent exemption.		

## PETROGLIDE TM/MC 100

#### 000003000413

Version 3.3




Print Date 2022/08/15

#### **SECTION 16. OTHER INFORMATION**

#### Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH NIOSH REL		USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits
OSHA P0		USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA OSHA Z-1 / TWA		8-hour time weighted average 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50

## PETROGLIDE TM/MC 100

#### 000003000413

Version 3.3

#### Revision Date 2022/08/15

- Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test

population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/08/15 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/08/15