TURBOFL	Ο	тм/мс	EΡ	32
---------	---	-------	----	----

000003000997

Version 3.0

Revision Date 2022/05/30



Print Date 2022/05/30

SECTION 1. IDENTIFICATION

Product name	:	TURBOFLO TM/MC EP 32
Synonyms	:	RDF-9908
Product code	:	TFEP32IBC, TFEP32DRM, TFEP32, TFEP32BLK
Manufacturer or supplier's de Telephone		ails Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555
Emergency telephone numb Emergency telephone num- ber		CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the ch Recommended use		nical and restrictions on use Turboflo EP fluids are premium anti-wear lubricants designed for geared heavy duty turbines with common gear and bearing lubrication systems.
Prepared by	:	Product Safety: +1 905-491-0565
	• • •	TION

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accor 1910.1200)	rdan	ce with the OSHA Hazard Communication Standard (29 CFR
Reproductive toxicity	:	Category 2
GHS label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Suspected of damaging fertility or the unborn child.
Precautionary statements	:	 Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF exposed or concerned: Get medical advice/ attention. Storage: Store locked up.

TURBOFLO

000003000997

Version 3.0

JRBOFLO ^{TM/MC} EP 32		PETRO CANADA
0003000997		
rsion 3.0	Revision Date 2022/05/30	Print Date 2022/05/30
	Disposal: Dispose of contents/ container to a plant.	n approved waste disposal
Other hazards None known.		
IARC	No component of this product prese or equal to 0.1% is identified as pro firmed human carcinogen by IARC.	bable, possible or con-
OSHA	No component of this product prese equal to 0.1% is on OSHA's list of r	0

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50, hy- drotreated neutral oil-based; Baseoil — unspecified	72623-87-1	70 - 90
Lubricating oils (petroleum), C15-30, hy- drotreated neutral oil-based; Baseoil — unspecified	72623-86-0	20 - 30
Phenol, isopropylated, phosphate (3:1)	68937-41-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled :	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact :	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact :	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed : Internet: lubricants.petro-canada.com/sds	Rinse mouth with water. Page: 2 /



TURBOFLO ^{™/MC} EP 32

000003000997



Version 3.0		Revision Date 2022/05/30	Print Date 2022/05/30
		DO NOT induce vomiting unless direction or poison control center. Never give anything by mouth to an Seek medical advice.	
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion	None known.	
Advice on safe handling :	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area.	
ernet: lubricants.petro-canada.com/sds	Page: 3	1

TURBOFLO ^{™/MC} EP 32

000003000997



Version 3.0		Revision Date 2022/05/30	Print Date 2022/05/30
In case of insufficient ventilation, wear se equipment. Avoid contact with skin, eyes and clothin Do not ingest. Keep away from heat and sources of ign Keep container closed when not in use.		othing. f ignition.	
Conditions for safe storage	:	Store in original container. Containers which are opened must be kept upright to prevent leakage. Keep in a dry, cool and well-ventilate Keep in properly labelled containers To maintain product quality, do not so light.	ed place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

:

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-87-1	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-86-0	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

TURBOFLO TM/MC EP 32

000003000997



Version 3.0		Revision Date 2022/05/30	Print Date 2022/05/30
Filter type	:	organic vapour filter	
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PV	A), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves approved standard must be worn unles indicates that this is not necessary.	
Eye protection	:	Wear face-shield and protective suit.	
Skin and body protection	:	Choose body protection in relation to it tration and amount of dangerous subst cific work-place. Suitable protective clothing should be	ances, and to the spe-
Protective measures	:	Wash contaminated clothing before re-	-use.
Hygiene measures	:	Remove and wash contaminated cloth ing the inside, before re-use. Wash face, hands and any exposed sk handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	Pale, straw-yellow.
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-33 °C (-27 °F) No data available
Flash point	:	220 °C (428 °F) Method: Cleveland open cup
Fire Point	:	238 °C (460 °F)
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower	:	No data available
nternet: lubricants.petro-canada.com/s rademarks are owned or used under license.	as	/ Page: 5 Petro-Canada Lubricants is a HF Sinclair br

TURBOFLO ^{™/MC} EP 32

000003000997

	7
	7
PETROC	ANADA

000003000997		
Version 3.0	Revision Date 2022/05/30	Print Date 2022/05/30
flammability limit		
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: 0.86 kg/l (15 °C / 59 °F)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity Viscosity, kinematic	: 34.2 cSt (40 °C / 104 °F)	
	5.6 cSt (100 °C / 212 °F)	
Explosive properties	: Do not pressurize, cut, weld, braz pose containers to heat or source	

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents, acids, alkalis and reducing agents.
Hazardous decomposition products	:	May release COx, NOx, SOx, methacrylate monomers, phe- nols, smoke and irritating vapours when heated to decomposi- tion.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes	of	exposure
Eye contact Ingestion Inhalation Skin contact		
Acute toxicity		
Product:		
Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Assessment: The substance or mixture has no acute inhala- tion toxicity Remarks: No data available
Acute dermal toxicity	:	Assessment: The substance or mixture has no acute dermal

TURBOFLO ^{™/MC} EP 32

000003000997

Version 3.0

PETRO-CANADA

rsion 3.0	Revision Date 2022/05/30	Print Date 2022/05/30
	toxicity Remarks: No data available	
Components:		
Lubricating oils (petroleum), fied:	C20-50, hydrotreated neutral oil-bas	ed; Baseoil — unspeci-
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
• • • •	C15-30, hydrotreated neutral oil-bas	sed; Baseoil — unspeci-
fied: Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation		
<u>Product:</u> Remarks	: No data available	
Serious eye damage/eye irrita	ation	
<u>Product:</u> Remarks	: No data available	
Respiratory or skin sensitisa	tion	
No data available		
Germ cell mutagenicity No data available		
Carcinogenicity No data available		
Reproductive toxicity		
No data available		
STOT - single exposure No data available		
STOT - repeated exposure No data available		

TURBOFLO TM/MC EP 32

000003000997

Version 3.0



Print Date 2022/05/30

SECTION 12. ECOLOGICAL INFORMATION

	Ecotoxicity			
	<u>Product:</u> Toxicity to fish	:	Remarks: No data available	
	Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available	
	Toxicity to algae/aquatic plants	:	Remarks: No data available	
	Toxicity to microorganisms	:	Remarks: No data available	
	Persistence and degradabili	ty		
	<u>Product:</u> Biodegradability	:	Remarks: No data available	
	Bioaccumulative potential No data available Mobility in soil No data available			
	Other adverse effects No data available			
=/			ATIONS	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

TURBOFLO TM/MC EP 32

000003000997

Version 3.0

Revision Date 2022/05/30



Print Date 2022/05/30

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65 ethyl acrylate	This product contains chemical(s) known to the State of Cali- fornia to cause cancer. For more information go to www.P65Warnings.ca.gov. The chemicals include: 140-88-5
	ct are reported in the following inventories:
IECSC :	On the inventory, or in compliance with the inventory
:	The Environmental Protection Agency prohibits processing and distribution of this chemical/product for any use other than: (1) in hydraulic fluids either for the aviation industry or to meet military specifications for safety and performance where no alternative chemical is available that meets U.S. Depart- ment of Defense specification requirements, (2) lubricants and greases, (3) new or replacement parts for automotive and aerospace industry, and the distribution in commerce of those parts to which PIP (3:1) has been added, (4) as an intermedi- ate in a closed system to produce cyanoacrylate adhesives, (5) in specialized engine filters for locomotive and marine ap- plications, (6) in adhesives and sealants before January 6, 2025, after which use in adhesives and sealants is prohibited, (7) for the recycling of PIP (3:1) containing plastic provided no new PIP (3:1) is added during the recycling process, (8) in articles and products made from recycled PIP (3:1) containing plastic provided no new PIP (3:1) is added during the recy- cling process or to the articles and products made from recy- cled plastic, and (9) in photographic printing articles and PIP (3:1) containing photographic printing articles until January 1, 2022. In addition, all persons are prohibited from releasing PIP (3:1) to water during manufacturing, processing and dis- tribution in commerce, and must follow all existing regulations and best practices to prevent the release of PIP (3:1) to water during the commercial use of PIP (3:1).
:	The Environmental Protection Agency (EPA) has identified
	 these additional hazards, not identified under OSHA/GHS hazards: Skin corrosion Skin Irritation Serious Eye Damage Skin Sensitization Reproductive Toxicity Specific Target Organ Toxicity

SECTION 16. OTHER INFORMATION

Further information


TURBOFLO ^{™/MC} EP 32

000003000997



Version 3.0





Full text of other abbreviations

ACGIH NIOSH REL OSHA P0	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / STEL	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA OSHA Z-1 / TWA	:	8-hour time weighted average 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New

TURBOFLO ^{™/MC} EP 32

000003000997

Version 3.0

Revision Date 2022/05/30

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/05/30 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/05/30