PURITY [™] FG WO WHITE MINERAL OIL 10



00003001229		
ersion 2.7	Revision Date 2022/08/16	Print Date 2022/08/16
CTION 1. IDENTIFICATION		
Product name	: PURITY [™] FG WO WHITE MINE	RAL OIL 10
Product code	: PFWO10P20, PFWO10IBC, PFW PFWO10BLK	/O10DRX, PFWO10,
Manufacturer or supplier's d Telephone	etails Petro-Canada America Lubricants 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States : 1-214-871-3555	
Emergency telephone numb	er	
Emergency telephone number	: CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult loo emergency number(s).	cal telephone directory for
Recommended use of the ch	nemical and restrictions on use	
Recommended use	: Purity FG WO White Mineral Oil 1 mineral oil intended for the food p	
	This product complies with FDA 2 Mineral Oil" and 21 CFR 178.362 food contact.	
Prepared by	: Product Safety: +1 905-491-0565	;

GHS classification in acco 1910.1200)	rdar	nce with the OSHA Hazard Communication Standard (29 CFR
Aspiration hazard	:	Category 1
GHS label elements		
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	May be fatal if swallowed and enters airways.
Precautionary statements	:	Response: IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting. Storage: Store locked up. Disposal: Dispose of contents/ container to an approved waste disposal plant.

PURITY [™] FG WO WHITE MINERAL OIL 10



000003001229		
Version 2.7	Revision Date 2022/08/16	Print Date 2022/08/16
Other hazards None known.		
IARC	No component of this product pres or equal to 0.1% is identified as pr confirmed human carcinogen by <i>l</i>	obable, possible or

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture :	
-----------------------	--

Components

OSHA

NTP

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	100
Actual concentration is withheld as a trade		

Substance

SECTION 4. FIRST AID MEASURES

If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	 Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	 Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.

PURITY [™] FG WO WHITE MINERAL OIL 10

000003001229

Version 2.7	Revision Date 2022/08/16	Print Date 2022/08/16

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the environment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Use only with adequate ventilation. Avoid contact with skin, eyes and clothing. Do not ingest. In case of insufficient ventilation, wear suitable respiratory equipment. Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.



PURITY [™] FG WO WHITE MINERAL OIL 10

000003001229



Version 2.7Revision Date 2022/08/16Print Date 2022/08/16Containers which are opened must be carefully resealed and
kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labelled containers.
To maintain product quality, do not store in heat or direct
sunlight.
Keep locked up or in an area accessible only to qualified or
authorised persons.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Engineering measures		ifficient to contro	ments. Good gene I worker exposure t	
Personal protective equipme	nt			
Respiratory protection	ventilation is that exposur Respirator se exposure lev	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapour filter		
Filter type	: organic vapo			
Hand protection Material	: neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .			
Remarks	approved sta	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.		
Eye protection	: Wear face-sl problems.	Wear face-shield and protective suit for abnormal processing problems.		
Skin and body protection		n and amount of	lation to its type, to dangerous substar	
Protective measures rnet: lubricants.petro-canada.com/so		minated clothing	before re-use.	Page: 4 / 10

PURITY [™] FG WO WHITE MINERAL OIL 10



000003001229		
Version 2.7	Revision Date 2022/08/16	Print Date 2022/08/16
Hygiene measures :	Remove and wash contaminated cloth including the inside, before re-use. Wash face, hands and any exposed sl	

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	Clear and bright
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-24 °C (-11 °F) No data available
Flash point	:	190 °C (374 °F) Method: Cleveland open cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
naminability limit		
Lower explosion limit / Lower flammability limit	:	No data available
Lower explosion limit / Lower		No data available No data available
Lower explosion limit / Lower flammability limit	:	
Lower explosion limit / Lower flammability limit Vapour pressure	:	No data available
Lower explosion limit / Lower flammability limit Vapour pressure Relative vapour density	::	No data available No data available
Lower explosion limit / Lower flammability limit Vapour pressure Relative vapour density Relative density	::	No data available No data available No data available
Lower explosion limit / Lower flammability limit Vapour pressure Relative vapour density Relative density Density	::	No data available No data available No data available
Lower explosion limit / Lower flammability limit Vapour pressure Relative vapour density Relative density Density Solubility(ies)	::	No data available No data available No data available 0.846 kg/l (15 °C / 59 °F)

000003001229

PURITY [™] FG WO WHITE MINERAL OIL 10



0000001225			
Version 2.7		Revision Date 2022/08/16	Print Date 2022/08/16
		3.1 cSt (100 °C / 212 °F)	
Explosive properties	:	: Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.	

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact	
Ingestion	
Inhalation	
Skin contact	

Acute toxicity

|--|

Acute oral toxicity	: Remarks: No data available
Acute inhalation toxicity	: Remarks: No data available
Acute dermal toxicity	: Remarks: No data available

Components:

White mineral oil (petroleum Acute oral toxicity	i):	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks	:	No data available
---------	---	-------------------

Serious eye damage/eye irritation

Product:

PURITY [™] FG WO WHITE MINERAL OIL 10

000003001229

Version 2.7

Print Date 2022/08/16

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradability	ity	
Product:		
Biodegradability	:	Remarks: No data available
Bioaccumulative potential		
No data available		
Mobility in soil		
No data available		
Other adverse effects		
No data available		

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues
- : The product should not be allowed to enter drains, water



PURITY [™] FG WO WHITE MINERAL OIL 10

000003001229



Version 2.7	Revision Date 2022/08/16	Print Date 2022/08/16
	courses or the soil. Offer surplus and non-recyclable disposal company. Waste must be classified and lab disposal. Send to a licensed waste manage Dispose of product residue in acc of the person responsible for was	elled prior to recycling or ement company. cordance with the instructions

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm. For more information go to www.P65Warnings.ca.gov.		
The components of this product are reported in the following inventories:				
DSL	:	On the inventory, or in compliance with the inventory		
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		
EINECS	:	On the inventory, or in compliance with the inventory		
IECSC	:	On the inventory, or in compliance with the inventory		
AICS	:	On the inventory, or in compliance with the inventory		
KECI	:	On the inventory, or in compliance with the inventory		
PICCS	:	On the inventory, or in compliance with the inventory		
NZIoC	:	On the inventory, or in compliance with the inventory		
	:	HSNO: HSR002605, Lubricants (Low Hazard) Group Standard 2020		

PURITY [™] FG WO WHITE MINERAL OIL 10

000003001229


Version 2.7

Print Date 2022/08/16

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH NIOSH REL		USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits
OSHA P0		USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA OSHA Z-1 / TWA		8-hour time weighted average 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50

PURITY [™] FG WO WHITE MINERAL OIL 10

000003001229

Version 2.7

Revision Date 2022/08/16

- Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/08/16 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/08/16