DURON TM/MC SAE 30

000003000460

Version 2.6

Revision Date 2022/07/06



Print Date 2022/07/06

SECTION 1. IDENTIFICATION

Product name :	DURON TM/MC SAE 30		
Product code :	DUR3IBC, DUR3P5R, DUR3P20, DUR3DRR, DUR3DRM, DUR3DCT, DUR3C16, DUR3C12, DUR3, DUR3BLK		
Manufacturer or supplier's det			
Telephone :	Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555		
Emergency telephone number			
Emergency telephone num- : ber	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).		
Recommended use of the chemical and restrictions on use			
Recommended use :	DURON single grade oils are intended for use in diesel and spark ignition engines according to the specific viscosity grade and performance level for each grade of product. They may also be used for wet clutch and gear type transmissions and hydraulic systems in line with equipment builder specifica- tions.		
Prepared by :	Product Safety: +1 905-491-0565		

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

DURON TM/MC SAE 30

000003000460

Version 2.6

Revision Date 2022/07/06

Print Date 2022/07/06

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50, hy- drotreated neutral oil-based, high- viscosity; Baseoil — unspecified	72623-85-9	50 - 70
Lubricating oils (petroleum), C20-50, hy- drotreated neutral oil-based; Baseoil — unspecified	72623-87-1	30 - 50
Lubricating oils (petroleum), C15-30, hy- drotreated neutral oil-based; Baseoil — unspecified	72623-86-0	10 - 20
Zinc alkyldithiophosphate	113706-15-3	1 - 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

lf inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.



DURON TM/MC SAE 30

000003000460



Version 2.6		Revision Date 2022/07/06	Print Date 2022/07/06
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire	with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxi oxides (SOx), phosphorus oxides (POx (H2S), zinc oxides (ZnOx), metal oxide smoke and irritating vapours as produc bustion.	x), sulphur compounds s, hydrocarbons,
Further information	:	Prevent fire extinguishing water from co water or the ground water system.	ontaminating surface

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun-

DURON TM/MC SAE 30

000003000460

PETRO-CANADA

Version 2.6

Revision Date 2022/07/06

Print Date 2022/07/06

light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified	72623-85-9	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-87-1	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-86-0	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.

DURON TM/MC SAE 30

000003000460



Version 2.6		Revision Date 2022/07/06	Print Date 2022/07/06
Eye protection	:	Wear face-shield and protective suit problems.	for abnormal processing
Skin and body protection	:	Choose body protection in relation to tration and amount of dangerous su cific work-place.	
Protective measures	:	Wash contaminated clothing before	re-use.
Hygiene measures	:	Remove and wash contaminated clo ing the inside, before re-use. Wash face, hands and any exposed handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	amber
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-30 °C (-22 °F) No data available
Flash point	:	249 °C (480 °F) Method: Cleveland open cup
Fire Point	:	265 °C (509 °F)
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available

DURON TM/MC SAE 30

000003000460



Version 2.6		Revision Date 2022/07/06	Print Date 2022/07/06
Density	:	0.8754 kg/l (15 °C / 59 °F)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	91.6 cSt (40 °C / 104 °F) 11.2 cSt (100 °C / 212 °F)	
Explosive properties	:	Do not pressurize, cut, weld, braze, so pose containers to heat or sources of i	

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, H2S, methacrylate monomers, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of e	exposure
Eye contact Ingestion Inhalation Skin contact	
Acute toxicity	
Product:	
Acute oral toxicity :	Remarks: No data available
Acute inhalation toxicity :	Assessment: The substance or mixture has no acute inhala- tion toxicity Remarks: No data available
Acute dermal toxicity :	Assessment: The substance or mixture has no acute dermal toxicity Remarks: No data available
<u>Components:</u>	
	20-50, hydrotreated neutral oil-based, high-viscosity;
Baseoil — unspecified: Acute oral toxicity :	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity :	LC50 (Rat): > 5.2 mg/l
Internet: lubricants.petro-canada.com/sds	Page: 6

DURON TM/MC SAE 30

000003000460



sion 2.6	Revision Date 2022/07/06	Print Date 2022/07/0
50112.0		
	Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Lubricating oils (petroleur	n), C20-50, hydrotreated neutral oil-b	ased; Baseoil — unspeci-
fied:		•
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l	
	Exposure time: 4 h Test atmosphere: dust/mist	
• • • • • •		
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Lubricating oils (petroleun fied:	n), C15-30, hydrotreated neutral oil-b	oased; Baseoil — unspeci-
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l	
	Exposure time: 4 h	
	Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation		
Product:		
Pomarke	 No data available 	
Remarks	: No data available	
Remarks Serious eye damage/eye ir		
Serious eye damage/eye ir		
Serious eye damage/eye ir <u>Product:</u>	ritation : No data available	
Serious eye damage/eye ir <u>Product:</u> Remarks	ritation : No data available	
Serious eye damage/eye ir <u>Product:</u> Remarks Respiratory or skin sensiti	ritation : No data available	
Serious eye damage/eye ir <u>Product:</u> Remarks Respiratory or skin sensiti No data available	ritation : No data available	
Serious eye damage/eye ir Product: Remarks Respiratory or skin sensiti No data available Germ cell mutagenicity	ritation : No data available	
Serious eye damage/eye in <u>Product:</u> Remarks Respiratory or skin sensiti No data available Germ cell mutagenicity No data available	ritation : No data available	
Serious eye damage/eye in Product: Remarks Respiratory or skin sensiti No data available Germ cell mutagenicity No data available Carcinogenicity	ritation : No data available	
Serious eye damage/eye in <u>Product:</u> Remarks Respiratory or skin sensiti No data available Germ cell mutagenicity No data available Carcinogenicity No data available	ritation : No data available	
Serious eye damage/eye in Product: Remarks Respiratory or skin sensiti No data available Germ cell mutagenicity No data available Carcinogenicity No data available Reproductive toxicity	ritation : No data available	
Serious eye damage/eye in Product: Remarks Respiratory or skin sensiti No data available Germ cell mutagenicity No data available Carcinogenicity No data available Reproductive toxicity No data available	ritation : No data available	
Serious eye damage/eye in Product: Remarks Respiratory or skin sensiti No data available Germ cell mutagenicity No data available Carcinogenicity No data available Reproductive toxicity No data available STOT - single exposure	rritation : No data available isation	

DURON TM/MC SAE 30

000003000460

Version 2.6



Print Date 2022/07/06

SECTION 12. ECOLOGICAL INFORMATION

	Ecotoxicity		
	Product:		
	Toxicity to fish	:	Remarks: No data available
	Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
	Toxicity to algae/aquatic plants	:	Remarks: No data available
	Toxicity to microorganisms	:	Remarks: No data available
	Persistence and degradabili	ty	
	Product:		
	Biodegradability	:	Remarks: No data available
	Bioaccumulative potential		
	No data available		
	Mobility in soil		
	No data available		
	Other adverse effects		
	No data available		
-			

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from residues : The product should not be allowed to enter drains, wat courses or the soil.	
Offer surplus and non-recyclable solutions to a license posal company. Waste must be classified and labelled prior to recycling disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the inst of the person responsible for waste disposal.	to a licensed dis- r to recycling or npany. with the instructions

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

DURON TM/MC SAE 30

000003000460

Version 2.6

Revision Date 2022/07/06



Print Date 2022/07/06


49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65 benzene		This product contains chemical(s) known to the State of Cali- fornia to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include: 71-43-2
•		et are reported in the following inventories:
DSL	•	On the inventory, or in compliance with the inventory
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION





HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

		USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL		USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

DURON TM/MC SAE 30

000003000460



Version 2.6	Revision Date 2022/07/06	Print Date 2022/07/06
NIOSH REL / TWA	: Time-weighted average concentrat workday during a 40-hour workwee	
NIOSH REL / STEL	: STEL - 15-minute TWA exposure t at any time during a workday	
OSHA P0 / TWA OSHA Z-1 / TWA	 8-hour time weighted average 8-hour time weighted average 	

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/07/06 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

DURON TM/MC SAE 30

000003000460

Version 2.6

Revision Date 2022/07/06

Print Date 2022/07/06

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

