DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

SECTION 1. IDENTIFICATION

Product name : DURON TM/MC SHP 15W-40

Product code : DSHP15CBE, DSHP15BLK, DSHP15P5R, DSHP15DRR,

DSHP15ICT, DSHP15C16, DSHP15C12, DSHP15P20, DSHP15DRM, DSHP15IBC, DSHP15DCT, DSHP15

Manufacturer or supplier's details

Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300

Dallas TX 75201 United States

Telephone: 1-214-871-3555

Emergency telephone number

Emergency telephone num-

: CHEMTREC: 1-800-424-9300;

ber

Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : DURON SHP 15W-40 is a superior quality heavy duty engine

oil meeting global standards for high speed 4-stroke diesel engines. It can also be used in other applications including a wide range of compression and spark ignition engines, wet

clutch transmissions and hydraulic systems.

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or con-

firmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	30 - 50
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified	72623-87-1	30 - 50
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified	72623-85-9	30 - 50
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0	30 - 50
reaction mass of isomers of: C7-9-alkyl 3- (3,5-di-tert-butyl-4- hydroxyphenyl)propionate	125643-61-0	1 - 5
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	1 - 5
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified	64742-70-7	1 - 5
Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified	64742-56-9	1 - 5
Zinc alkyldithiophosphate	113706-15-3	1 - 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

First aider needs to protect himself.

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

delayed

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during fire-

fighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion prod- :

ucts

Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), sulphur compounds (H2S), zinc oxides (ZnOx), metal oxides, hydrocarbons, smoke and irritating vapours as products of incomplete com-

bustion.

Further information Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

If the product contaminates rivers and lakes or drains inform **Environmental precautions**

respective authorities.

Methods and materials for containment and cleaning up Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : None known.

fire and explosion

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

Page: 3 / 11

Petro-Canada Lubricants is a HF Sinclair brand

SAFETY DATA SHEET DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep tightly closed in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sun-

light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hy-	64742-54-7	TWA (Inhal-	5 mg/m3	ACGIH
drotreated heavy paraffinic;		able particu-		
Baseoil — unspecified		late matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum),	72623-87-1	TWA (Inhal-	5 mg/m3	ACGIH
C20-50, hydrotreated neutral		able particu-		
oil-based; Baseoil — unspeci-		late matter)		
fied				
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum),	72623-85-9	TWA (Inhal-	5 mg/m3	ACGIH
C20-50, hydrotreated neutral		able particu-		
oil-based, high-viscosity; Baseoil — unspecified		late matter)		
<u> </u>		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum),	72623-86-0	TWA (Inhal-	5 mg/m3	ACGIH
C15-30, hydrotreated neutral	72020 00 0	able particu-	o mg/mo	7.00111
oil-based; Baseoil — unspeci-		late matter)		
fied				
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent-	64742-65-0	TWA (Inhal-	5 mg/m3	ACGIH
dewaxed heavy paraffinic;		able particu-		
Baseoil — unspecified		late matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

		ST (Mist)	10 mg/m3	NIOSH REL
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified	64742-70-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent- dewaxed light paraffinic; Baseoil — unspecified	64742-56-9	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

Colour light brown

Odour Mild petroleum oil like.

Odour Threshold No data available

pΗ No data available

Pour point -36 °C (-33 °F) Boiling point/boiling range No data available

Flash point 226 °C (439 °F)

Method: Cleveland open cup

Fire Point 247 °C (477 °F)

Evaporation rate No data available

Flammability Low fire hazard. This material must be heated before ignition

will occur.

Auto-Ignition Temperature No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

: No data available Vapour pressure Relative vapour density No data available

Relative density No data available

: 0.8662 kg/l (15 °C / 59 °F) Density

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 113.9 cSt (40 °C / 104 °F)

15.4 cSt (100 °C / 212 °F)

Do not pressurize, cut, weld, braze, solder, drill, grind or ex-Explosive properties

pose containers to heat or sources of ignition.

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- :

tions

Hazardous polymerisation does not occur.

Stable under normal conditions.

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

Page: 6 / 11

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents and reducing agents.

Hazardous decomposition

products

May release COx, H2S, smoke and irritating vapours when

heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Eye contact Inhalation Ingestion

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No data available

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci-

fied:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity;

Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci-

fied:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

LC50 (Rat): > 5.2 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity LD50 (Rabbit): > 5,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks No data available

Serious eye damage/eye irritation

Product:

Remarks No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65 This product contains chemical(s) known to the State of Cali-

fornia to cause cancer and/or to cause birth defects or other

reproductive harm. For more information go to

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. Page: 9 / 11 Petro-Canada Lubricants is a HF Sinclair brand

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

www.P65Warnings.ca.gov. The chemicals include:

benzene 71-43-2

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the


TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency

DURON TM/MC SHP 15W-40



000003005463

Version 2.12 Revision Date 2022/07/19 Print Date 2022/07/19

Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

United States, telephone: 1-800-268-5850; fax: 1-800-201-

6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2022/07/19 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN