# DURON <sup>™/MC</sup> UHP 5W-30

#### 000003002355

Version 3.4

Revision Date 2022/07/06



Print Date 2022/07/06

### SECTION 1. IDENTIFICATION

	DURON TMMC UHP 5W-30
:	RDL-3669
:	DUHP53DCT, DUHP53, DUHP53C20, DUHP53BOX, DUHP53BLK, DUHP53P5R, DUHP53DRR, DUHP53ICT, DUHP53IBC, DUHP53DRM, DUHP53P20, DUHP53C16, DUHP53C12
deta	ails Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States
:	1-214-871-3555
ber	
:	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
hen	nical and restrictions on use
:	A synthetic, SAE 5W-30 Heavy Duty Diesel Engine Oil de- signed to meet API CK-4 standards. It is suitable for most 4- stroke engines operating on diesel, gasoline or natural gas fuel in mobile equipment. The low sulphated ash, phosphorus and sulphur design helps to protect emission control equip- ment such as particulate filters and catalytic converters and SCRs.
:	Product Safety: +1 905-491-0565
	deta ber

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

# DURON <sup>™/MC</sup> UHP 5W-30

### 000003002355

PETRO CANADA

Version 3.4

Revision Date 2022/07/06

Print Date 2022/07/06

by NTP.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy	64742-54-7	70 - 90
paraffinic; Baseoil — unspecified		
Lubricating oils (petroleum), C15-30, hy-	72623-86-0	50 - 70
drotreated neutral oil-based; Baseoil —		
unspecified		
Dec-1-ene, oligomers, hydrogenated	68037-01-4	5 - 10
Lubricating oils (petroleum), C20-50, hy-	72623-87-1	5 - 10
drotreated neutral oil-based; Baseoil —		
unspecified		
Distillates (petroleum), hydrotreated light	64742-55-8	1 - 5
paraffinic; Baseoil — unspecified		
Distillates (petroleum), solvent-dewaxed	64742-65-0	1 - 5
heavy paraffinic; Baseoil — unspecified		
Phenol, tetrapropylene-, sulfurized, car-	122384-87-6	1 - 5
bonates, calcium salts, overbased		
bis(nonylphenyl)amine	36878-20-3	1 - 5
Distillates (petroleum), solvent-dewaxed	64742-56-9	1 - 5
light paraffinic; Baseoil — unspecified		
Zinc alkyldithiophosphate	113706-15-3	1 - 5
Actual concentration is withhold as a trade		

Actual concentration is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.

# DURON <sup>™/MC</sup> UHP 5W-30

#### 000003002355



 Version 3.4
 Revision Date 2022/07/06
 Print Date 2022/07/06

 Most important symptoms
 : First aider needs to protect himself.

Most important symptoms : First aider needs to and effects, both acute and delayed

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), sulphur compounds (H2S), zinc oxides (ZnOx), metal oxides, hydrocarbons, smoke and irritating vapours as products of incomplete com- bustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

#### SECTION 7. HANDLING AND STORAGE

	Advice on protection against ire and explosion	:	None known.
A	Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. In case of insufficient ventilation, wear suitable respiratory
erne	et: lubricants.petro-canada.com/s	ds	Page: 3 / 11

# DURON TM/MC UHP 5W-30

### 000003002355



Version 3.4	Revision Date 2022/07/06	Print Date 2022/07/06
Conditions for safe storage	<ul> <li>equipment.</li> <li>Avoid contact with skin, eyes and Do not ingest.</li> <li>Keep away from heat and sources Keep container closed when not i</li> <li>Store in original container.</li> <li>Containers which are opened muscle kept upright to prevent leakage.</li> <li>Keep in a dry, cool and well-ventil Keep in properly labelled container</li> </ul>	clothing. s of ignition. n use. st be carefully resealed and lated place. ers.
	To maintain product quality, do no light.	or store in near of direct sun-

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Distillates (petroleum), hy- drotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-86-0	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-87-1	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hy- drotreated light paraffinic; Baseoil — unspecified	64742-55-8	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1

# DURON <sup>™/MC</sup> UHP 5W-30

### 000003002355

Version 3.4

#### Revision Date 2022/07/06

Print Date 2022/07/06

		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent-	64742-56-9	TWA (Inhal-	5 mg/m3	ACGIH
dewaxed light paraffinic;		able particu-		
Baseoil — unspecified		late matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL

**Engineering measures** 

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

r oroenar preteotive equipm	0	
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection		
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton <sup>®</sup> .
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Protective measures	:	Wash contaminated clothing before re-use.
Hygiene measures	:	Remove and wash contaminated clothing and gloves, includ- ing the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	brown
Odour	:	Mild petroleum oil like.



# DURON TM/MC UHP 5W-30

### 000003002355



rsion 3.4		Revision Date 2022/07/06	Print Date 2022/07/06
Odour Threshold	:	No data available	
рН	:	No data available	
Pour point Boiling point/boiling range	:	-45 °C (-49 °F) No data available	
Flash point	:	215 °C (419 °F) Method: Cleveland open cup	
Fire Point	:	235 °C (455 °F)	
Evaporation rate	:	No data available	
Flammability	:	Low fire hazard. This material me will occur.	ust be heated before ignition
Auto-Ignition Temperature	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	0.8563 kg/l (15 °C / 59 °F)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	70.3 cSt (40 °C / 104 °F)	
		11.9 cSt (100 °C / 212 °F)	
Explosive properties	:	Do not pressurize, cut, weld, bra pose containers to heat or sourc	

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- : tions	Hazardous polymerisation do Stable under normal conditior	
Conditions to avoid :	No data available	
Incompatible materials :	Reactive with oxidising agents	S.
Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.		Page: 6 / 11 Petro-Canada Lubricants is a HF Sinclair brand

# DURON <sup>™/MC</sup> UHP 5W-30

#### 000003002355



Version 3.4

Revision Date 2022/07/06

Print Date 2022/07/06

Hazardous decomposition : May release COx, H2S, smoke and irritating vapours when heated to decomposition.

#### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure				
Eye contact Ingestion Inhalation Skin contact				
Acute toxicity				
Product:				
Acute oral toxicity	:	Remarks: No data available		
Acute inhalation toxicity	:	Remarks: No data available		
Acute dermal toxicity	:	Remarks: No data available		
Components:				
Lubricating oils (petroleur fied:	m), C	15-30, hydrotreated neutral oil-based; Baseoil — unspeci-		
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,		
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci-				
fied: Acute oral toxicity	÷	LD50 (Rat): > 5,000 mg/kg,		
Acute inhalation toxicity		LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,		
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:</b> Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,				
Acute oral toxicity	·	LD50 (Rat). > 5,000 mg/kg,		
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg,		
Skin corrosion/irritation				
Product:				
Remarks	:	No data available		

# DURON <sup>™/MC</sup> UHP 5W-30

#### 000003002355

Version 3.4

Revision Date 2022/07/06



Print Date 2022/07/06

### Serious eye damage/eye irritation

### Product:

Remarks

: No data available

#### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

#### Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradabili	tv	
	LÀ	
Product:	Ly	
_	:	Remarks: No data available
Product:	•	Remarks: No data available
Product: Biodegradability	•	Remarks: No data available
Product: Biodegradability Bioaccumulative potential	•	Remarks: No data available
Product: Biodegradability Bioaccumulative potential No data available	•	Remarks: No data available

No data available

# DURON <sup>™/MC</sup> UHP 5W-30

#### 000003002355

Version 3.4



Print Date 2022/07/06

#### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Offer surplus and non-recyclable solutions to a licensed disposal company.</li> <li>Waste must be classified and labelled prior to recycling or disposal.</li> <li>Send to a licensed waste management company.</li> <li>Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.</li> </ul>

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### **National Regulations**

#### 49 CFR

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

California Prop. 65	This product contains chemical(s) known to the State of Cali- fornia to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include:		
benzene	71-43-2		
The components of this product are reported in the following inventories:			
DSL :	On the inventory, or in compliance with the inventory		
TSCA :	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		

#### **SECTION 16. OTHER INFORMATION**


#### Further information

# DURON <sup>™/MC</sup> UHP 5W-30

### 000003002355

PETRO-CANADA

Version 3.4



### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH NIOSH REL OSHA P0	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / STEL	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA OSHA Z-1 / TWA	:	8-hour time weighted average 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New

### DURON <sup>™/MC</sup> UHP 5W-30

#### 000003002355

Version 3.4

Revision Date 2022/07/06

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/07/06 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/07/06