SUPREME ^{™/MC} HIGH MILEAGE 10W-30



000003008913 Version 3.4 Revision Date 2022/08/18 Print Date 2022/08/19 **SECTION 1. IDENTIFICATION** Product name : SUPREME ^{™/MC} HIGH MILEAGE 10W-30 Product code : MOHM13C20, MOHM13IBC, MOHM13DRM, MOHM13C16, MOHM13C12, MOHM13BLK, MOHM13B6U, MOHM13 Manufacturer or supplier's details Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 **United States** Telephone : 1-214-871-3555 **Emergency telephone number** Emergency telephone num- : CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for ber emergency number(s).

Recommended use of the chemical and restrictions on use			
Recommended use	: A passenger car engine oil for use in vehicles with higher mileage fueled with gasoline, E85, propane or CNG meeting the latest API and ILSAC (if applicable) requirements.		
Prepared by	: Product Safety: +1 905-491-0565		

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
ΝΤΡ	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

SUPREME TM/MC HIGH MILEAGE 10W-30

000003008913

Version 3.4

Revision Date 2022/08/18 Print Date 2022/08/19

CAS-No.	Concentration (% w/w)
72623-87-1	60 - 70
72623-86-0	20 - 30
64742-54-7	5 - 10
	72623-87-1 72623-86-0

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Internet: lubricants.petro-canada.com/s	sds	Page: 2 /

Trademarks are owned or used under license.



SUPREME ^{™/MC} HIGH MILEAGE 10W-30



000003008913 Version 3.4 Revision Date 2022/08/18 Print Date 2022/08/19

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
------------	---------	------------------------	---------------------------------------	-------

SUPREME TM/MC HIGH MILEAGE 10W-30

000003008913

Version 3.4

Print Date 2022/08/19

		exposure)	concentration	
Lubricating oils (petroleum),	72623-87-1	TWA (Inhal-	5 mg/m3	ACGIH
C20-50, hydrotreated neutral		able particu-		
oil-based; Baseoil — unspeci-		late matter)		
fied				
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum),	72623-86-0	TWA (Inhal-	5 mg/m3	ACGIH
C15-30, hydrotreated neutral		able particu-	-	
oil-based; Baseoil — unspeci-		late matter)		
fied				
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hy-	64742-54-7	TWA (Inhal-	5 mg/m3	ACGIH
drotreated heavy paraffinic;		able particu-	_	
Baseoil — unspecified		late matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Engineering measures :		fficient to control	ments. Good general worker exposure to a	
Personal protective equipmer	nt			
Respiratory protection :	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.			

Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Protective measures	:	Wash contaminated clothing before re-use.



SUPREME TM/MC HIGH MILEAGE 10W-30



000003008913

Version 3.4	Revision Date 2022/08/18	Print Date 2022/08/19
Hygiene measures	: Remove and wash contaminated ing the inside, before re-use. Wash face, hands and any expose handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	amber
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-42 °C (-44 °F) No data available
Flash point	:	206 °C (403 °F) Method: Pensky-Martens closed cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8619 kg/l (15 °C / 59 °F)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity Viscosity, kinematic	:	68.1 cSt (40 °C / 104 °F)
		10.5 cSt (100 °C / 212 °F)

SUPREME TM/MC HIGH MILEAGE 10W-30



000003008913

Version 3.4	Revision Date 2022/08/18	Print Date 2022/08/19	
Explosive properties	: Do not pressurize, cut, weld, braz pose containers to heat or source		

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents and reducing agents.
Hazardous decomposition products	:	May release COx, NOx, SOx, POx, H2S, metal oxides, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely route Eye contact Ingestion Inhalation Skin contact	es of	exposure		
Acute toxicity				
Product:				
Acute oral toxicity	:	Remarks: No data available		
Acute inhalation toxicity	:	Remarks: No data available		
Acute dermal toxicity	:	Remarks: No data available		
Components:				
Lubricating oils (petroleun fied:	n), C	20-50, hydrotreated neutral oil-based; Baseoil — unspeci-		
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,		
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,		
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci- fied:				
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,		
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,		

SUPREME TM/MC HIGH MILEAGE 10W-30



sion 3.4		Revision Date 2022/08/18	Print Date 2022/08
Distillates (petroleum), hyd	drotr	eated heavy paraffinic; Baseoil —	unspecified:
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation			
Product:			
Remarks	:	No data available	
Serious eye damage/eye ir	ritati	on	
Product:			
Remarks	:	No data available	
Respiratory or skin sensiti	satio	on	
No data available			
Germ cell mutagenicity			
No data available			
Carcinogenicity			
No data available			
Reproductive toxicity			
No data available			
STOT - single exposure			
No data available			
STOT - repeated exposure			
No data available			

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradability		
Product:		

Biodegradability	:	Remarks: No data available
------------------	---	----------------------------



SUPREME TM/MC HIGH MILEAGE 10W-30

000003008913

Version 3.4

Revision Date 2022/08/18

Print Date 2022/08/19

Bioaccumulative potential No data available Mobility in soil No data available Other adverse effects No data available SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal.
	Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65	This product contains chemical(s) known to the State of Cali- fornia to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include:			
benzene	71-43-2			
The components of this product are reported in the following inventories:				
DSL :	On the inventory, or in compliance with the inventory			
TSCA :	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.			



SUPREME ^{™/MC} HIGH MILEAGE 10W-30




000003008913

Version 3.4 Revision Date 2022/08/18 Print Date 2022/08/19

IECSC

On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION



OSHA P0 / TWA:8-hour time weighted averageOSHA Z-1 / TWA:8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - In-

SUPREME ^{™/MC} HIGH MILEAGE 10W-30

000003008913

Version 3.4

Revision Date 2022/08/18

ternational Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/08/18 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/08/19