PURITY TM/MC FG2 SYNTHETIC



000003001183

Version 2.11

Revision Date 2022/08/10

SECTION 1. IDENTIFICATION

Product name :	PURITY TMMC FG2 SYNTHETIC
Product code :	PFGSYN2AL2, PFGSYN2AL1, PFGSYN2P17, PFGSYN2KGL, PFGSYN2DRL, PFGSYN2, PFGSYN2C30
Manufacturer or supplier's det Telephone :	tails Petro-Canada America Lubricants LLC 2828 N. Harwood St., Suite 1300 Dallas TX 75201 United States 1-214-871-3555
Emergency telephone number Emergency telephone num- : ber	
Recommended use of the che	mical and restrictions on use
Recommended use :	Purity FG2 Synthetic grease is a food grade lubricant.
	NSF H1 Registered.
	All components comply with FDA 21 CFR 178.3570 "Lubri- cants with Incidental Food Contact". It is intended for applica- tion on industrial and food equipment. It should not be added directly to the food product.
Prepared by :	Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

PURITY TM/MC FG2 SYNTHETIC

000003001183

Version 2.11

Revision Date 2022/08/10

Print Date 2022/08/10

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), solvent-refined	64741-88-4	20 - < 30
heavy paraffinic; Baseoil — unspecified		
calcium carbonate	471-34-1	20 - < 30
calcium dodecylbenzenesulphonate	26264-06-2	1 - < 2.5
Benzenamine, N-phenyl-, reaction prod-	68411-46-1	1 - < 2.5
ucts with 2,4,4-trimethylpentene		
A stud concentration is withhold on a trade		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.



PURITY TM/MC FG2 SYNTHETIC





Version 2.11		Revision Date 2022/08/10	Print Date 2022/08/10
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire	with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and products of incomplete combustion.	irritating vapours as
Further information	:	Prevent fire extinguishing water from converter or the ground water system.	ontaminating surface

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

PURITY TM/MC FG2 SYNTHETIC



Version 2.11

Revision Date 2022/08/10

Print Date 2022/08/10

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
Distillates (petroleum), solvent- refined heavy paraffinic; Baseoil — unspecified	64741-88-4	exposure) TWA (Inhal- able particu- late matter)	concentration 5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
	474.04.4	ST (Mist)	10 mg/m3	NIOSH REL
calcium carbonate	471-34-1	TWA (Res- pirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Engineering measures		fficient to control	nents. Good general worker exposure to a	
Personal protective equipmer	nt			
Respiratory protection	ventilation is that exposure Respirator se exposure lev	provided or expo es are within reco election must be	ess adequate local e psure assessment dep ommended exposure based on known or a of the product and the respirator.	monstrates guidelines. nticipated
Filter type	organic vapo	ur filter		
Hand protection Material	neoprene, nit	rile, polyvinyl alc	ohol (PVA), Viton [®] .	
Remarks	approved sta	ndard should be	s gloves complying v worn at all times whe sessment indicates th	en handling
Eye protection	Wear face-sh problems.	Wear face-shield and protective suit for abnormal processing problems.		
Skin and body protection		mount of danger	ation to its type, to the ous substances, and	
Protective measures	Wash contan	ninated clothing b	pefore re-use.	
Hygiene measures	ing the inside	Remove and wash contaminated clothing and gloves, includ- ing the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.		



PURITY TM/MC FG2 SYNTHETIC

000003001183

Version 2.11

Revision Date 2022/08/10



Print Date 2022/08/10

Appearance	:	Semi-solid.
Colour	:	tan
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-63 °C (-81 °F)Base Fluid Blend
Boiling point/boiling range	:	No data available
Flash point	:	252 °C (486 °F) Method: Cleveland open cup Base Fluid Blend
Fire Point	:	286 °C (547 °F) Base Fluid Blend
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignit will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9568 kg/l (15 °C / 59 °F)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity Viscosity, kinematic	:	50 cSt (40 °C / 104 °F) Base Fluid Blend
		7.8 cSt (100 °C / 212 °F) Base Fluid Blend

PURITY TM/MC FG2 SYNTHETIC



000003001183

Version 2.11		Revision Date 2022/08/10	Print Date 2022/08/10
Explosive properties	:	Do not pressurize, cut, weld, braz pose containers to heat or source	
SECTION 10. STABILITY AND R	EAC	TIVITY	
Possibility of hazardous reac	- :	Hazardous polymerisation does r Stable under normal conditions.	not occur.

tions		Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, SOx, CaOx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Eye contact Ingestion Inhalation Skin contact Acute toxicity	f exposure			
Product:				
Acute oral toxicity	: Remarks: No data available			
Acute inhalation toxicity	Remarks: No data available			
Acute dermal toxicity	Remarks: No data available			
Components: Distillates (petroleum), solv Acute oral toxicity Acute dermal toxicity calcium carbonate: Acute oral toxicity	nt-refined heavy paraffinic; Baseoil — unsp LD50 (Rat): > 5,000 mg/kg, LD50 (Rabbit): > 5,000 mg/kg, LD50 (Rat): > 2,000 mg/kg,	ecified:		
·	LD30 (Rat). > 2,000 Hig/kg,			
Skin corrosion/irritation				
<u>Product:</u> Remarks	No data available			
Serious eye damage/eye irritation				
<u>Product:</u> Remarks	No data available			
Remarks	No data available			

PURITY ^{™/MC} FG2 SYNTHETIC

000003001183

Version 2.11

Print Date 2022/08/10

Respiratory or skin sensitisation

Product:

Result: Not a skin sensitizer.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradabili	ty	
<u>Product:</u> Biodegradability	:	Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

PURITY TM/MC FG2 SYNTHETIC

000003001183

Version 2.11

Revision Date 2022/08/10



Print Date 2022/08/10

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm. For more information go to www.P65Warnings.ca.gov.
The components of this product are reported in the following inventories:		
DSL	:	On the inventory, or in compliance with the inventory
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
EINECS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
AICS	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory

PURITY TM/MC FG2 SYNTHETIC

000003001183



Version 2.11	Revision Date 2022/08/10	Print Date 2022/08/10
NZIoC	: On the inventory, or in compliance	with the inventory

: HSNO: HSR002605, Lubricants (Low Hazard) Group Standard 2020

SECTION 16. OTHER INFORMATION

Further information

NFPA 704: HMIS® IV: Flammability HEALTH FLAMMABILITY 1 Health Instability 0 1 **PHYSICAL HAZARD** 0 HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents Special hazard a chronic hazard, while the "/" represents the absence of a chronic hazard. Full text of other abbreviations

		USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL		USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification

PURITY TM/MC FG2 SYNTHETIC

000003001183

Version 2.11

Revision Date 2022/08/10

System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/08/10 yyyy/mm/dd

the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN



Print Date 2022/08/10