According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:	Print Date: 07/03/2020
1.2	03/27/2020	800010016440	Date of last issue: 02/29/2016

SECTION 1. IDENTIFICATION

Product name	:	Pennzoil Platinum Gear 75W-90

Product code : 001F1400

Manufacturer or supplier's details

Manufacturer/Supplier	:	Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA
SDS Request Customer Service	:	(+1) 877-276-7285

Emergency telephone number

Spill Information	: 877-504-9351
Health Information	: 877-242-7400

Recommended use of the chemical and restrictions on use : Transmission oil.

Recommended use

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200				
Long-term (chronic) aquatic : hazard	Category 3			
GHS label elements				
Hazard pictograms :	No symbol			
Signal word :	No signal word			
Hazard statements :	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with long lasting effects.			
Precautionary statements :	Prevention: P273 Avoid release to the environment.			
	Response: No precautionary phrases.			
	Storage:			
	No precautionary phrases.			

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:	Print Date: 07/03/2020
1.2	03/27/2020	800010016440	Date of last issue: 02/29/2016

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

:

Chemical nature

Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Distillates (petrole- um), hydrotreated light	Distillates (pe- troleum), hy- drotreated light	64742-47-8	< 3
Alkyl amine	Amines, C12- 14-tert-alkyl	68955-53-3	< 0.5
Alkenyl amine		Not Assigned	< 0.5
Alcohols, C12-14, ethoxylated	Alcohols, C12- 14. ethoxylated (>5 EO <15)	68439-50-9	< 0.5

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version 1.2	Revision Date: 03/27/2020		OS Number: 0010016440	Print Date: 07/03/2020 Date of last issue: 02/29/2016
Pro	otection of first-aiders	:		ring first aid, ensure that you are wearing the onal protective equipment according to the nd surroundings.
Indication of any immediate medical attention and special treatment needed		:	Treat symptoma	tically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version 1.2	Revision Date: 03/27/2020	SDS Number: 800010016440	Print Date: 07/03/2020 Date of last issue: 02/29/2016		
		see Chapter 8	of this Safety Data Sheet.		
		this Safety Dat	n disposal of spilled material see Chapter 13 of a Sheet.		
SECTION 7. HANDLING AND STORAGE					

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

· · · · ·				
Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
			leis / Permissible	
		exposure)	concentration	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Ŭ	TWA (Inhal-	5 mg/m3	ACGIH
		able particu-	Ŭ	
		late matter)		

Biological occupational exposure limits

No biological limit allocated.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:
1.2	03/27/2020	800010016440

Print Date: 07/03/2020 Date of last issue: 02/29/2016

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use.
		In accordance with good industrial hygiene practices, precau- tions should be taken to avoid breathing of material.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version 1.2	Revision Date: 03/27/2020	SDS Number: 800010016440	Print Date: 07/03/2020 Date of last issue: 02/29/2016
		tions to a level select respirate cific conditions Check with res Where air-filter priate combina Select a filter s	controls do not maintain airborne concentra- which is adequate to protect worker health, ory protection equipment suitable for the spe- of use and meeting relevant legislation. piratory protective equipment suppliers. ing respirators are suitable, select an appro- tion of mask and filter. uitable for the combination of organic gases and particles [Type A/Type P boiling point].
	I protection		
R	emarks	gloves approve US: F739) may suitable chemi gloves Suitabil usage, e.g. fre sistance of glo glove suppliers Personal hygie Gloves must o gloves, hands cation of a nor For continuous through time o 480 minutes w short-term/spla recognize that may not be ave time maybe ac and replaceme a good predict dependent on Glove thickness	ontact with the product may occur the use of ed to relevant standards (e.g. Europe: EN374, de from the following materials may provide cal protection. PVC, neoprene or nitrile rubber ity and durability of a glove is dependent on quency and duration of contact, chemical re- ve material, dexterity. Always seek advice from s. Contaminated gloves should be replaced. ene is a key element of effective hand care. Inly be worn on clean hands. After using should be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. a contact we recommend gloves with break- f more than 240 minutes with preference for > here suitable gloves can be identified. For ash protection we recommend the same but suitable gloves offering this level of protection ailable and in this case a lower breakthrough ceptable so long as appropriate maintenance ent regimes are followed. Glove thickness is not or of glove resistance to a chemical as it is the exact composition of the glove material. s should be typically greater than 0.35 mm the glove make and model.
Eye ç	protection		andled such that it could be splashed into eyes, wear is recommended.
Skin	and body protection	work clothes.	is not ordinarily required beyond standard ice to wear chemical resistant gloves.
Prote	ective measures		ctive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.
Therr	mal hazards	: Not applicable	
Envi	ronmental exposure o	controls	
Gene	eral advice	vant environm	ate measures to fulfill the requirements of rele- ental protection legislation. Avoid contamination nent by following advice given in Section 6. If
		6 / 16	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version 1.2	Revision Date: 03/27/2020		S Number: 0010016440	Print Date: 07/03/2020 Date of last issue: 02/29/2016
			charged to waste municipal or indus discharge to surfa Local guidelines of	nt undissolved material from being dis- water. Waste water should be treated in a strial waste water treatment plant before ace water. on emission limits for volatile substances I for the discharge of exhaust air containing
SECTION	9. PHYSICAL AND CHE	ΞΜΙΟ	CAL PROPERTIE	8
Appea	arance	:	liquid	
Colou	r	:	Clear amber	
Odour	r	:	Slight hydrocarbo	on
Odour	Threshold	:	Data not availabl	e
pН		:	Not applicable	
pour p	point	:	-42 °C / -44 °F Method: ASTM [097
Initial range	boiling point and boiling	:	> 280 °C / 536 °F estimated value(
Flash	point	:	229 °C / 444 °F	
			Method: ASTM E	092 (COC)
Evapo	pration rate	:	Data not availabl	e
Flamn	nability (solid, gas)	:	Data not availabl	e
	explosion limit / upper ability limit	:	Typical 10 %(V)	
	explosion limit / Lower ability limit	:	Typical 1 %(V)	
Vapou	ur pressure	:	< 0.5 Pa (20 °C /	68 °F)
			estimated value(s)
Relati	ve vapour density	:	> 1 estimated value(s)
Relati	ve density	:	0.869 (15 °C / 59) °F)
Densi	ty	:	869 kg/m3 (15.0 Method: ASTM [
	ility(ies) ater solubility	:	negligible	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Vers 1.2	sion	Revision Date: 03/27/2020		S Number: 0010016440	Print Date: 07/03/2020 Date of last issue: 02/29/2016
	Sol	ubility in other solvents	:	Data not availab	e
		on coefficient: n- I/water	:	log Pow: > 6 (based on inform	ation on similar products)
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	=
	Decom	position temperature	:	Data not availab	e
	Viscos Vise	ity cosity, dynamic	:	Data not availab	e
	Vise	cosity, kinematic	:	108 mm2/s (40.0) °C / 104.0 °F)
				Method: ASTM [0445
				15.3 mm2/s (100) °C / 212 °F)
				Method: ASTM E	0445
	Explos	ive properties	:	Not classified	
	Oxidizi	ng properties	:	Data not availab	le
	Condu	ctivity	:	This material is r	not expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a
		the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:	Print Date: 07/03/2020
1.2	03/27/2020	800010016440	Date of last issue: 02/29/2016

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity :	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity :	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity :	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Alkyl amine:

Remarks: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation. May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:	Print Date: 07/03/2020
1.2	03/27/2020	800010016440	Date of last issue: 02/29/2016

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity	
Product:	
	: Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product: Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

ersion 2	Revision Date: 03/27/2020	-	0S Number: 0010016440	Print Date: 07/03/2020 Date of last issue: 02/29/2016
Basis for assessment		:	for this product. Information given and the ecotoxico Unless indicated of tive of the product ponent(s).(LL/EL/	data have not been determined specifically is based on a knowledge of the components logy of similar products. otherwise, the data presented is representa- t as a whole, rather than for individual com- IL50 expressed as the nominal amount of o prepare aqueous test extract).
Ecoto	oxicity			
<u>Produ</u> Toxici ty)	ict: ty to fish (Acute toxici-	:	Remarks: LL/EL/I Harmful	L50 10-100 mg/l
	ty to daphnia and other ic invertebrates (Acute y)	:	Remarks: LL/EL/I Harmful	L50 10-100 mg/l
Toxici icity)	ty to algae (Acute tox-	:	Remarks: LL/EL/I Harmful	L50 10-100 mg/l
Toxici icity)	ty to fish (Chronic tox-	:	Remarks: Data no	ot available
	ty to daphnia and other c invertebrates (Chron- city)	:	Remarks: Data no	ot available
	ty to microorganisms e toxicity)	:	Remarks: Data no	ot available
<u>Comp</u>	oonents:			
Alken	yl amine:			
M-Fac icity)	ctor (Acute aquatic tox-	:	1	
M-Fac toxicity	ctor (Chronic aquatic y)	:	10	
Persis	stence and degradabil	ity		
<u>Produ</u>	<u>ict:</u>			
Biode	gradability	:	Major constituents	dily biodegradable. s are inherently biodegradable, but contains may persist in the environment.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Vers 1.2	sion	Revision Date: 03/27/2020	SDS Number: 800010016440		Print Date: 07/03/2020 Date of last issue: 02/29/2016
	Bioaco	cumulative potential			
	Produ	<u>ct:</u>			
	Bioacc	umulation	:	Remarks: Contains components with the potential to bioac- cumulate.	
	Mobili	ty in soil			
	Produ	<u>ct:</u>			
	Mobility		:	: Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.	
				Remarks: Floats on water.	
	Other	adverse effects			
	Produ	<u>ct:</u>			
	Additic mation	nal ecological infor-	:	ozone creation po Product is a mixtu	one depletion potential, photochemical otential or global warming potential. Ire of non-volatile components, which will not in any significant quantities under normal
				Poorly soluble mize Causes physical f	xture. ouling of aquatic organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:
1.2	03/27/2020	800010016440

Print Date: 07/03/2020 Date of last issue: 02/29/2016

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated light

64742-47-8

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:	Print Date: 07/03/2020
1.2	03/27/2020	800010016440	Date of last issue: 02/29/2016

Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7

64742-47-8

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated light

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

ACGIH OSHA Z-1 ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms		USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants 8-hour, time-weighted average 8-hour time weighted average The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
		ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:	Print Date: 07/03/2020
1.2	03/27/2020	800010016440	Date of last issue: 02/29/2016
		EC = Europear EC50 = Effectiv ECETOC = Europe GHA = Europe EINECS = The Chemical Subse EL50 = Effectiv ENCS = Japan Inventory EWC = Europe GHS = Globally Labelling of Ch IARC = Internat IC50 = Inhibitor IL50 = Inhibitor IMDG = Internat INV = Chinese IP346 = Institut determination of KECI = Korea II LC50 = Lethal LD50 = Lethal LL/EL/IL = Leth LL50 = Lethal LL50 = Lethal UN = Chinese IP346 = Institut determination of KECI = Korea II CS0 = Lethal LD50 = Lethal LD50 = Lethal LC50 = Lethal EL50 = Lethal INV = Chinese IP346 = Institut determination of KECI = Korea II CS0 = Lethal CS0 = Lethal INV = Chinese IC50 = Lethal CS0 = CS0	ve Concentration fifty ropean Center on Ecotoxicology and Toxicolo- ls ean Chemicals Agency European Inventory of Existing Commercial stances re Loading fifty ese Existing and New Chemical Substances an Waste Code y Harmonised System of Classification and emicals tional Agency for Research on Cancer tional Agency for Research on Cancer tional Air Transport Association ry Concentration fifty y Level fifty ational Maritime Dangerous Goods Chemicals Inventory te of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. hal Loading/Effective Loading/Inhibitory loading Loading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume ent, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical eted No Effect Concentration istration Evaluation And Authorisation Of ons Relating to International Carriage of Dan-

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to	:	The quoted data are from, but not limited to, one or more
compile the Safety Data		sources of information (e.g. toxicological data from Shell
Sheet		Health Services, material suppliers' data, CONCAWE, EU
		IUCLID date base, EC 1272 regulation, etc).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Pennzoil Platinum Gear 75W-90

Version	Revision Date:	SDS Number:	Print Date: 07/03/2020
1.2	03/27/2020	800010016440	Date of last issue: 02/29/2016

Revision Date : 03/27/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN